

Kupfer-Aderendhülsen ohne Isolation

DIN 46228, Teil 1, ausgenommen*

Embouts de fil en cuivre sans isolation

DIN 46228, partie 1, excepté*

Uninsulated copper ferrules

DIN 46228, part 1, except*

Werkstoff:

E-CU = Elektrolytkupfer

Oberflächenbehandlung: Code
 bl = blank (0)
 ag = versilbert (1)
 sn = verzinkt (7)

Matière:

E-CU = cuivre électrolytique

Traitements de surface: Code
 bl = brut (0)
 ag = argenté (1)
 sn = étamé (7)

Material:

E-CU = electrolytic copper

Surface-plating: Code
 bl = clean (0)
 ag = silver-plated (1)
 sn = tin-plated (7)

Bestellbeispiel:
 Exemple de commande:
 Example of order:

440005.47
 (4400/05 CU sn)



mm ² (AWG)	Artikel-Nr. Numéro d'article Part-No.	DIN 46 228/1	øD1 mm	øD2 mm	L1 mm	S mm	Stand- Packg.	Werkzeuge Outils Tools	mm ² (AWG)	Artikel-Nr. Numéro d'article Part-No.	DIN 46 228/1	øD1 mm	øD2 mm	L1 mm	S mm	Stand- Packg.	Werkzeuge Outils Tools									
0.1-0.3 (26-24)	440005.4() *	*	0.8	1.7	5	0.15	5000	3984H 4517 4536 4542	6 (10)	440710.4() *	6-10	3.5	4.7	10	0.2	1000	3984J 4521 4523N 4526N 4531 4536 4542									
	440007.4() *		0.8	1.7	7	0.15	5000			440712.4() *		6-12	3.5	4.7	12	0.2		1000	440715.4() *	6-15	3.5	4.7	15	0.2	1000	440718.4() *
0.5 (22)	440106.4() *	0.5-6	1	2.1	6	0.15	5000	3984H 4518N 4523N 4527 4531 4536 4542	10 (8)	440812.4() *	10-12	4.5	5.8	12	0.2	1000	3984J 4521 4522 4526N									
	440108.4() *		1	2.1	8	0.15	5000			440815.4() *		10-15	4.5	5.8	15	0.2		1000	440818.4() *	10-18	4.5	5.8	18	0.2	1000	
	440110.4() *	0.5-10	1	2.1	10	0.15	5000		440820.4() *	*	4.5	5.8	20	0.2	1000	3984J 4522 4526N										
	440112.4() *		1	2.1	12	0.15	5000		440825.4() *		* 4.5	5.8	25	0.2	1000											
0.75 (20)	440206.4() *	0.75-6	1.2	2.3	6	0.15	5000	3984H 4518N 4521 4523N 4527 4531 4536 4542	16 (6)	440912.4() *	16-12	5.8	7.5	12	0.2	1000	3984J 4522 4526N									
	440208.4() *		1.2	2.3	8	0.15	5000			440915.4() *		16-15	5.8	7.5	15	0.2		1000								
	440210.4() *	0.75-10	1.2	2.3	10	0.15	5000		440918.4() *	*	5.8	7.5	18	0.2	1000	3984J 4522 4526N										
	440212.4() *		1.2	2.3	12	0.15	5000		440920.4() *		16-18	5.8	7.5	20	0.2		1000									
1 (18)	440306.4() *	1-6	1.4	2.5	6	0.15	5000	3984H 4518N 4521 4523N 4527 4531 4536 4542	25 (4)	440925.4() *	16-25	5.8	7.5	25	0.2	1000	4522 4538N 4539N									
	440308.4() *		1.4	2.5	8	0.15	5000			440930.4() *		* 5.8	7.5	30	0.2	1000										
	440310.4() *	1-10	1.4	2.5	10	0.15	5000		440932.4() *	16-32	5.8	7.5	32	0.2	1000											
	440312.4() *		1.4	2.5	12	0.15	5000		441012.4() *		*	7.3	9.5	12	0.2	1000										
440320.4() *	1.4	2.5	20	0.15	2000	441015.4() *	25-15	7.3	9.5	15		0.2	1000													
1.5 (16)	440406.4() *	*	1.7	2.8	6	0.15	5000	3984H 4518N 4521 4523N 4527 4531 4536 4542	35 (2)	441112.4() *	*	8.3	11	12	0.2	500	4522 4538N									
	440407.4() *		1.5-7	1.7	2.8	7	0.15			5000		441115.4() *	* 8.3	11	15	0.2		500								
	440408.4() *	1.7		2.8	8	0.15	5000		441118.4() *	35-18	8.3	11	18	0.2	500											
	440410.4() *	1.5-10	1.7	2.8	10	0.15	5000		441120.4() *		* 8.3	11	20	0.2	500											
	440412.4() *		1.5-12	1.7	2.8	12	0.15		5000	441125.4() *	35-25	8.3	11	25	0.2	500										
	440415.4() *	1.7		2.8	15	0.15	5000		441130.4() *	* 8.3		11	30	0.2	500											
	440418.4() *	1.5-18	1.7	2.8	18	0.15	5000		441132.4() *	35-32	8.3	11	32	0.2	500											
	440420.4() *		1.7	2.8	20	0.15	2000																			
2.5 (14)	440506.4() *	*	2.2	3.4	6	0.15	5000	3984H 4521 4523N 4531 4536 4542	50 (1/0)	441218.4() *	50-18	10.3	13	18	0.3	500	4537 4539N									
	440507.4() *		2.5-7	2.2	3.4	7	0.15			5000		441220.4() *	* 10.3	13	20	0.3		500								
	440508.4() *	2.2		3.4	8	0.15	5000		441222.4() *	*	10.3	13	22	0.3	500											
	440510.4() *	2.5-10	2.2	3.4	10	0.15	2000		441225.4() *		50-25	10.3	13	25	0.3	500										
	440512.4() *		2.5-12	2.2	3.4	12	0.15		2000	441230.4() *		* 10.3	13	30	0.3	500										
	440515.4() *	2.2		3.4	15	0.15	2000		441232.4() *	50-32	10.3	13	32	0.3	500											
	440518.4() *	2.5-18	2.2	3.4	18	0.15	2000		441322.4() *		*	12.5	15	22	0.4	100										
	440520.4() *		2.2	3.4	20	0.15	2000		441325.4() *	* 12.5		15	25	0.4	100											
	440530.4() *	2.2	3.4	30	0.15	2000	441332.4() *		* 12.5	15	32	0.4	100													
	4 (12)	440608.4() *	*	2.8	4	8	0.2		2000	3984H 4521 4523N 4531 4536 4542	70 (2/0)	441425.4() *	*	14.5	17	25	0.4	100	4537							
440609.4() *		4-9		2.8	4	9	0.2	2000	441432.4() *			* 14.5		17	32	0.4	100									
440610.4() *			2.8	4	10	0.2	2000	441425.4() *	*		14.5	17	25	0.4	100											
440612.4() *		4-12	2.8	4	12	0.2	2000	441432.4() *			* 14.5	17	32	0.4	100											
440615.4() *			4-15	2.8	4	15	0.2	2000	441425.4() *		*	14.5	17	25	0.4	100										
440618.4() *		4-18	2.8	4	18	0.2	2000	441432.4() *	* 14.5			17	32	0.4	100											
440620.4() *			2.8	4	20	0.2	1000	441425.4() *	*		14.5	17	25	0.4	100											
440630.4() *		2.8	4	30	0.2	1000	441432.4() *	* 14.5			17	32	0.4	100												