Product Environmental Profile

Harmony Industrial PC








General information

Representative product	Harmony Industrial PC - HMIBSCEA53D1L0T
Description of the product	IIoT Edge Box Core eMMC DC Linux TPM
Description of the range	Harmony iPCs (formerly known as Magelis iPC) and Edge Box run at the Edge Control level of Ecostruxure, the Schneider Electric IIoT architecture. They enable secured communication from shop floor to IT, improving profitability and offering new business opportunities through enhanced asset performance for more efficient operation and maintenance of capital assets. They offer smart application design and engineering to leverage asset performance, with end-to-end cybersecurity. The environmental impacts of this referenced product are representative of the impacts of the other products of the range which are developed with a similar technology.
Functional unit	Harmony iPC and Edge Box offer an Industrial design, operating within a 0-55°C temperature range for 10 years and consuming 15,8W/5,2W in active/standby mode.

Constituent materials



E Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 2 January 2013, amended in March 2015, 2015/863/EU and in November 2017, 2017/2102/EU) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers – PBDE), Bis (2-ethylhexyl)phthalate - DEHP, Benzyl butyl phthalate– BBP, Dibutyl phthalate - DBP, Disobutyl phthalate - DIBP) as mentioned in the Directive.


Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page

Additional environmental information

	The Harmony Industrial PC presents the following relevent environmental aspects					
Manufacturing	Manufactured at a production site complying with the regulations					
	Weight and volume of the packaging optimized, based on the European Union's packaging directive					
Distribution	Packaging weight is 263,2 g, consisting of Cardboard (72%), polystyrene (28%)					
	Product distribution optimised by setting up local distribution centres					
Use	1 Battery BR2032 to be changed every 5 years					
	End of life optimized to decrease the amount of waste and allow recovery of the product components and materials					
	This product contains Battery (1,2g), electronic card (170g) that should be separated from the stream of waste so as to optimize end-of-life treatment.					
End of life	The location of these components and other recommendations are given in the End of Life Instruction document which is available on the Schneider-Electric Green Premium website					
	http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page					
	Recyclability potential:77%Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).					

Reference life time	10 years					
Product category	Other equipments - Active product					
Installation elements	cable, connectors, screws					
Use scenario	The product is in active mode 55 time with a power use of 5,19W t	•	use of 15,8W and in idle	phase 45% of the		
Geographical representativeness	Europe, US, Asia					
Technological representativeness	IIoT Edge Box Core eMMC DC Linux TPM					
	Manufacturing	Installation	Use	End of life		
Energy model used	Energy model used: Taiwan	Electricity mix; AC; consumption mix, at consumer; 100V; JP	Electricity mix; AC; consumption mix, at consumer; 100V; JP	Electricity mix; AC; consumption mix, at consumer; 100V; JP		

Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	2.48E-03	2.46E-03	0*	0*	1.82E-05	0*
Contribution to the soil and water acidification	$kg SO_2 eq$	4.98E-01	7.09E-02	7.05E-04	7.20E-05	4.26E-01	3.63E-04
Contribution to water eutrophication	kg PO4 ³⁻ eq	1.10E-01	1.55E-02	1.62E-04	4.00E-05	9.41E-02	1.35E-04
Contribution to global warming	kg $\rm CO_2$ eq	4.41E+02	3.13E+01	1.54E-01	0*	4.09E+02	3.51E-01
Contribution to ozone layer depletion	kg CFC11 eq	8.87E-05	1.58E-05	0*	0*	7.28E-05	1.41E-08
Contribution to photochemical oxidation	kg C_2H_4 eq	7.27E-02	4.98E-03	5.03E-05	0*	6.77E-02	3.45E-05
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m3	6.80E+02	1.08E-01	0*	0*	6.80E+02	0*
Total Primary Energy	MJ	7.49E+03	4.00E+02	2.18E+00	0*	7.08E+03	1.69E+00



Manufacturing Distribution Installation Use End of life

r	ıa	OI	iire	

Optional indicators		Harmony In	dustrial PC - HM	IBSCEA53D1L	_0T		
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to fossil resources depletion	MJ	4.65E+03	3.51E+02	2.17E+00	0*	4.29E+03	1.37E+00
Contribution to air pollution	m³	2.92E+04	1.99E+03	6.57E+00	0*	2.72E+04	1.20E+01
Contribution to water pollution	m³	2.78E+04	4.08E+03	2.54E+01	0*	2.37E+04	1.93E+01
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Use of secondary material	kg	5.70E-01	5.70E-01	0*	0*	0*	0*
Total use of renewable primary energy resources	MJ	5.11E+02	5.72E+00	0*	0*	5.05E+02	0*
Total use of non-renewable primary energy resources	MJ	6.98E+03	3.94E+02	2.18E+00	0*	6.58E+03	1.69E+00
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	5.07E+02	1.88E+00	0*	0*	5.05E+02	0*
Use of renewable primary energy resources used as raw material	′ MJ	3.84E+00	3.84E+00	0*	0*	0*	0*
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	6.97E+03	3.88E+02	2.18E+00	0*	6.58E+03	1.69E+00
Use of non renewable primary energy resources used as raw material	MJ	5.95E+00	5.95E+00	0*	0*	0*	0*
Use of non renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Use of renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Waste categories	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life

ENVPEP2003021_V1

Hazardous waste disposed	kg	1.42E+01	4.65E+00	0*	0*	8.18E+00	1.39E+00
Non hazardous waste disposed	kg	1.20E+02	1.33E+01	0*	6.28E-02	1.06E+02	0*
Radioactive waste disposed	kg	8.91E-01	9.99E-03	0*	0*	8.81E-01	0*
Other environmental information	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Materials for recycling	kg	1.07E+00	1.07E-01	0*	2.07E-01	0*	7.51E-01
Materials for recycling Components for reuse	kg kg	1.07E+00 0.00E+00	1.07E-01 0*	0* 0*	2.07E-01 0*	0* 0*	7.51E-01 0*
, ,	-					-	

* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.8.1, database version 2016-11 in compliance with ISO14044.

The use phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

According to this environmental analysis, proportionality rules may be used to evaluate the impacts of other products of this range.

Depending on the impact analysis and with exception of the mineral resource depletion indicator, other environmental indicators of other products in this family may be proportionnal extrapolated by energy consumption values.

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Registration number		ENVPEP2003021 V1	Draf	ting rules	PCR-ed3-EN-2015 04 02
Registration number			Diai	ing rules	1 01(-603-211-2013 04 02
Date of issue		03/2020			
Validity period		5 years		mation and reference ments	www.pep-ecopassport.org
Independent verificat	tion of the	e declaration and data			
Internal	х	External			
The elements of the present PEP cannot be compared with elements from another program.					
Document in complia environmental labelli		ISO 14021:2016 « Environmer	ntal labels and decl	arations - Self-declare	d environmental claims (Type II

Schneider Electric Industries SAS

Country Customer Care Center http://www.schneider-electric.com/contact

35, rue Joseph Monier CS 30323 F- 92506 Rueil Malmaison Cedex RCS Nanterre 954 503 439 Capital social 896 313 776 €

www.schneider-electric.com	Published by Schneider Electric
ENVPEP2003021_V1	© 2020 - Schneider Electric – All rights reserved

03/2020