


# Product Environmental Profile

## Lexium Integrated Drive ILS with Gearbox





## General information

### Representative product

Lexium Integrated Drive ILS with Gearbox - ILS1F852S1415, IFS92 - VRDM3910 (4,0 Nm) motor with PLE 80 -012 Uni gearbox.

### Description of the product

The main purpose of the Lexium Integrated Drive ILS product range is to control the variation of the rotational speed and position of a stepper electric motor.

### Description of the range

This range consists of integrated drives ILS with stepper motors with ratings from 3.8A to 5A for operation on 24 V to 36 V, DC-Supply with gearboxes

The environmental impacts of this referenced product are representative of the impacts of the other products of the range which are developed with a similar technology.

### Functional unit


To coordinate and synchronize motion control with stepper, servo or burshless DC motor 70% of the time for 10 years.



## Constituent materials

### Reference product mass

7060 g including the product, its packaging and additional elements and accessories



Plastics	3,7%
Metals	84,2%
Others	12,2%



## Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 2 January 2013, amended in March 2015, 2015/863/EU and in November 2017, 2017/2102/EU) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers – PBDE), Bis (2-ethylhexyl)phthalate - DEHP, Benzyl butyl phthalate– BBP, Dibutyl phthalate - DBP, Diisobutyl phthalate - DIBP) as mentioned in the Directive.

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website

<http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page>

## Additional environmental information


The Lexium Integrated Drive ILS with Gearbox presents the following relevant environmental aspects

<b>Manufacturing</b>	Manufactured at a Schneider Electric production site ISO14001 certified
<b>Distribution</b>	Weight and volume of the packaging optimized, based on the European Union's packaging directive Packaging weight is 773,5 g, consisting of cardboard (93,7%), PE film (5,1%), paper (1,2%) Product distribution optimised by setting up local distribution centres
<b>Installation</b>	ILS1F852S1449 does not require any installation operations.
<b>Use</b>	The product does not require special maintenance operations.
<b>End of life</b>	End of life optimized to decrease the amount of waste and allow recovery of the product components and materials  This product contains five electronic cards (95,6g) that should be separated from the stream of waste so as to optimize end-of-life treatment.  The location of these components and other recommendations are given in the End of Life Instruction document which is available on the Schneider-Electric Green Premium website  <a href="http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page">http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page</a>  Recyclability potential: <b>86%</b> Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).

## Environmental impacts

<b>Reference life time</b>	10 years			
<b>Installation elements</b>	No special components needed			
<b>Use scenario</b>	The use scenario is: - Active phase: consumed power 32 W during 40 % uptime - Standby phase: consumed power 15 W during 30 % uptime - Off phase: consumed power 0 W during 30 % uptime - 24 hours per day, during 10 years			
<b>Geographical representativeness</b>	Europe			
<b>Technological representativeness</b>	The main purpose of the Lexium Integrated Drive ILS product range is to control the variation of the rotational speed and position of a stepper electric motor.			
<b>Energy model used</b>	<b>Manufacturing</b>	<b>Installation</b>	<b>Use</b>	<b>End of life</b>
	Energy model used: Germany	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27

Compulsory indicators		Lexium Integrated Drive ILS with Gearbox - ILS1F852S1415, IFS92 - VRDM3910 (4,0 Nm) motor with PLE 80 -012 Uni gearbox.					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	3,31E-03	3,25E-03	0*	0*	6,45E-05	0*
Contribution to the soil and water acidification	kg SO <sub>2</sub> eq	3,20E+00	1,01E-01	4,16E-03	0*	3,10E+00	1,86E-03
Contribution to water eutrophication	kg PO <sub>4</sub> <sup>3-</sup> eq	2,04E-01	1,57E-02	9,58E-04	5,84E-05	1,87E-01	4,71E-04
Contribution to global warming	kg CO <sub>2</sub> eq	7,83E+02	3,89E+01	9,11E-01	0*	7,43E+02	7,58E-01
Contribution to ozone layer depletion	kg CFC11 eq	5,87E-05	1,03E-05	0*	0*	4,84E-05	4,28E-08
Contribution to photochemical oxidation	kg C <sub>2</sub> H <sub>4</sub> eq	1,81E-01	1,03E-02	2,97E-04	0*	1,70E-01	1,98E-04
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m3	2,69E+03	3,94E-01	0*	0*	2,69E+03	0*
Total Primary Energy	MJ	1,57E+04	8,50E+02	1,29E+01	0*	1,48E+04	9,30E+00



Optional indicators								Lexium Integrated Drive ILS with Gearbox - ILS1F852S1415, IFS92 - VRDM3910 (4,0 Nm) motor with PLE 80-012 Uni gearbox.							
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	
Contribution to fossil resources depletion	MJ	8,82E+03	3,75E+02	1,28E+01	0*	8,43E+03	7,47E+00								
Contribution to air pollution	m <sup>3</sup>	4,10E+04	8,97E+03	3,87E+01	0*	3,20E+04	6,58E+01								
Contribution to water pollution	m <sup>3</sup>	3,31E+04	2,24E+03	1,50E+02	6,53E+00	3,06E+04	7,44E+01								
<b>Resources use</b>	<b>Unit</b>	<b>Total</b>	<b>Manufacturing</b>	<b>Distribution</b>	<b>Installation</b>	<b>Use</b>	<b>End of Life</b>	<b>Unit</b>	<b>Total</b>	<b>Manufacturing</b>	<b>Distribution</b>	<b>Installation</b>	<b>Use</b>	<b>End of Life</b>	
Use of secondary material	kg	2,06E+00	2,06E+00	0*	0*	0*	0*								
Total use of renewable primary energy resources	MJ	1,91E+03	2,48E+01	0*	0*	1,89E+03	0*								
Total use of non-renewable primary energy resources	MJ	1,38E+04	8,25E+02	1,29E+01	0*	1,29E+04	9,29E+00								
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	1,90E+03	1,04E+01	0*	0*	1,89E+03	0*								
Use of renewable primary energy resources used as raw material	MJ	1,44E+01	1,44E+01	0*	0*	0*	0*								
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	1,38E+04	8,13E+02	1,29E+01	0*	1,29E+04	9,29E+00								
Use of non renewable primary energy resources used as raw material	MJ	1,23E+01	1,23E+01	0*	0*	0*	0*								
Use of non renewable secondary fuels	MJ	0,00E+00	0*	0*	0*	0*	0*								
Use of renewable secondary fuels	MJ	0,00E+00	0*	0*	0*	0*	0*								
<b>Waste categories</b>	<b>Unit</b>	<b>Total</b>	<b>Manufacturing</b>	<b>Distribution</b>	<b>Installation</b>	<b>Use</b>	<b>End of Life</b>	<b>Unit</b>	<b>Total</b>	<b>Manufacturing</b>	<b>Distribution</b>	<b>Installation</b>	<b>Use</b>	<b>End of Life</b>	
Hazardous waste disposed	kg	6,81E+01	6,04E+01	0*	0*	3,87E-01	7,30E+00								
Non hazardous waste disposed	kg	2,79E+03	2,34E+01	0*	0*	2,77E+03	0*								
Radioactive waste disposed	kg	1,86E+00	1,46E-02	0*	0*	1,85E+00	0*								
<b>Other environmental information</b>	<b>Unit</b>	<b>Total</b>	<b>Manufacturing</b>	<b>Distribution</b>	<b>Installation</b>	<b>Use</b>	<b>End of Life</b>	<b>Unit</b>	<b>Total</b>	<b>Manufacturing</b>	<b>Distribution</b>	<b>Installation</b>	<b>Use</b>	<b>End of Life</b>	
Materials for recycling	kg	6,85E+00	6,86E-01	0*	7,35E-01	0*	5,43E+00								
Components for reuse	kg	0,00E+00	0*	0*	0*	0*	0*								
Materials for energy recovery	kg	5,30E-02	0*	0*	0*	0*	5,30E-02								
Exported Energy	MJ	8,71E-03	6,63E-03	0*	2,08E-03	0*	0*								

\* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.8.1, database version 2016-11 in compliance with ISO14044.

The use phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

According to this environmental analysis, proportionality rules may be used to evaluate the impacts of other products of this range.

Depending on the impact analysis, the environmental indicators (without "contribution to mineral resources depletion") of other products in this family may be proportional extrapolated by energy consumption values". For the Mineral resources depletion, impact may be proportional extrapolated by mass of the product.

*Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.*

<i>Registration number</i>	ENVPEP1411002_V2	<i>Drafting rules</i>	PCR-ed3-EN-2015 04 02
<i>Date of issue</i>	11/2020		
<i>Validity period</i>	5 years	<i>Information and reference documents</i>	<a href="http://www.pep-ecopassport.org">www.pep-ecopassport.org</a>
<i>Independent verification of the declaration and data</i>			
Internal	X	External	
<i>The elements of the present PEP cannot be compared with elements from another program.</i>			
<i>Document in compliance with ISO 14021:2016 « Environmental labels and declarations - Self-declared environmental claims (Type II environmental labelling) »</i>			

Schneider Electric Industries SAS

Country Customer Care Center  
<http://www.schneider-electric.com/contact>

35, rue Joseph Monier  
CS 30323  
F- 92506 Rueil Malmaison Cedex  
RCS Nanterre 954 503 439  
Capital social 896 313 776 €

[www.schneider-electric.com](http://www.schneider-electric.com)

ENVPEP1411002\_V2

Published by Schneider Electric

© 2020 - Schneider Electric – All rights reserved

11/2020