


# Product Environmental Profile

## ClimaSys CA - Ventilation grills






## General information

Representative product	ClimaSys CA - Ventilation grills - NSYCAG125LPF
Description of the product	The main purpose of the Thermoplastic Rectangular ClimaSys CA-Ventilation grills or Air transfer is It is used when larger amounts of heat need to be evacuated in a polluted environment.Fans with filters are designed to evacuate a large amount of heat economically
Functional unit	"To transfer air for ventilation and air filtration and smoke exhaust of a building,for a connection cross-section of 1 dm <sup>2</sup> ,over the typical product lifetime of 17 years".



## Constituent materials

Reference product mass 246 g including the product, its packaging and additional elements and accessories



Plastics	64.9%
Metals	6.1%
Others	29.0%



## Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 2 January 2013, amended in March 2015, 2015/863/EU and in November 2017, 2017/2102/EU) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers – PBDE), Bis (2-ethylhexyl)phthalate - DEHP, Benzyl butyl phthalate– BBP, Dibutyl phthalate - DBP, Diisobutyl phthalate - DIBP) as mentioned in the Directive.

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website

<http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page>



## Additional environmental information

The ClimaSys CA - Ventilation grills presents the following relevant environmental aspects


<b>Manufacturing</b>	Manufactured at a Schneider Electric production site ISO14001 certified
<b>Distribution</b>	Weight and volume of the packaging optimized, based on the European Union's packaging directive Packaging weight is 68 g, consisting of Cardboard (96.3%), Paper (3.7%) Product distribution optimised by setting up local distribution centres
<b>Installation</b>	The product does not require special installation procedure and requires little to no energy to install. The disposal of the packaging materials are accounted for during the installation phase (including transport to disposal).
<b>Use</b>	The product does not require special maintenance operations.
<b>End of life</b>	End of life optimized to decrease the amount of waste and allow recovery of the product components and materials  No special end-of-life treatment required. According to countries' practices this product can enter the usual end-of-life treatment process.  Recyclability potential: <b>9%</b> <span style="float: right;">Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).</span>



## Environmental impacts

<b>Reference life time</b>	17 years			
<b>Installation elements</b>	No special installation components need during installation phase, but transport of packaging to disposal and disposal of packaging accounted for during installation.			
<b>Use scenario</b>	Non Applicable for Ventilation grills			
<b>Geographical representativeness</b>	Europe			
<b>Technological representativeness</b>	The Modules of Technologies such as material production, manufacturing process and transport technology used in this PEP analysis (LCA-EIME in this case) are Similar and representative of the actual type of technologies used to make the product in production.			
<b>Energy model used</b>	<b>Manufacturing</b>	<b>Installation</b>	<b>Use</b>	<b>End of life</b>
	Energy model used: France	Not Applicable	Not Applicable	Not Applicable

Compulsory indicators		ClimaSys CA - Ventilation grills - NSYCAG125LPF					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	8.89E-06	8.89E-06	9.77E-10	0*	0*	0*
Contribution to the soil and water acidification	kg SO <sub>2</sub> eq	3.02E-03	2.86E-03	1.11E-04	1.18E-05	0*	4.35E-05
Contribution to water eutrophication	kg PO <sub>4</sub> <sup>3-</sup> eq	5.89E-03	5.85E-03	2.57E-05	2.87E-06	0*	1.40E-05
Contribution to global warming	kg CO <sub>2</sub> eq	9.75E-01	9.16E-01	2.44E-02	2.83E-03	0*	3.16E-02
Contribution to ozone layer depletion	kg CFC11 eq	7.67E-08	7.56E-08	4.94E-11	0*	0*	1.05E-09
Contribution to photochemical oxidation	kg C <sub>2</sub> H <sub>4</sub> eq	2.75E-04	2.62E-04	7.95E-06	8.82E-07	0*	4.36E-06
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m3	2.60E-02	2.60E-02	0*	0*	0*	2.23E-05
Total Primary Energy	MJ	1.90E+01	1.84E+01	3.45E-01	3.70E-02	0*	2.03E-01



Optional indicators		ClimaSys CA - Ventilation grills - NSYCAG125LPF					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to fossil resources depletion	MJ	1.59E+01	1.53E+01	3.43E-01	3.67E-02	0*	1.64E-01
Contribution to air pollution	m³	4.79E+01	4.52E+01	1.04E+00	1.13E-01	0*	1.51E+00
Contribution to water pollution	m³	2.87E+02	2.80E+02	4.01E+00	4.29E-01	0*	2.02E+00
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Use of secondary material	kg	3.64E-03	3.64E-03	0*	0*	0*	0*
Total use of renewable primary energy resources	MJ	8.16E-01	8.15E-01	4.60E-04	0*	0*	2.23E-04
Total use of non-renewable primary energy resources	MJ	1.82E+01	1.76E+01	3.45E-01	3.69E-02	0*	2.03E-01
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	-1.85E-01	-1.86E-01	0*	0*	0*	0*
Use of renewable primary energy resources used as raw material	MJ	1.00E+00	1.00E+00	0*	0*	0*	0*
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	1.37E+01	1.32E+01	3.45E-01	3.69E-02	0*	2.03E-01
Use of non renewable primary energy resources used as raw material	MJ	4.46E+00	4.46E+00	0*	0*	0*	0*
Use of non renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Use of renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Waste categories	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Hazardous waste disposed	kg	9.04E-01	6.42E-01	0*	0*	0*	2.62E-01
Non hazardous waste disposed	kg	2.43E+00	2.43E+00	8.67E-04	3.84E-04	0*	6.20E-04
Radioactive waste disposed	kg	7.47E-04	7.46E-04	6.18E-07	7.56E-08	0*	1.01E-06
Other environmental information	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Materials for recycling	kg	8.27E-02	1.87E-02	0*	5.20E-02	0*	1.20E-02
Components for reuse	kg	0.00E+00	0*	0*	0*	0*	0*
Materials for energy recovery	kg	6.13E-03	0*	0*	0*	0*	6.13E-03
Exported Energy	MJ	1.65E-04	1.55E-05	0*	1.50E-04	0*	0*

\* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.9.1, database version 2016-11 in compliance with ISO14044.

The manufacturing phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Registration number :	SCHN-00646-V01.01-EN	Drafting rules	PCR-ed3-EN-2015 04 02
Verifier accreditation N°	VH39	Supplemented by	PSR-0008-ed2.0-EN-2018 02 09
Date of issue	02/2021	Information and reference documents	<a href="http://www.pep-ecopassport.org">www.pep-ecopassport.org</a>
		Validity period	5 years
Independent verification of the declaration and data, in compliance with ISO 14025 : 2010			
Internal		External	X
The PCR review was conducted by a panel of experts chaired by Philippe Osset (SOLINNEN)			
PEP are compliant with XP C08-100-1 :2016			
The elements of the present PEP cannot be compared with elements from another program.			
Document in compliance with ISO 14025 : 2010 « Environmental labels and declarations. Type III environmental declarations »			



Schneider Electric Industries SAS

Country Customer Care Center

<http://www.schneider-electric.com/contact>

35, rue Joseph Monier

CS 30323

F- 92506 Rueil Malmaison Cedex

RCS Nanterre 954 503 439

Capital social 896 313 776 €

[www.schneider-electric.com](http://www.schneider-electric.com)

Published by Schneider Electric

SCHN-00646-V01.01-EN

© 2019 - Schneider Electric – All rights reserved

02/2021