

Product Environmental Profile

Modicon ABLM Modular Regulated Power Supply






General information

Representative product	Modicon ABLM Modular Regulated Power Supply - ABLM1A24025
Description of the product	The ABLM Modular type meets all the needs of simple automation systems with power ratings from 10 to 60W and an output voltage of 5 V, 12 V or 24 VDC.
Description of the range	The Modicon electronic switch mode power supply offer is designed to provide the DC voltage necessary for the PLC and automation system equipment control circuits. Modicon switch mode power supplies are fully electronic and their output voltage is regulated. The use of electronics makes it possible to significantly improve the performance of these power supplies. The environmental impacts of this referenced product are representative of the impacts of the other products of the range which are developed with a similar technology.
Functional unit	To supply control circuits in industrial and building automation up to 6,5 W at 100% for 10 years.



Constituent materials

Reference product mass	217.3 g including the product, its packaging and additional elements and accessories
------------------------	--



Plastics	26,2%
Metals	1,6%
Others	72,2%

Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 2 January 2013, amended in March 2015, 2015/863/EU and in November 2017, 2017/2102/EU) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers – PBDE), Bis (2-ethylhexyl)phthalate - DEHP, Benzyl butyl phthalate– BBP, Dibutyl phthalate - DBP, Diisobutyl phthalate - DIBP) as mentioned in the Directive.

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website

<http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page>

Additional environmental information


The Modicon ABLM Modular Regulated Power Supply presents the following relevant environmental aspects

Manufacturing	Manufactured at a Schneider Electric production site ISO14001 certified
Distribution	Weight and volume of the packaging optimized, based on the European Union's packaging directive Packaging weight is 41.1 g, consisting of cardboard (76%) and paper (24%) Product distribution optimised by setting up local distribution centres
Installation	Modicon ABLM Modular Regulated power supply does not require any installation operations.
Use	The product does not require special maintenance operations.
End of life	End of life optimized to decrease the amount of waste and allow recovery of the product components and materials This product contains one electronic card (135g) That should be separated from the stream of waste so as to optimize end-of-life treatment by special treatments. that should be separated from the stream of waste so as to optimize end-of-life treatment. The location of these components and other recommendations are given in the End of Life Instruction document which is available on the Schneider-Electric Green Premium website http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page Recyclability potential: 12% Based on “ECO'DEEE recyclability and recoverability calculation method” (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).

Environmental impacts

Reference life time	10 years			
Installation elements	No special components needed			
Use scenario	The dissipated power depends on the conditions under which the product is implemented and used. This dissipated power is 6,5 W for the ABLM1A24025 product.			
Geographical representativeness	Europe			
Technological representativeness	The ABLM Modular type meets all the needs of simple automation systems with power ratings from 10 to 60W and an output voltage of 5 V, 12 V or 24 VDC.			
Energy model used	Manufacturing	Installation	Use	End of life
	Energy model used: Thailand	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27

Compulsory indicators		Modicon ABLM Modular Regulated Power Supply - ABLM1A24025					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	2,61E-04	2,37E-04	0*	0*	2,42E-05	0*
Contribution to the soil and water acidification	kg SO ₂ eq	1,17E+00	5,74E-03	1,28E-04	0*	1,16E+00	0*
Contribution to water eutrophication	kg PO ₄ ³⁻ eq	7,16E-02	1,28E-03	2,95E-05	0*	7,03E-02	5,74E-05
Contribution to global warming	kg CO ₂ eq	2,82E+02	3,07E+00	0*	0*	2,79E+02	1,87E-01
Contribution to ozone layer depletion	kg CFC11 eq	1,86E-05	4,57E-07	0*	0*	1,82E-05	6,35E-09
Contribution to photochemical oxidation	kg C ₂ H ₄ eq	6,46E-02	6,20E-04	9,14E-06	0*	6,39E-02	8,43E-06
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m3	1,01E+03	0*	0*	0*	1,01E+03	0*
Total Primary Energy	MJ	5,61E+03	3,79E+01	0*	0*	5,57E+03	0*



Optional indicators		Modicon ABLM Modular Regulated Power Supply - ABLM1A24025					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to fossil resources depletion	MJ	3,19E+03	2,66E+01	3,94E-01	0*	3,17E+03	3,65E-01
Contribution to air pollution	m ³	1,23E+04	3,26E+02	0*	0*	1,20E+04	3,22E+00
Contribution to water pollution	m ³	1,21E+04	5,83E+02	4,61E+00	0*	1,15E+04	7,64E+00
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Use of secondary material	kg	2,72E-03	2,72E-03	0*	0*	0*	0*
Total use of renewable primary energy resources	MJ	7,10E+02	1,60E+00	0*	0*	7,09E+02	0*
Total use of non-renewable primary energy resources	MJ	4,90E+03	3,63E+01	0*	0*	4,86E+03	0*
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	7,09E+02	8,14E-01	0*	0*	7,09E+02	0*
Use of renewable primary energy resources used as raw material	MJ	7,87E-01	7,87E-01	0*	0*	0*	0*
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	4,90E+03	3,33E+01	0*	0*	4,86E+03	0*
Use of non renewable primary energy resources used as raw material	MJ	3,01E+00	3,01E+00	0*	0*	0*	0*
Use of non renewable secondary fuels	MJ	0,00E+00	0*	0*	0*	0*	0*
Use of renewable secondary fuels	MJ	0,00E+00	0*	0*	0*	0*	0*

Waste categories	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Hazardous waste disposed	kg	1,09E+00	4,74E-01	0*	0*	1,45E-01	4,68E-01
Non hazardous waste disposed	kg	1,04E+03	5,25E-01	0*	0*	1,04E+03	0*
Radioactive waste disposed	kg	6,95E-01	5,19E-04	0*	0*	6,95E-01	0*
Other environmental information	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Materials for recycling	kg	7,45E-02	1,17E-02	0*	4,09E-02	0*	2,18E-02
Components for reuse	kg	0,00E+00	0*	0*	0*	0*	0*
Materials for energy recovery	kg	5,22E-02	0*	0*	0*	0*	5,22E-02
Exported Energy	MJ	5,89E-03	5,77E-03	0*	1,18E-04	0*	0*

* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.8.1, database version 2016-11 in compliance with ISO14044.

The use phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

According to this environmental analysis, proportionality rules may be used to evaluate the impacts of other products of this range.

Depending on the impact analysis, the environmental indicators (except "contribution to Mineral Resources Depletion") of other products in this family may be proportional extrapolated by energy consumption values". For Mineral Resources Depletion, impact may be proportional extrapolated by mass of the product.

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Registration number	ENVPEP2004005_V1	Drafting rules	PCR-ed3-EN-2015 04 02
Date of issue	03/2020	Supplemented by	PSR-0010-ed1.1-EN-2015 10 16
Validity period	5 years	Information and reference documents	www.pep-ecopassport.org
Independent verification of the declaration and data			
Internal	X	External	
The elements of the present PEP cannot be compared with elements from another program.			
Document in compliance with ISO 14021:2016 « Environmental labels and declarations - Self-declared environmental claims (Type II environmental labelling) »			

Schneider Electric Industries SAS

Country Customer Care Center
<http://www.schneider-electric.com/contact>

35, rue Joseph Monier
CS 30323
F- 92506 Rueil Malmaison Cedex
RCS Nanterre 954 503 439
Capital social 896 313 776 €

www.schneider-electric.com

ENVPEP2004005_V1

Published by Schneider Electric

© 2020 - Schneider Electric – All rights reserved

03/2020