


Product Environmental Profile

Modicon ABLP power supply






General information

Representative product	Modicon ABLP power supply - ABLP1A24045
Description of the product	The ABLP type meets all the needs of simple automation systems with power ratings from 100 to 240W and an output voltage of 12 or 24 VDC.
Description of the range	Modicon ABLP power supplies are designed to supply control circuits in industrial applications from 100W up to 240 W. The environmental impacts of this referenced product are representative of the impacts of the other products of the range which are developed with a similar technology.
Functional unit	To supply control circuits in commercial automation up to 240W at 100% for 10 years.



Constituent materials

Reference product mass	451,84 g including the product, its packaging and additional elements and accessories
------------------------	---



Plastics	5,7%
Metals	28,6%
Others	65,6%



Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 2 January 2013, amended in March 2015, 2015/863/EU and in November 2017, 2017/2102/EU) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers - PBDE), Bis (2-ethylhexyl)phthalate - DEHP, Benzyl butyl phthalate- BBP, Dibutyl phthalate - DBP, Diisobutyl phthalate - DIBP) as mentioned in the Directive.

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website

<http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page>



Additional environmental information

The Modicon ABLP power supply presents the following relevant environmental aspects


Manufacturing	Manufactured at a Schneider Electric production site ISO14001 certified
Distribution	Weight and volume of the packaging optimized, based on the European Union's packaging directive Packaging weight is 142,7 g, consisting of cardboard (94,2%), paper (5,8%) Product distribution optimised by setting up local distribution centres
Installation	ABLP1A24045 does not require any installation operations.
Use	The product does not require special maintenance operations.
End of life	End of life optimized to decrease the amount of waste and allow recovery of the product components and materials This product contains electronic card (146,4g) that should be separated from the stream of waste so as to optimize end-of-life treatment. The location of these components and other recommendations are given in the End of Life Instruction document which is available on the Schneider-Electric Green Premium website http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page Recyclability potential: 32% Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).



Environmental impacts

Reference life time	10 years			
Installation elements	No special components needed			
Use scenario	The dissipated power depends on the conditions under which the product is implemented and used.This dissipated power is 20 W for the ABLP1A24045 product.			
Geographical representativeness	Europe			
Technological representativeness	The ABLP type meets all the needs of simple automation systems with power ratings from 100 to 240W and an output voltage of 12 or 24 VDC.			
Energy model used	Manufacturing	Installation	Use	End of life
	Energy model used: China	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27

Compulsory indicators		Modicon ABLP power supply - ABLP1A24045					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	6,06E-04	5,31E-04	0*	0*	7,46E-05	0*
Contribution to the soil and water acidification	kg SO ₂ eq	3,60E+00	1,51E-02	0*	0*	3,58E+00	0*
Contribution to water eutrophication	kg PO ₄ ³⁻ eq	2,19E-01	2,67E-03	6,13E-05	0*	2,16E-01	7,80E-05
Contribution to global warming	kg CO ₂ eq	8,65E+02	6,22E+00	0*	0*	8,58E+02	2,46E-01
Contribution to ozone layer depletion	kg CFC11 eq	5,68E-05	8,26E-07	0*	0*	5,59E-05	8,57E-09
Contribution to photochemical oxidation	kg C ₂ H ₄ eq	1,98E-01	1,34E-03	0*	0*	1,97E-01	0*
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m ³	3,11E+03	0*	0*	0*	3,11E+03	0*
Total Primary Energy	MJ	1,72E+04	8,99E+01	0*	0*	1,71E+04	0*



Optional indicators		Modicon ABLP power supply - ABLP1A24045					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to fossil resources depletion	MJ	9,80E+03	5,81E+01	0*	0*	9,74E+03	0*
Contribution to air pollution	m³	3,76E+04	6,11E+02	0*	0*	3,69E+04	4,79E+00
Contribution to water pollution	m³	3,60E+04	5,88E+02	9,59E+00	0*	3,54E+04	1,05E+01
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Use of secondary material	kg	3,20E-02	3,20E-02	0*	0*	0*	0*
Total use of renewable primary energy resources	MJ	2,19E+03	5,21E+00	0*	0*	2,18E+03	0*
Total use of non-renewable primary energy resources	MJ	1,51E+04	8,47E+01	0*	0*	1,50E+04	0*
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	2,18E+03	2,56E+00	0*	0*	2,18E+03	0*
Use of renewable primary energy resources used as raw material	MJ	2,65E+00	2,65E+00	0*	0*	0*	0*
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	1,50E+04	8,26E+01	0*	0*	1,50E+04	0*
Use of non renewable primary energy resources used as raw material	MJ	2,11E+00	2,11E+00	0*	0*	0*	0*
Use of non renewable secondary fuels	MJ	0,00E+00	0*	0*	0*	0*	0*
Use of renewable secondary fuels	MJ	0,00E+00	0*	0*	0*	0*	0*
Waste categories	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Hazardous waste disposed	kg	2,08E+00	9,72E-01	0*	0*	4,48E-01	6,59E-01
Non hazardous waste disposed	kg	3,20E+03	2,96E+00	0*	0*	3,20E+03	0*
Radioactive waste disposed	kg	2,14E+00	2,28E-03	0*	0*	2,14E+00	0*
Other environmental information	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Materials for recycling	kg	2,71E-01	3,03E-02	0*	1,42E-01	0*	9,91E-02
Components for reuse	kg	0,00E+00	0*	0*	0*	0*	0*
Materials for energy recovery	kg	6,69E-02	0*	0*	0*	0*	6,69E-02
Exported Energy	MJ	8,51E-04	4,43E-04	0*	4,08E-04	0*	0*

* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.8.1, database version 2016-11 in compliance with ISO14044.

The use phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

According to this environmental analysis, proportionality rules may be used to evaluate the impacts of other products of this range.

Depending on the impact analysis, the environmental indicators (without "contribution to Mineral Resources Depletion" and "contribution to ozone layer depletion") of other products in this family may be proportional extrapolated by energy consumption values. For mineral Resources Depletion, 88% is caused by manufacturing and 12% is caused by the use phase therefore 88% of the impact may be proportional extrapolated by mass of the product and 12% may be proportional extrapolated by energy consumption values.

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Registration number	ENVPEP2007017_V1	Drafting rules	PCR-ed3-EN-2015 04 02
Date of issue	08/2020	Supplemented by	PSR-0010-ed1.1-EN-2015 10 16
Validity period	5 years	Information and reference documents	www.pep-ecopassport.org
Independent verification of the declaration and data			
Internal X External			
The elements of the present PEP cannot be compared with elements from another program.			
Document in compliance with ISO 14021:2016 « Environmental labels and declarations - Self-declared environmental claims (Type II environmental labelling) »			

Schneider Electric Industries SAS

Country Customer Care Center
<http://www.schneider-electric.com/contact>

35, rue Joseph Monier
CS 30323
F- 92506 Rueil Malmaison Cedex
RCS Nanterre 954 503 439
Capital social 896 313 776 €

www.schneider-electric.com

ENVPEP2007017_V1

Published by Schneider Electric

© 2020 - Schneider Electric – All rights reserved

08/2020