POWER-SUPPLY

MAG A1000GL PCIE5



- ATX 3.1 bereit, nativer zweifarbiger PCIe CEM 5.1 Anschluss
- Unterstützt NVIDIA® GeForce RTX™ 40er Serie Grafikkarten
- Vollmodulares Design, flache Kabel
- 80 PLUS Gold zertifiziert für hohe Effizienz
- Aktives PFC-Design
- Schutz mit OVP / OCP / OPP / OTP / SCP / UVP
- 135 mm Fluiddynamiklager-Lüfter
- LLC Full-Bridge-Topologie mit DC-zu-DC-Moduldesign

SPECIFICATIONS

Efficiency Rating	80 PLUS Gold (up to 90%)
Modular	Yes (fully modular)
Fan Bearing	Fluid Dynamic Bearing
Power Watt	1000W
Power Excursion	2000W (*up to 200% of the PSU's rated power for 100µs)
Input Voltage	100-240V~
Input Frequency	50-60Hz
ATX (24 pin)	1
EPS (4+4 PIN)	2
PCI-E 5.1 (16 pin)	1 (600W)
Fan Size	135 mm
Dimension	150 x 150 x 86 mm
PCI-E (6+2 pin)	4
PFC Type	Active PFC
SATA (15 pin)	12
Protection	OCP / OVP / OPP / OTP / SCP / UVP
MOLEX (4 pin)	4
FDD (4 pin)	1

MAG A1000GL PCIE5					
AC INPUT	100-240V, 13A ,50-60Hz				
DC OUTPUT	+5V	+3.3V	+12V	-12V	+5Vsb
	22A	22A	83.3A	0.3A	3A
TOTAL POWER	120W		999.6W	3.6W	15W
	1000W				

© 2025 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved.

MAG A1000GL PCIE5

CONNECTOR						
ATX	EPS	PCI-E 5.1	PCI-E	SATA	PERIPHERAL	FDD
1	2	1	4	12	4	1

Generated 2025-01-16, check for the latest version www.msi.com/datasheet. The information provided in this document is intended for informational purposes only and is subject to change without notice.

© 2025 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved.