

# Technical data sheet **Dégraissant Polyvalent ECO**

Reference: 6695 - 6696









## 1. General description

Solvent based degreaser for mechanical parts. Biodegradability OECD 301B: 62% (readily).

#### 2. Features

- Attacks encrusted residues. Quickly penetrates and cuts through dirt.
- Does not leave a residue.
- Non corrosive.
- Fast evaporation to minimize downtime.
- Safe on all metal surfaces, does not stain.
- Safe on most rubbers, plastics and coatings. Test on sensitive or stressed materials before use.
- Convenient 360° (including inverted position) spray valve for aerosols.
- High purity CO2 propellant, giving an active product content of 95%.

### 3. Applications

- Cleaning mechanical parts.
- Pneumatic tools.
- Compressors.
- Handling equipment.
- Open drive mechanisms.
- Wire ropes.
- Chains.
- Bearings.

#### 4. Directions

- Spray liberally and allow to run off.
- Use extension tube for more precise application.



Manufactured by:

#### **CRC Industries Europe byba**

Touwslagerstraat 1 9240 Zele Belgium

Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34

www.crcind.com





# Technical data sheet **Dégraissant Polyvalent ECO**

Reference: 6695 - 6696

- Use only with adequate ventilation.
- Test before use on sensitive materials.
- Do not use on sensitive electronic equipment.
- Do not use on energized equipment.
- Allow to dry completely before reactivation.
- Allow to dry at room temperature.
- Repeat if necessary.
- Protect and re-lubricate if necessary.
- $\bullet$  A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.

## 5. Typical product data (without propellant)

Aerosol Bulk
Appearance CO2 propelled liquid. Not available.

Appearance CO2 propelled liquid. Not available Color Colorless. Colorless.

Odor Characteristic odor. Characteristic odor.

Density 0.802 g/cm3 (@ 20°C). Characteristic odor.

0.802 g/cm3 (@ 20°C).

Flash Point 12 °C 12 °C

## 6. Packaging

Aerosol 12x500 ML Bulk 2x5 L

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: <a href="www.crcind.com">www.crcind.com</a> We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.

Version KF-DEGRAISSANT\_POLYVALENT\_ECO-20130205

Date



Manufactured by:

#### **CRC Industries Europe byba**

Touwslagerstraat 1 9240 Zele Belgium
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34

www.crcind.com





# Technical data sheet

# Dégraissant Polyvalent ECO

Reference: 6695 - 6696



Manufactured by:

# **CRC Industries Europe byba**

Touwslagerstraat 1 9240 Zele Belgium Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34

www.crcind.com

