

Mounting material - PACT-FAST-MNT-W13-L65 - 2276625

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



The transformer quick-action mechanism enables the lightning-fast mounting of PACT current transformers on the power rail. The installation can be completed easily by hand without the use of tools. Fixing pins: 65 mm, holding latches: 13 mm

Key commercial data

| | |
|-------------------------|---------------|
| package_quantity | 1 |
| GTIN | 4046356658348 |

Technical data

Dimensions

| | |
|--------------|-------|
| Width | 13 mm |
| Depth | 65 mm |

Ambient conditions

| | |
|--|-------------------|
| Ambient temperature (operation) | -25 °C ... 120 °C |
|--|-------------------|

General

| | |
|-------------------------|--|
| Housing material | PA 6 |
| Torque | 0.4 Nm |
| Note | The 16 mm wide converter attachment can also be used for larger current transformers if the length of the fixing pins is sufficient. |

classifications

eCl@ss

| | |
|-------------------|----------|
| eCl@ss 4.0 | 27210902 |
| eCl@ss 4.1 | 27210902 |
| eCl@ss 5.0 | 27210902 |
| eCl@ss 5.1 | 27210902 |
| eCl@ss 6.0 | 27210902 |
| eCl@ss 7.0 | 27210902 |
| eCl@ss 8.0 | 27210902 |

ETIM

| | |
|-----------------|----------|
| ETIM 3.0 | EC001505 |
| ETIM 4.0 | EC002498 |
| ETIM 5.0 | EC002498 |

Mounting material - PACT-FAST-MNT-W13-L65 - 2276625

classifications

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211501 |
| UNSPSC 7.0901 | 39121019 |
| UNSPSC 11 | 39121006 |
| UNSPSC 12.01 | 39121006 |
| UNSPSC 13.2 | 39121006 |

Drawings

Dimensioned drawing

