



NRKH7.E239373 - PROXIMITY SWITCHES CERTIFIED FOR CANADA

Proximity Switches Certified for Canada

See General Information for Proximity Switches Certified for Canada

CONTRINEX AG

Industrial Electronics, Route du Paqui 5
CH-1720 Corminboeuf, SWITZERLAND

E239373

Investigated to CSA-C22.2 No. 14

DC proximity switches (inductive) Model(s) DW-AS-603-C44-660, DW-AS-603-M18-661, DW-AS-603-M18-663, DW-AS-603-M30-661, DW-AS-623-M12-661

Photoelectric proximity switches Model(s) DTL-C23PB-TMS-139-501, DTL-C55PA-TMS-119-502, DTL-C55PA-TMS-119-503, DTL-C55PA-TMS-119-504, DTL-C55PA-TMS-407-505, DTR-C23PB-TLS-129, DTR-C23PB-TMS-139

F, K, L, followed by F, H, L, R, T or X, followed by K, S, T, V, P, G, R, F or W, followed by additional suffixes, number and/or letters.

LHL-C55PA-TMS-107-501

Photoelectric Proximity Switches - C23PA series, Catalog numbers: LHR, LTR, LRR, LLR, TRR, TRU followed by -C23PA followed by 6 digits suffixes

Ultrasonic proximity switches, with cable or plug connections Model(s) USR-M18MC-WMS-301, USR-M18MC-WMS-303, USR-M18MC-WSS-301, USR-M18MC-WSS-303, USR-M18MS-TLS-301, USR-M18MS-TLS-403, USR-M18MS-TMS-301, USR-M18MS-TMS-403, USR-M18PC-WMS-301, USR-M18PC-WMS-303, USR-M18PC-WSS-301, USR-M18PC-WSS-303, USR-M18PS-TLS-301, USR-M18PS-TLS-403, USR-M18PS-TMS-301, USR-M18PS-TMS-403, USR-M18MC-NMS-403, USR-M18MC-NSS-403, USR-M18MC-WMS-301, USR-M18MC-WMS-303, USR-M18MC-WMS-309, USR-M18MC-WMS-30A, USR-M18MC-WSS-301, USR-M18MC-WSS-303, USR-M18MS-TLS-101, USR-M18MS-TLS-301, USR-M18MS-TLS-403, USR-M18MS-TLS-603, USR-M18MS-TLS-711, USR-M18MS-TLS-729, USR-M18MS-TLS-72A, USR-M18MS-TLS-813, USR-M18MS-TLS-839, USR-M18MS-TLS-83A, USR-M18MS-TMS-101, USR-M18MS-TMS-301, USR-M18MS-TMS-403, USR-M18MS-TMS-603, USR-M18MS-TMS-711, USR-M18MS-TMS-729, USR-M18MS-TMS-72A, USR-M18MS-TMS-813, USR-M18MS-TMS-839, USR-M18MS-TMS-83A, USR-M18PC-WMS-301, USR-M18PC-WMS-303, USR-M18PC-WMS-309, USR-M18PC-WMS-30A, USR-M18PC-WSS-301, USR-M18PC-WSS-303, USR-M18PS-TLS-101, USR-M18PS-TLS-301, USR-M18PS-TLS-403, USR-M18PS-TLS-603, USR-M18PS-TLS-711, USR-M18PS-TLS-729, USR-M18PS-TLS-72A, USR-M18PS-TLS-813, USR-M18PS-TLS-839, USR-M18PS-TLS-83A, USR-M18PS-TMS-101, USR-M18PS-TMS-301, USR-M18PS-TMS-403, USR-M18PS-TMS-603, USR-M18PS-TMS-711, USR-M18PS-TMS-729, USR-M18PS-TMS-72A, USR-M18PS-TMS-813, USR-M18PS-TMS-839, USR-M18PS-TMS-83A, USR-M30MS-TLS-403, USR-M30MS-TLS-603, USR-M30MS-TMS-403, USR-M30MS-TMS-603, USR-M30PO-TXS-403, USR-M30PO-TXS-603, USR-M30PS-TLS-403, USR-M30PS-TLS-603, USR-M30PS-TMS-403, USR-M30PS-TMS-603

Investigated to CAN/CSA-C22.2 No. 60947-5-2

Proximity switches Model(s) DW followed by A, D, L, M, or H, followed by D, S, or V, followed by 5, 6, or 7, followed by 0, 1, 2, or 3, followed by 0, 1, 2, 3, 4, 5, 6, 9, A or B, followed by M, C, 0, or P, followed by 3, 4, 5, 8, 10, 12, 18, 20, 23, 30, 44, 65, 80, may be followed by additional suffixes

DW followed by L, followed by D or S, followed by 7, followed by 0 or 1, followed by any digit from 1 to 4, followed by M, followed by 12 or 18 or 30 or 65 or 80, may be followed by additional suffixes

Last Updated on 2019-09-07

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"