

Mini DomiLEDTM

Synonymous with function and performance, the Mini DomiLEDTM series is perfectly suited for a variety of cross-industrial applications due to its small package outline, durability and superior brightness.



Features:

- > High brightness surface mount LED.
- > 120° viewing angle.
- > Small package outline (LxWxH) of 2.0 x 1.4 x 1.3mm.
- > Qualified according to JEDEC moisture sensitivity Level 2.
- > Compatible to IR reflow soldering.
- > Environmental friendly; RoHS compliance.



Applications:

- > Automotive: interior applications, eg: switches, telematics, climate control system, dashboard, etc.
- > Backlighting: button, LCD display



Optical Characteristics at Tj=25°C

Part Ordering Number	Chip Technology / Color	Viewing Angle°	Luminous Intensity @ IF = 20mA IV (mcd)
DNH-CJS-N2Q1-1	AllnGaP	120	35.5 - 90.0
• DNH-CJS-N2	Hyper-red, 640nm		35.5 - 45.0
• DNH-CJS-P1			45.0 - 56.0
• DNH-CJS-P2			56.0 - 71.5
• DNH-CJS-Q1			71.5 - 90.0
DNS-CJS-PQ2-1	AllnGap	120	45.0 - 112.5
• DNS-CJS-P1	Super-red, 632nm		45.0 - 56.0
• DNS-CJS-P2			56.0 - 71.5
• DNS-CJS-Q1			71.5 - 90.0
• DNS-CJS-Q2			90.0 - 112.5
DNR-CJS-RS2-1	AllnGap	120	112.5 - 285.0
• DNR-CJS-R1	Red, 625nm		112.5 - 140.0
• DNR-CJS-R2			140.0 - 180.0
• DNR-CJS-S1			180.0 - 224.0
• DNR-CJS-S2			224.0 - 285.0
DNA-CJS-RS2-1	AllnGap	120	112.5 - 285.0
• DNA-CJS-R1	Amber, 615nm		112.5 - 140.0
• DNA-CJS-R2			140.0 - 180.0
• DNA-CJS-S1			180.0 - 224.0
• DNA-CJS-S2			224.0 - 285.0
DNO-CJS-RS2-1	AllnGap	120	112.5 - 285.0
• DNO-CJS-R1	Orange, 605nm		112.5 - 140.0
• DNO-CJS-R2			140.0 - 180.0
• DNO-CJS-S1			180.0 - 224.0
• DNO-CJS-S2			224.0 - 285.0
DNY-CJS-RS2-1	AllnGap	120	112.5 - 285.0
• DNY-CJS-R1	Yellow, 587nm		112.5 - 140.0
• DNY-CJS-R2			140.0 - 180.0
• DNY-CJS-S1			180.0 - 224.0
• DNY-CJS-S2			224.0 - 285.0
DNG-CJS-PQ2-1	AllnGap	120	45.0 - 112.5
• DNG-CJS-P1	Green, 570nm		45.0 - 56.0
• DNG-CJS-P2			56.0 - 71.5
• DNG-CJS-Q1			71.5 - 90.0
• DNG-CJS-Q2			90.0 - 112.5
DNP-CJS-LM2-1	AllnGap		11.2 - 28.5
• DNP-CJS-L1	Pure Green, 560nm		11.2 - 14.0
• DNP-CJS-L2			14.0 - 18.0
• DNP-CJS-M1			18.0 - 22.4
• DNP-CJS-M2			22.4 - 28.5

NOTE

1. All part number above comes in a quantity of 3000 units per reel.
2. Other luminous intensity groups are also available upon request.
3. Luminous intensity is measured with an accuracy of $\pm 11\%$.
4. Wavelength binning is carried for all units as per the wavelength-binning table. Only one wavelength group is allowed for each reel.

Wavelength Grouping at Tj=25°C

Color	Group	Wavelength distribution (nm)
DNH; Hyper-red	Full	636 - 646
DNS; Super-red	Full	625 - 640
DNR; Red	Full	620 - 630
DNA; Amber	Full	610 - 621
	W	610 - 615
	X	615 - 621
DNO; Orange	Full	600 - 612
	W	600 - 603
	X	603 - 606
	Y	606 - 609
	Z	609 - 612
DNY; Yellow	Full	582 - 594
	W	582 - 585
	X	585 - 588
	Y	588 - 591
	Z	591 - 594
DNG; Green	Full	564.5 - 576.5
	W	564.5 - 567.5
	X	567.5 - 570.5
	Y	570.5 - 573.5
	Z	573.5 - 576.5
DNP; Pure Green	Full	552.5 - 564.5
	W	552.5 - 555.5
	X	555.5 - 558.5
	Y	558.5 - 561.5
	Z	561.5 - 564.5

Dominant wavelength is measured with an accuracy of ± 1 nm.

Electrical Characteristics at Tj=25°C

Part Number	Vf @ If = 20mA			Vr @ Ir = 10uA
	Min. (V)	Typ. (V)	Max. (V)	Min. (V)
DNH-CJS, DNS-CJS, DNR-CJS, DNA-CJS, DNO-CJS, DNY-CJS, DNG-CJS, DNP-CJS	1.7	1.95	2.4	12

Forward voltage, Vf is measured with an accuracy of ± 0.1 V.

Material

Material	
Lead-frame	Cu Alloy With Ag Plating
Package	High Temperature Resistant Plastic, PPA
Encapsulant	Epoxy
Soldering Leads	Sn-Sn Plating


Absolute Maximum Ratings

	Maximum Value	Unit
DC forward current	30	mA
Peak pulse current; (tp ≤ 10µs, Duty cycle = 0.005)	DNH, DNS, DNR, DNA, DNO DNY, DNG, DNP 800 200	mA
Reverse voltage	12	V
ESD threshold (HBM)	2	KV
LED junction temperature	125	°C
Operating temperature	-40 ... +100	°C
Storage temperature	-40 ... +100	°C
Power dissipation (at room temperature)	75	mW
Thermal resistance		
- Junction / ambient, Rth JA	580	K/W
- Junction / solder point, Rth JS	330	K/W
(Mounting on FR4 PCB, pad size ≥ 16 mm² per pad)		


Characteristics

	Symbol	Part Number	Value	Unit
Temperature coefficient of λ_{dom} (typ) $I_F = 20\text{mA}; 0\text{ }^\circ\text{C} \leq T \leq 100\text{ }^\circ\text{C}$	$TC_{\lambda_{dom}}$ (typ)	DNH-CJS	0.04	nm / K
		DNS-CJS	0.04	
		DNR-CJS	0.04	
		DNA-CJS	0.06	
		DNO-CJS	0.07	
		DNY-CJS	0.09	
		DNG-CJS	0.11	
		DNP-CJS	0.11	
Temperature coefficient of V_F (typ) $I_F = 20\text{mA}; 0\text{ }^\circ\text{C} \leq T \leq 100\text{ }^\circ\text{C}$	TC_V	DNH-CJS	-2.6	mV / K
		DNS-CJS	-2.7	
		DNR-CJS	-2.6	
		DNA-CJS	-2.6	
		DNO-CJS	-1.9	
		DNY-CJS	-1.9	
		DNG-CJS	-1.8	
		DNP-CJS	-1.8	
Temperature coefficient of I_V (typ) $I_F = 20\text{mA}; 0\text{ }^\circ\text{C} \leq T \leq 100\text{ }^\circ\text{C}$	TC_{I_V}	DNH-CJS	-0.45	mcd / K
		DNS-CJS	-0.73	
		DNR-CJS	-0.80	
		DNA-CJS	-0.96	
		DNO-CJS	-1.16	
		DNY-CJS	-2.00	
		DNG-CJS	-0.77	
		DNP-CJS	-0.19	


Relative Luminous Intensity Vs Forward Current




Forward Current Vs Forward Voltage




Maximum Current Vs Temperature




Relative Intensity Vs Wavelength




Allowable Forward Current Vs Duty Ratio (Ta=25 Deg C, tp<10us)




Radiation Pattern




Mini DomiLED™ • AllnGap : DNx-CJS Package Outlines



Recommended Solder Pad



Improved Design For Better Heat Dissipation




Additional Cu area for improved heat dissipation, > 16mm sq.


 Solder resist.

Taping and orientation


- Reels come in quantity of 3000 units.
- Reel diameter is 180 mm.




Packaging Specification



Packaging Specification




	Average 1pc Mini DomiLED	1 completed bag (3000pcs)
Weight (gram)	0.007	140 ± 10




For Mini DomiLED™

Cardboard Box Size	Dimensions (mm)	Empty Box Weight (kg)	Reel / Box	Quantity / Box (pcs)
Small	300 x 250 x 250	0.58	15 reels MAX	45,000 MAX
Large	416 x 516 x 476	1.74	55 reels MAX	165,000 MAX

Recommended Sn-Pb IR-Reflow Soldering Profile



Recommended Pb-free Soldering Profile



Revision History

Page	Subjects	Date of Modification
-	Initial Release	04 Feb 2008

NOTE

All the information contained in this document is considered to be reliable at the time of publishing. However, DOMINANT Semiconductors does not assume any liability arising out of the application or use of any product described herein.

DOMINANT Semiconductors reserves the right to make changes at any time without prior notice to any products in order to improve reliability, function or design.

DOMINANT Semiconductors products are not authorized for use as critical components in life support devices or systems without the express written approval from the Managing Director of DOMINANT Semiconductors.

About Us

DOMINANT Semiconductors is a dynamic Malaysian Corporation that is among the world's leading SMT LED Manufacturers. An excellence – driven organization, it offers a comprehensive product range for diverse industries and applications. Featuring an internationally certified quality assurance acclaim, DOMINANT's extra bright LEDs are perfectly suited for various lighting applications in the automotive, consumer and communications as well as industrial sectors. With extensive industry experience and relentless pursuit of innovation, DOMINANT's state-of-art manufacturing, research and testing capabilities have become a trusted and reliable brand across the globe. More information about DOMINANT Semiconductors can be found on the Internet at <http://www.dominant-semi.com>.

Please contact us for more information:

Head Quarter

DOMINANT Semiconductors Sdn. Bhd.
Lot 6, Batu Berendam, FTZ Phase III, 75350 Melaka, Malaysia
Tel: (606) 283 3566 Fax: (606) 283 0566
E-mail: sales@dominant-semi.com

DOMINANT Semiconductors Malaysia Sdn. Bhd. Shanghai Representative Office

DOMINANT Semiconductors (Shenzhen) Co. Ltd.
Rm 1007, DaZhong Building, No. 1515 Zhong Shan (W) Rd, Shanghai, China 200235
Tel: +86 21 6428 6428 Fax: +86 21 6428 6880
E-mail: sales_china@dominant-semi.com

DOMINANT Korea Sales Office

DOMINANT Semiconductors Korea Inc.
#709, Yatap Leaders Bldg., 342-1 Yatap-dong, Bundang-gu, Seongnam-si, Gyeonggi-do, 463-828 Korea.
Tel: +82-31-701-5203 Fax: +82-31-701-5204
E-mail: sales_korea@dominant-semi.com

DOMINANT U.S.A Sales Office

25 Rockaway Road, 08833 Lebanon, New Jersey, USA
Tel: (908) 439-9930 Cell: (908) 343-5810 Fax: (908) 439-9929
E-mail: don.wendel@dominant-semi.com

DOMINANT Europe Sales Office

DOMINANT Semiconductors Europe GmbH
Raiffeisenstr. 38, 74906 Bad Rappenau Germany
Tel: +49 (0) 7264-89010-10 / +49 (0) 7264-89010-11 Cell: +49 173-6907370 / +49 173-6907751
Fax: +49 (0) 7264-89010-29
E-mail: gerd.wachno@dominant-semi.eu; hartmut.wettengl@dominant-semi.eu

DOMINANT India Sales Office

C-11, Vasanth Business Centre #86, TTK Road, Alwarpet Chennai - 600 018, INDIA
Tel: 91-44-42030616 / 516 Cell: 91-9444920537 Fax: 91-9444920616
E-mail: pravat.behera@dominant-semi.com

