PCB terminal block - SPT 5/ 4-V-7,5-ZB BU/GY/BK/RD - 1701934

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)

PCB terminal block, nominal current: 41 A, nominal voltage: 800 V, pitch: 7.5 mm, number of positions: 4, connection method: spring-cage connection, assembly: soldering, conductor/PCB connection direction: 90°, color: blue, gray, black, red

Key commercial data

package_quantity	50
GTIN	4046356567176

Technical data

Dimensions

Pitch	7.5 mm
Dimension a	22.5 mm
Pin dimensions	1,7 x 0,8
Pin spacing	7.5 mm
Hole diameter	2.1 mm

General

Range of articles	SPT 5/..-V
Rated surge voltage (III/3)	8 kV
Rated surge voltage (III/2)	8 kV
Rated surge voltage (II/2)	6 kV
Rated voltage (III/3)	800 V
Rated voltage (III/2)	1000 V
Rated voltage (II/2)	1000 V
Connection in acc. with standard	EN-VDE
Nominal current I_N	41 A
Nominal cross section	6 mm²
Solder pin surface	Sn
Stripping length	15 mm
Number of positions	4

Connection data

Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	8
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min.	0.25 mm²

PCB terminal block - SPT 5/ 4-V-7,5-ZB BU/GY/BK/RD - 1701934

Technical data

Connection data

2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max.	1.5 mm²

classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27141190
eCl@ss 6.0	27261101
eCl@ss 7.0	27440401
eCl@ss 8.0	27440401

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002643
ETIM 5.0	EC002643

UNSPSC

UNSPSC 6.01	30211801
UNSPSC 7.0901	39121432
UNSPSC 11	39121432
UNSPSC 12.01	39121432
UNSPSC 13.2	39121432

approvals

SEV / CCA / GOST / IECEE CB Scheme / GOST /

Approval details

SEV	
Nominal voltage UN	1000 V
Nominal current IN	41 A
mm²/AWG/kcmil	6

CCA	
Nominal voltage UN	1000 V
Nominal current IN	41 A
mm²/AWG/kcmil	6

PCB terminal block - SPT 5/ 4-V-7,5-ZB BU/GY/BK/RD - 1701934

approvals

GOST

IECEE CB Scheme

Nominal voltage UN	1000 V
Nominal current IN	41 A
mm²/AWG/kcmil	6

© Phoenix Contact 2013 - all rights reserved
http://www.phoenixcontact.com