

Network isolator - FL ISOLATOR 100-RJ/SC - 2313928

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Passive network isolator for electrical isolation in Ethernet networks. This protects Ethernet devices from potential differences of up to 4 kV. Can be used for transmission speeds of up to 100 Mbps. Connection using RJ45 and COMBICON plug-in screw terminal block.

Product Features

- No power supply required
- Protection against aggressive environmental influences, particularly harsh industrial environments, thanks to coated PCB
- Dielectric strength of up to 4 kV
- Approval for railway applications (rolling stock) according to EN 50155 and EN 50121
- Transmission speed of up to 1000 Mbps
- Continuous insulation voltage of 250 VRMS
- Extended temperature range of -25°C to +85°C
- Electrical isolation of data cables and cable shielding
- Mounting on EN DIN rails



Key commercial data

package_quantity	1
GTIN	4046356575072

Technical data

Dimensions

Width	22.5 mm
Height	99 mm
Depth	92 mm

Ambient conditions

Ambient temperature (operation)	-25 °C ... 75 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C
Permissible humidity (operation)	10 % ... 95 % (no condensation)
Permissible humidity (storage/transport)	5 % ... 95 % (no condensation)
Altitude	5000 m (For restrictions see manufacturer's declaration)
Degree of protection	IP20

Serial interface

Interface 1	Ethernet interface, 10/100BASE-T(X) in acc. with IEEE 802.3u
-------------	--

Network isolator - FL ISOLATOR 100-RJ/SC - 2313928

Technical data

Serial interface

Interface	Ethernet
Connection method	RJ45 socket, shielded
Transmission length	≤ 100 m (Total length across both ports (dependent on data rate and cable used))
Serial transmission speed	10/100 Mbps
Interface 2	Ethernet interface, 10/100/1000Base-T(X) according to IEEE 802.3u
Interface	Ethernet
Connection method	COMBICON screw terminal block
Transmission length	≤ 100 m (Total length across both ports (dependent on data rate and cable used))
Conductor cross section solid min.	0.14 mm ²
Conductor cross section solid max.	1.5 mm ²
Conductor cross section stranded min.	0.14 mm ²
Conductor cross section stranded max.	1.5 mm ²
Conductor cross section AWG/kcmil min.	26
Conductor cross section AWG/kcmil max	16

General

Electrical isolation	(Ethernet // Ethernet)
Test voltage data interface/data interface	4 kV AC (50 Hz, 1 min.)
Insulation voltage input/output	250 V _{rms}
Standards/regulations	EN 50121 and EN 50155 (for railway applications)
Electromagnetic compatibility	Conformance with EMC Directive 2004/108/EC
Net weight	90 g
Housing material	PA 6.6-FR
Color	green
MTBF	26549 Years (Telcordia standard, 25°C temperature, 21% operating cycle (5 days a week, 8 hours a day))
MTBF	9033 Years (Telcordia standard, 40°C temperature, 34.25% operating cycle (5 days a week, 12 hours a day))
UL, USA / Canada	508 listed

classifications

eCl@ss

eCl@ss 4.0	27250591
eCl@ss 4.1	27230207
eCl@ss 5.0	27230207
eCl@ss 5.1	27061803
eCl@ss 6.0	27061803
eCl@ss 7.0	27061803
eCl@ss 8.0	27061803

Network isolator - FL ISOLATOR 100-RJ/SC - 2313928

classifications

ETIM

ETIM 3.0	EC000313
ETIM 4.0	EC000467
ETIM 5.0	EC000467




UNSPSC

UNSPSC 6.01	26121607
UNSPSC 7.0901	26121607
UNSPSC 11	26121607
UNSPSC 12.01	26121607
UNSPSC 13.2	26121607

approvals

UL Listed / cUL Listed / UL Listed / cUL Listed / cULus Listed /

Approval details



accessories

Patch panel

Network isolator - FL ISOLATOR 100-RJ/SC - 2313928

accessories

FL CAT5 TERMINAL BOX - 2744610



FL-PP-RJ45-SCC - 2901642



FL-PP-RJ45-SC - 2901643



FL-PP-RJ45-LSA - 2901645



FL-PP-RJ45/RJ45 - 2901646



Passive isolators

Network isolator - FL ISOLATOR 100-RJ/SC - 2313928

accessories

FL ISOLATOR 100-RJ/RJ - 2313931



FL ISOLATOR 1000-RJ/RJ - 2313915



Patch cable

FL CAT5 PATCH 0,3 - 2832250



FL CAT5 PATCH 0,5 - 2832263



FL CAT5 PATCH 1,0 - 2832276



Network isolator - FL ISOLATOR 100-RJ/SC - 2313928

accessories

FL CAT5 PATCH 1,5 - 2832221



FL CAT5 PATCH 2,0 - 2832289



FL CAT5 PATCH 3,0 - 2832292



FL CAT6 PATCH 0,3 - 2891181



FL CAT6 PATCH 0,5 - 2891288



FL CAT6 PATCH 1,0 - 2891385



Network isolator - FL ISOLATOR 100-RJ/SC - 2313928

accessories

FL CAT6 PATCH 1,5 - 2891482



FL CAT6 PATCH 2,0 - 2891589



FL CAT6 PATCH 3,0 - 2891686



Drawings

© Phoenix Contact 2013 - all rights reserved
<http://www.phoenixcontact.com>