

## Industrial Ethernet IE-SW-PL08MT-6TX-2ST

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



Weidmüller's Premium Line consists of high-end switches with advanced management and security features. It is suitable for demanding network solutions. The equipment can be delivered with Fast Ethernet or Gigabit Ethernet ports. One variety is fitted with Fast Ethernet and Power-over-Ethernet ports. With their advanced ring redundancy technology (recovery time  $\leq 20$  ms), these devices raise the reliability and availability of your industrial networks. The optional SFP transceiver can be fitted offering a high degree of flexibility. Gigabit versions permit use in networks with a high volume of communications

- Managed Fast Ethernet versions in a high-quality metal housing (IP 30)
- Managed Power-over-Ethernet (PoE) switch with 6 Fast Ethernet ports, 4 of them PoE+ ports
- Versions with 10 or 18 ports and Gigabit uplink ports
- Full Gigabit switch with 9 ports
- Supports all standard TCP/IP-based protocols in industrial networks (for example Ethernet/IP, Modbus/TCP)
- Integrated redundancy mechanisms (recovery time  $\leq 20$  ms) increase the reliability in network ring structures
- Approvals: CE, FCC, cULus, Class I Div. 2 / ATEX, DNV / GL

### General ordering data

Type	IE-SW-PL08MT-6TX-2ST
Order No.	<a href="#">1286800000</a>
Version	Network switch, managed, Fast Ethernet, Number of ports: 6x RJ45, 2 * ST Multi-mode, IP 30, -40 °C...+75 °C
GTIN (EAN)	4050118077285
Qty.	1 pc(s).

## Industrial Ethernet IE-SW-PL08MT-6TX-2ST

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technische Daten

### Dimensions and weights

Width	80.2 mm	Height	135 mm
Depth	105 mm	Weight	1,040 g
Net weight	1,040 g		

### Downloads

Firmware	Version 2.6.24	Manual	Manual
----------	----------------	--------	--------

### EMC conformity and approvals

Explosive risk zone	UL/cUL, Class I, Division 2, Groups A, B, C and D, ATEX Zone 2, Ex nC IIC	Free fall	IEC 60068-2-32
Security	UL508, UL60950-1, CSA C22.2 No. 60950-1, EN60950-1	Ship use	DNV, GL
Shock resistance IEC 60068-2-27	Available	Vibration resistance IEC 60068-2-6	Available

### Environmental conditions

Humidity	5 to 95 % (non-condensing)	Operating temperature, max.	75 °C
Operating temperature, min.	-40 °C	Storage temperature, max.	85 °C
Storage temperature, min.	-40 °C		

### Guarantee

Time interval	5 years
---------------	---------

### Interfaces

Alarm contact	2 relay outputs with a current capacity of 1 A at 24 V DC	Console port interface	RS-232
DIP switch	Turbo-Ring, Master, Coupler, Reserve	Digital inputs	2 inputs with the same ground, isolated <ul style="list-style-type: none"> <li>• +13 To +30 V for logic "1"</li> <li>• -30 To +3 V for logic "0"</li> <li>• Max. input current: 8 mA</li> </ul>
Fibre-optic ports	100BaseFX ports (ST connector), Multimode	LED indicator	PWR1, PWR2, FAULT, MSTR/HEAD, CPLR/TAIL, 10/100M (TP-Port), 100M (Glasfaser-Port)
Number of ports	6x RJ45, 2 * ST Multimode	RJ45 ports	10/100BaseT(X), auto negotiation, Full-/half-duplex mode, Auto MDI/MDI-X port

### MTBF

MTBF	339,000 hrs	MTBF	Telcordia (Bellcore), GB
------	-------------	------	--------------------------

### Order data

Number of ports	6x RJ45, 2 * ST Multimode	Operating temperature	-40 °C...+75 °C
-----------------	---------------------------	-----------------------	-----------------

Erstellungs-Datum December 20, 2013 8:15:22 AM CET

## Industrial Ethernet IE-SW-PL08MT-6TX-2ST

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technische Daten

### Power supply

Connection type	2 removable 6-pin terminal blocks	Reverse polarity protection	Available
Supply voltage	24 V DC, 12 bis 45 V DC, 2 redundant inputs	Turn-on current limit	Existing

### Switch characteristics

IGMP-Groups	256	MAC table size	8 K
Max. number of available VLANs	64	Priority queues	4
VLAN-ID max	4,094	VLAN-ID min	1

### Technical data

Housing main material	metal	Protection degree	IP 30
Type of mounting	Mounting rail		

### Technology

Flow control	IEEE 802.3x flow control, Back pressure flow control	MIB	MIB-II, Ethernet-Like MIB, P-BRIDGE MIB, Q-BRIDGE MIB, Bridge MIB, RSTP MIB, RMON MIB Group 1, 2, 3, 9
Protocol	IGMPv1/v2, GVRP, SNMPv1/v2c/v3, DHCP Server/Client, BootP, TFTP, SNTP, SMTP, RARP, GMRP, LACP, RMON, HTTP, HTTPS, Telnet, Syslog, DHCP option 66/67/82, SSH, SNMP Inform, Modbus/TCP, LLDP, IEEE 1588 PTP, IPv6	Standard	IEEE 802.3 for 10BaseT, IEEE 802.3u for 100BaseT(X) und 100BaseFX, IEEE 802.3x for flow control, IEEE 802.1D for the Spanning Tree protocol, IEEE 802.1w for Rapid STP, IEEE 802.1Q for VLAN tagging, IEEE 802.1p for Class of Service, IEEE 802.1X for authentication, IEEE 802.3ad for port trunk with LACP

### Classifications

eClass 6.2	19-17-01-06	eClass 7.1	19-17-01-06
------------	-------------	------------	-------------

### Approvals

Approvals



ROHS	Conform
------	---------

**Industrial Ethernet  
IE-SW-PL08MT-6TX-2ST**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Technische Daten****Downloads**

---

Manual	<a href="#">Manual</a>
Package insert	<a href="#">Hardware Installation Guide</a>
Declaration of Conformity	<a href="#">K4200213.pdf</a>
SNMP MIB file	<a href="#">SNMP MIB file</a>
Tools	<a href="#">Managed Switch Configuration Utility</a>
Firmware	<a href="#">Version 2.6.24</a>
<a href="#">3D Modell</a>	

---