## POK HG K+POK



#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com





For many years, the name Klippon® has stood for competence and quality in enclosures. The enclosures are ideal for turnkey customised solutions for standard industrial applications and for explosive-risk applications.

Improved products that meet all application requirements: this was Weidmüller's aim during the update of the Klippon® K housing series. Weidmüller delivers many types of aluminium enclosures; they are designed to fit precisely with a wide range of customer requirements and applications.

Our comprehensive product line provides the following advantages:

- Available in two different surfaces: natural and powdercoated (RAL 7001)
- Available normally with silicone or chloroprene gasket seal
- A uniform Torx-slotted screw head is used for over 19 different housing sizes.
- Mounting holes not within the sealed area
- High degree of protection: IP66, IP67 and IP68
- Impact resistance of up to 10 Joules
- The housings are certified by ATEX, GOST, GOST Ex, cULus, Russian Maritime Register, German Lloyd, as well as the empty housing standard.
- Alloy is resistant to salt water

• Standardised distributor housings with threaded holes and a variety of terminal configurations

#### General ordering data

| Туре       | HG K+POK              |  |  |
|------------|-----------------------|--|--|
| Order No.  | <u>1580360000</u>     |  |  |
| Version    | External joint, Hinge |  |  |
| GTIN (EAN) | 4008190203542         |  |  |
| Qty.       | 1 pc(s).              |  |  |

### POK **HG K+POK**

# **Technische Daten**



### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

| Dimensions and weights |                |            |             |  |
|------------------------|----------------|------------|-------------|--|
|                        |                |            |             |  |
| Net weight             | 75 g           |            |             |  |
| General information    |                |            |             |  |
| Protection degree      | IP 66          |            |             |  |
| General information o  | on accessories |            |             |  |
|                        |                |            |             |  |
| Type of fixing         | Screwed        |            |             |  |
| Classifications        |                |            |             |  |
| ETIM 3.0               | EC000318       | UNSPSC     | 31-16-23-03 |  |
| eClass 5.1             | 27-18-92-07    | eClass 6.2 | 27-18-92-34 |  |
| eClass 7.1             | 27-18-92-34    |            |             |  |
| Approvals              |                |            |             |  |
| Approvals              |                |            |             |  |
| ROHS                   | Conform        |            |             |  |