SAIB-VSA-4P/230/11-H/OB

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Individual cable lengths are often required nowadays. In order to meet these demands, Weidmüller offers a wide range of plug-in connectors for custom assembly. Customisable valve plugs are used frequently in special-purpose machine engineering. Such plugs are used to connect solenoid valves. The valve plugs are available in all standard design types. The range includes the design types A, B Industrial, B acc. to DIN, C Industrial and C acc. to DIN. The valve plugs are available in 3 and 4-pole versions without cables. A flat gasket seal is included which, when screwed on, guarantees IP 65 protection.

General ordering data

Type	SAIB-VSA-4P/230/11-H/OB
Order No.	1873160000
Version	Sockets prefabricated to customer spec., Plugs prefabricated to customer spec., bush, 90°, A
GTIN (EAN)	4032248492534
Qty.	1 pc(s).

SAIB-VSA-4P/230/11-H/OB

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technische Daten

Dimensions and weights

Net weight	30 g

Technical data customisable plug-in connectors

Cable diameter	6...8 mm (PG9) / 8...10 mm (PG11)	Cable diameter, max.	10 mm
Cable diameter, min.	8 mm	Cable gland	PG 11
Coding	Design A (18 mm)	Connection cross-section, max.	1.5 mm²
Connection cross-section, min.	0.34 mm²	Contact surface	Ni
Housing main material	PA 6 GF	Insulation resistance	10^8 Ω
No. of poles	4	Pollution severity	3
Protection degree	IP 65	Rated current	10 A
Rated voltage	230 V	Rated voltage (text)	230 V
Type of connection	Screw connection		

Classifications

ETIM 3.0	EC002062	UNSPSC	30-21-18-10
eClass 5.1	27-26-07-01	eClass 6.2	27-26-07-03
eClass 7.1	27-44-01-01		

Approvals

Approvals	
ROHS	Conform