

SAIB-VSBD-3P/250/9-OB**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



Individual cable lengths are often required nowadays. In order to meet these demands, Weidmüller offers a wide range of plug-in connectors for custom assembly. Customisable valve plugs are used frequently in special-purpose machine engineering. Such plugs are used to connect solenoid valves. The valve plugs are available in all standard design types. The range includes the design types A, B Industrial, B acc. to DIN, C Industrial and C acc. to DIN. The valve plugs are available in 3 and 4-pole versions without cables. A flat gasket seal is included which, when screwed on, guarantees IP 65 protection.

General ordering data

Type	SAIB-VSBD-3P/250/9-OB
Order No.	1873190000
Version	Sockets prefabricated to customer spec., Plugs prefabricated to customer spec., bush, 90°, BD
GTIN (EAN)	4032248495412
Qty.	1 pc(s).

SAIB-VSBD-3P/250/9-OB

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technische Daten

Dimensions and weights

Net weight	21 g
------------	------

Technical data customisable plug-in connectors

Cable diameter	6...8 mm (PG9)	Cable diameter, max.	8 mm
Cable diameter, min.	6 mm	Cable gland	PG 9
Coding	DIN design B (10 mm)	Connection cross-section, max.	1.5 mm ²
Connection cross-section, min.	0.34 mm ²	Contact surface	Ni
Housing main material	PA 6 GF	Insulation resistance	10 ⁸ Ω
No. of poles	3	Pollution severity	3
Protection degree	IP 65	Rated current	10 A
Rated voltage	250 V	Rated voltage (text)	250 V (4-pole) / 125 V (5-pole)
Type of connection	Screw connection		

Classifications

ETIM 3.0	EC002062	UNSPSC	30-21-18-10
eClass 5.1	27-26-07-01	eClass 6.2	27-26-07-03
eClass 7.1	27-44-01-01		

Approvals

Approvals	
ROHS	Conform