

**HDC insert  
HDC HA 10 MC****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16


D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



The small and thin HA series can be used wherever space is limited.

The wire connection level is designed as a crimp contact.

The established crimp connection has been used as a standard for decades.

Crimp contacts are not delivered with the inserts.

Pole count: 10

Rated current: 22 A

Rated voltage 250 V

Nominal voltage acc. to UL/CSA: 600 V AC/DC

Crimp connection

**General ordering data**

|            |                                                                           |
|------------|---------------------------------------------------------------------------|
| Type       | HDC HA 10 MC                                                              |
| Order No.  | <a href="#">1873870000</a>                                                |
| Version    | HDC insert, Pin, 250 V, 16 A, No. of poles: 10, Crimp connection, Size: 2 |
| GTIN (EAN) | 4032248458387                                                             |
| Qty.       | 1 pc(s).                                                                  |

## HDC insert HDC HA 10 MC

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

## Technical data

### Dimensions and weights

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Width      | 23 mm   | Width (inches)  | 0.906 inch |
| Height     | 29 mm   | Height (inches) | 1.142 inch |
| Depth      | 56.6 mm | Depth (inches)  | 2.228 inch |
| Net weight | 28 g    |                 |            |

### Temperatures

|                   |                   |
|-------------------|-------------------|
| Limit temperature | -40 °C ... 125 °C |
|-------------------|-------------------|

### Dimensions

|                |       |                   |         |
|----------------|-------|-------------------|---------|
| Height of plug | 29 mm | Total length base | 56.6 mm |
|----------------|-------|-------------------|---------|

### General data

|                                      |                     |                              |                                                             |
|--------------------------------------|---------------------|------------------------------|-------------------------------------------------------------|
| Conductor cross-section              | 2.5 mm <sup>2</sup> | Insulating material          | PC glass-fibre reinforced (UL-listed and railway-certified) |
| Insulating material group            | IIIa                | Insulation strength          | 10 <sup>10</sup> Ω                                          |
| Material                             | Copper alloy        | No. of poles                 | 10                                                          |
| Plugging cycles, gold                | ≥ 500               | Plugging cycles, silver      | ≥ 500                                                       |
| Pollution severity                   | 3                   | Rated current (DIN EN 61984) | 16 A                                                        |
| Rated impulse voltage (DIN EN 61984) | 4 kV                | Rated voltage (DIN EN 61984) | 250 V                                                       |
| Rated voltage according to UL/CSA    | 600 V AC/DC         | Series                       | HA                                                          |
| Size                                 | 2                   | Surface finish               | Silver passivated, gold                                     |
| Type                                 | Pin                 | UL 94 flammability rating    | V-0                                                         |
| Volume resistance                    | ≤ 2 mΩ              |                              |                                                             |

### Connection data PE

|                                                                                         |                     |                                                                                         |                     |
|-----------------------------------------------------------------------------------------|---------------------|-----------------------------------------------------------------------------------------|---------------------|
| Blade size, crosshead                                                                   | size PH1            | Blade size, slotted (PE connection)                                                     | SD 0.8 x 4.0        |
| Connection type PE                                                                      | Screw connection    | Fixing screw                                                                            | M 4                 |
| Rated cross-section                                                                     | 2.5 mm <sup>2</sup> | Stripping length PE connection                                                          | 10 mm               |
| Tightening torque, max. PE connection                                                   | 1.5 Nm              | Tightening torque, min. PE connection                                                   | 1.2 Nm              |
| Wire connection cross section, finely stranded, max.                                    | 2.5 mm <sup>2</sup> | Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max. | 2.5 mm <sup>2</sup> |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min. | 0.5 mm <sup>2</sup> | Wire connection cross-section, finely stranded, min.                                    | 0.5 mm <sup>2</sup> |
| Wire cross section, AWG (PE), max.                                                      | AWG 14              | Wire cross section, AWG (PE), min.                                                      | AWG 20              |
| Wire cross-section, solid, max.                                                         | 2.5 mm <sup>2</sup> | Wire cross-section, solid, min.                                                         | 0.5 mm <sup>2</sup> |

## HDC insert HDC HA 10 MC

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

## Technical data

### Version

|                                                                                         |                     |                                                                                         |                         |
|-----------------------------------------------------------------------------------------|---------------------|-----------------------------------------------------------------------------------------|-------------------------|
| Conductor cross-section, max.                                                           | 4 mm <sup>2</sup>   | Conductor cross-section, min.                                                           | 0.5 mm <sup>2</sup>     |
| Material                                                                                | Copper alloy        | Size                                                                                    | 2                       |
| Stripping length, rated connection                                                      | 8 mm                | Surface finish                                                                          | Silver passivated, gold |
| Type of connection                                                                      | Crimp connection    | Volume resistance                                                                       | ≤ 2mΩ                   |
| Wire connection cross section AWG, max.                                                 | AWG 12              | Wire connection cross section AWG, min.                                                 | AWG 20                  |
| Wire connection cross section, finely stranded, max.                                    | 2.5 mm <sup>2</sup> | Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max. | 2.5 mm <sup>2</sup>     |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min. | 0.5 mm <sup>2</sup> | Wire connection cross-section, finely stranded, min.                                    | 0.5 mm <sup>2</sup>     |
| Wire cross-section, solid, max.                                                         | 2.5 mm <sup>2</sup> | Wire cross-section, solid, min.                                                         | 0.5 mm <sup>2</sup>     |

### Classifications

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 3.0   | EC000796    | ETIM 4.0   | EC000438    |
| ETIM 5.0   | EC000438    | ETIM 6.0   | EC000438    |
| UNSPSC     | 30-21-18-01 | eClass 5.1 | 27-14-34-19 |
| eClass 6.2 | 27-26-12-04 | eClass 7.1 | 27-44-02-05 |
| eClass 8.1 | 27-44-02-05 | eClass 9.0 | 27-44-02-05 |
| eClass 9.1 | 27-44-02-05 |            |             |

### Approvals

Approvals



ROHS

Conform

### Downloads

|                         |                                                                         |
|-------------------------|-------------------------------------------------------------------------|
| Brochure/Catalogue      | <a href="#">CAT 3 HDC 17/18 EN</a><br><a href="#">FL FIELDWIRING EN</a> |
| Engineering Data        | <a href="#">EPLAN_WSCAD</a>                                             |
| Engineering Data        | <a href="#">STEP</a>                                                    |
| Technical Documentation | <a href="#">1873870000 HDC HA 10 MC STP Blatt_1.pdf</a>                 |

### HDC insert HDC HA 10 MC

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold


Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings



# Tightening torques and screwing tools

| Screw size         | Connector type                          | Dia. tightening torque in Nm                                                      | Recommended blade inserts and AF size for hexagon socket |
|--------------------|-----------------------------------------|-----------------------------------------------------------------------------------|----------------------------------------------------------|
| <b>M 2.5</b>       | <b>Signal contacts</b>                  |                                                                                   |                                                          |
|                    | S 6/6                                   | 0.5 - 0.55                                                                        | SD 0.6 x 3.5 mm or PZ0                                   |
|                    | S 6/12                                  | 0.5 - 0.55                                                                        | SD 0.6 x 3.5 mm or PZ0                                   |
| <b>M 2.9 x 0.5</b> | <b>Fastening screws</b>                 |                                                                                   |                                                          |
|                    | HQ 4/2                                  | 0.8 (plastic) / 1.1 (metal)                                                       | SD 0.6 x 3.5 mm or PH0                                   |
|                    | HQ 8                                    | 0.8 (plastic) / 1.1 (metal)                                                       | SD 0.6 x 3.5 mm or PH0                                   |
|                    | HQ 17                                   | 0.8 (plastic) / 1.1 (metal)                                                       | SD 0.6 x 3.5 mm or PH0                                   |
| <b>M 3</b>         | <b>Contact screws</b>                   |                                                                                   |                                                          |
|                    | HA 3                                    | 0.5 - 0.55                                                                        | SD 0.5 x 3.0 mm                                          |
|                    | HA 4                                    | 0.5 - 0.55                                                                        | SD 0.5 x 3.0 mm                                          |
|                    | HA 10 bis HA 48                         | 0.5 - 0.55                                                                        | SD 0.6 x 3.5 mm or PH0                                   |
|                    | HE                                      | 0.5 - 0.55                                                                        | SD 0.6 x 3.5 mm or PZ0                                   |
|                    | HVE                                     | 0.5 - 0.55                                                                        | SD 0.6 x 3.5 mm or PZ0                                   |
|                    | <b>Signal contacts:</b>                 |                                                                                   |                                                          |
|                    | S 4/2                                   | 0.5 - 0.55                                                                        | SD 0.6 x 3.5 mm or PZ0                                   |
|                    | S 4/8                                   | 0.5 - 0.55                                                                        | SD 0.6 x 3.5 mm or PZ0                                   |
|                    | <b>PE connection via female contact</b> |                                                                                   |                                                          |
|                    | S 4                                     | 0.5 - 0.8                                                                         | SD 0.6 x 3.5 mm                                          |
|                    | ConCept modular frame, metal            | 0.5 - 0.55                                                                        | SD 0.6 x 3.5 mm                                          |
|                    | <b>PE terminal</b>                      |                                                                                   |                                                          |
|                    | HQ 5                                    | 0.5 - 0.55                                                                        | SD 0.6 x 3.5 or 0.8 x 4 mm                               |
|                    | HQ 7                                    | 0.5 - 0.55                                                                        | SD 0.6 x 3.5 or 0.8 x 4 mm                               |
|                    | <b>Fastening screws</b>                 | 0.5 - 0.55                                                                        | SD 0.6 x 3.5 mm or PZ0                                   |
|                    | <b>Guide pin</b>                        | 0.5 - 0.55                                                                        | SD 0.6 x 3.5 mm or PZ0                                   |
|                    | <b>Guide bush</b>                       | 0.5 - 0.55                                                                        | SD 0.6 x 3.5 mm or PZ0                                   |
|                    | <b>Coding pins</b>                      | 0.5 - 0.55                                                                        | SD 0.6 x 3.5 mm or PZ0                                   |
| <b>M 4</b>         | <b>Contact screws</b>                   |                                                                                   |                                                          |
|                    | HSB                                     | 1.2 - 1.5                                                                         | SD 0.6 x 3.5 or 0.8 x 4 mm or PZ1                        |
|                    | <b>PE connection via male contact</b>   |                                                                                   |                                                          |
|                    | S 4                                     | 0.5 - 0.8                                                                         | SD 0.6 x 3.5 mm                                          |
|                    | ConCept modular frame, metal            | 1.2 - 1.5                                                                         | SD 0.6 x 3.5 mm                                          |
|                    | <b>PE terminal</b>                      |                                                                                   |                                                          |
|                    | HA                                      | 1.2 - 1.5                                                                         | SD 0.6 x 3.5 or 0.8 x 4 mm or PH1                        |
|                    | HE                                      | 1.2 - 1.5                                                                         | SD 0.6 x 3.5 or 0.8 x 4 mm or PH1                        |
|                    | HEE                                     | 1.2 - 1.5                                                                         | SD 0.6 x 3.5 or 0.8 x 4 mm or PH1                        |
|                    | HVE                                     | 1.2 - 1.5                                                                         | SD 0.6 x 3.5 or 0.8 x 4 mm or PH1                        |
|                    | HD                                      | 1.2 - 1.5                                                                         | SD 0.6 x 3.5 or 0.8 x 4 mm or PZ1                        |
|                    | HDD                                     | 1.2 - 1.5                                                                         | SD 0.6 x 3.5 or 0.8 x 4 mm or PZ1                        |
|                    | S 6/6 (for signal contacts)             | 1.2 - 1.5                                                                         | 0.8 x 4 mm or PZ1                                        |
|                    | ConCept modular frame, plastic          | 1.2 - 1.5                                                                         | 0.8 x 4 mm or PZ1                                        |
| <b>M 5</b>         | <b>PE terminal</b>                      |                                                                                   |                                                          |
|                    | HSB                                     | 2 - 2.5                                                                           | SD 1 x 5.5 mm or PZ2                                     |
|                    | S 4/0 (Screw connection)                | 2 - 2.5                                                                           | SD 1.2 x 6.5 mm or PH2                                   |
|                    | S 4/0 (Axial screw connection)          | 2 - 2.5                                                                           | SD 0.8 x 4 mm or PZ 2                                    |
|                    | S 4/2                                   | 2 - 2.5                                                                           | SD 1.2 x 6.5 mm or PH2                                   |
|                    | S 4/8                                   | 2 - 2.5                                                                           | SD 1.2 x 6.5 mm or PH2                                   |
|                    | S 6/12                                  | 2 - 2.5                                                                           | SD 0.8 x 4 mm or PZ 2                                    |
|                    | S 6/36                                  | 2 - 2.5                                                                           | SD 1.2 x 6.5 mm or PH2                                   |
|                    | S 8/24                                  | 2 - 2.5                                                                           | SD 1.2 x 6.5 mm or PH2                                   |
|                    | S 12/2                                  | 2 - 2.5                                                                           | SD 1.2 x 6.5 mm or PH2                                   |
| <b>M 6</b>         | <b>Power contacts</b>                   |                                                                                   |                                                          |
|                    | S 4/0 (Screw connection)                | 1.2 (1.5 mm <sup>2</sup> ) / 2 (2.5 mm <sup>2</sup> ) / 3 (4-16 mm <sup>2</sup> ) | SD 0.8 x 4 mm                                            |
|                    | S 4/2                                   | 1.2 (1.5 mm <sup>2</sup> ) / 2 (2.5 mm <sup>2</sup> ) / 3 (4-16 mm <sup>2</sup> ) | SD 0.8 x 4 mm                                            |
|                    | S 4/8                                   | 1.2 (1.5 mm <sup>2</sup> ) / 2 (2.5 mm <sup>2</sup> ) / 3 (4-16 mm <sup>2</sup> ) | SD 0.8 x 4 mm                                            |
| <b>M 7 x 0.75</b>  | <b>Power contacts</b>                   |                                                                                   |                                                          |
|                    | S 4                                     | 1.1 - 1.7                                                                         | SW 2                                                     |
|                    | S 6/6 (+ PE)                            | 6 - 8                                                                             | SW 4                                                     |
| <b>M 8 x 0.75</b>  | <b>Power contacts</b>                   |                                                                                   |                                                          |
|                    | S 6/12                                  | 1.1 - 1.7                                                                         | SW 2                                                     |
|                    | S 8/0 (+ PE)                            | 6 (10-16 mm <sup>2</sup> ) - 7 (25 mm <sup>2</sup> )                              | SW 4                                                     |
| <b>M10 x 1</b>     | <b>Power contacts</b>                   |                                                                                   |                                                          |
|                    | S 4/0 (Axial connection)                | 2 - 3                                                                             | SW 3                                                     |

Increasing the tightening torque does not improve the contact resistance. The stated torque settings offer optimal mechanical, thermal and electrical conditions. Exceeding the recommended values may even damage the conductor and terminal.