

Ballistol Universalöl-Spray

Print date 14.12.2022 Revision date 01.12.2022 Version 13.0 (en)

replaces version of 07.09.2022 (12.3)

* SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name/designation Ballistol Universalöl-Spray

- * 1.2 Relevant identified uses of the substance or mixture and uses advised against
- * Use of the substance/mixture

For the care of metal, wood, leather, rubber, plastic

Remark

UFI: U4PA-H1NJ-M00F-7UN7

1.3 Details of the supplier of the safety data sheet

Manufacturer

F.W.Klever
Hauptstraße 20
D-84168 Aham
Telephone +49 (0) 8744 96 99 10
Telefax + 49 (0) 8744 96 99 96
E-mail info@ballistol.de
Website www.ballistol.de

Department responsible for information:

Qualitätssicherung

Telephone +49 (0) 8744 96 99 80

E-mail (competent person):

info@ballistol.de

* 1.4 Emergency telephone number

Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

* SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP] Classification procedure

Aerosol 1, H222 H229

Hazard statements for physical hazards

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

- * 2.2 Label elements
- * Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms





ES WIRKT.

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Ballistol Universalöl-Spray

Print date 14.12.2022 Revision date 01.12.2022 Version 13.0 (en)

replaces version of 07.09.2022 (12.3)

Signal word

Danger

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Precautionary statements

P102 Keep out of reach of children.

P251 Do not pierce or burn, even after use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P370 + P378 In case of fire: Use water for extinction.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container to recycling

2.3 Other hazards

No data available

SECTION 3: Composition / information on ingredients

3.1 Substances

not applicable

3.2 Mixtures

Hazardous ingredients

CAS No.	EC No.	Substance name	Concentration	Classification according to Regulation (EC) No 1272/2008 [CLP]	SCL/ M/ ATE
107-83-5	203-523-4	hexane (containing < 5-% n- hexane (203-777-6))	< 15 weight-%	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	
106-97-8	203-448-7	butane	10.2 weight-%	Flam. Gas 1; H220 Press. Gas	
74-98-6	200-827-9	propane	4.5 weight-%	Flam. Gas 1; H220 Press. Gas	

SECTION 4: First aid measures

4.1 Description of first aid measures

Following inhalation

Provide fresh air.

In the event of symptoms refer for medical treatment.

Following skin contact

No special measures are necessary.

After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.



Ballistol Universalöl-Spray

Print date 14.12.2022 Revision date 01.12.2022 Version 13.0 (en)

replaces version of 07.09.2022 (12.3)

Following ingestion

No special measure necessary.

4.2 Most important symptoms and effects, both acute and delayed

No data available

4.3 Indication of any immediate medical attention and special treatment needed

Notes for the doctor

Treat symptomatically.

* SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam ABC-powder Carbon dioxide (CO2) Water spray jet

Unsuitable extinguishing media

Strong water jet

* 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

In the event of fire the following can be released: Carbon dioxide (CO2) Nitrogen oxides (NOx)

Carbon monoxid (CO)

5.3 Advice for firefighters

Special protective equipment for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers.

Heating causes rise in pressure with risk of bursting

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Special danger of slipping by leaking/spilling product.

6.2 Environmental precautions

No data available

6.3 Methods and material for containment and cleaning up

For containment

Take up residues with absorbent material (e.g. sawdust).



Ballistol Universalöl-Spray

Print date 14.12.2022 Revision date 01.12.2022 Version 13.0 (en)

replaces version of 07.09.2022 (12.3)

6.4 Reference to other sections

No data available

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Do not spray on naked flames or any incandescent material.

Keep away from sources of ignition - No smoking

Protect aerosols from temperatures exceeding 50°C/ 122°F

Advices on general occupational hygiene

Remove contaminated, saturated clothing immediately.

Wash hands before breaks and after work.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep/Store only in original container.

Storage class

2B Aerosol dispensers and lighters

Further information on storage conditions

Recommended storage temperature: room temperature.

At appropriate storage unlimited stability.

7.3 Specific end use(s)

No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

CAS No.	EC No.	Substance name	occupational exposure limit value
107-83-5	203-523-4	Hexane, all isomers except n-hexane	500 [ml/m³(ppm)] 1800 [mg/m³] Short-term(ml/m³) 1000 Short-term(mg/m³) 3600 (IE)
106-97-8	203-448-7	n-Butane	600 [ml/m³(ppm)] 1450 [mg/m³] Short-term(ml/m³) 750 Short-term(mg/m³) 1810 (UK)
107-83-5	203-523-4	Hexane, all isomers except n-hexane	500 [ml/m³(ppm)] 1800 [mg/m³] (UK)
106-97-8	203-448-7	n-Butane	Short-term(ml/m³) 1000 (1) (1) 15 minutes average value (IE)



Ballistol Universalöl-Spray

Print date 14.12.2022 Revision date 01.12.2022 Version 13.0 (en)

replaces version of 07.09.2022 (12.3)

8.2 Exposure controls

Personal protection equipment

Eye/face protection

With demand: protective glasses

Hand protection

Ballistol is dermatologically tested and rated "very good", so that the hand guard or the skin is not necessary.

Respiratory protection

Respiratory protection must be worn whenever the WEL levels have been exceeded

The following applies to propane in general: If the concentration is exceeded, closed-circuit breathing apparatures must be used

Use filter apparatus type AX, identification colour brown according to EN 371

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state

Aerosol

Colour

light yellow

Odour

characteristic

Safety relevant basis data

	Value	Method	Source, Remark
Odour threshold:	not determined		
Melting point/freezing point	not determined		
Boiling point or initial boiling point and boiling range	-48 °C		(Propan)
flammability	not determined		
Lower and upper explosion limit	Upper explosion limit 10.9 Vol-%		(Propan)
Lower and upper explosion limit	Lower explosion limit approx. 1.5 Vol-%		(Propan)
Flash point	approx104 °C		(Propan)
Auto-ignition temperature	not determined		
Decomposition temperature	not determined		
pH	in delivery state approx. 8 (20°C)		dispersion in water
Viscosity	not determined		
Solubility(ies)	Water solubility (20°C) pressure 1013 hPa		emulsifiable
Partition coefficient n- octanol/water (log value)	not determined		
Vapour pressure	not determined		



ES WIRKT.

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Ballistol Universalöl-Spray

Print date 14.12.2022 Revision date 01.12.2022 Version 13.0 (en)

replaces version of 07.09.2022 (12.3)

Method Source, Remark Value

approx. 0.775 g/mL Density and/or relative density

(20°C)

pressure 1013 mbar

Relative vapour density not determined particle characteristics not determined

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

No data available

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Container under pressure. Protect from direct exposure to sunlight and temperatures exceeding 50°C/122°F.

10.5 Incompatible materials

Oxidising agent, strong

10.6 Hazardous decomposition products

Carbon monoxide Carbon dioxide

Additional information

Product is stable under normal storage conditions

* SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Animal data

	Effective dose	Method, Evaluation	Source, Remark
Acute oral toxicity	> 2000 mg/kg Species Rat		No noticeable toxic effect

Acute dermal toxicity Based on available data, the classification criteria are not

met

Acute inhalation toxicity

* Skin corrosion/irritation

Animal data

Result / Evaluation Method Source, Remark

Practical experience/human evidence. non-sensitising



Ballistol Universalöl-Spray

Print date 14.12.2022 Revision date 01.12.2022 Version 13.0 (en)

replaces version of 07.09.2022 (12.3)

Serious eye damage/irritation

Animal data

Result / Evaluation Method Source, Remark

slightly irritant experiences

* Sensitisation to the respiratory tract

not determined

Skin sensitisation

Animal data

Result / Evaluation Dose / Concentration Method Source, Remark not sensitising. experiences

* Germ cell mutagenicity

Method Value Result / Evaluation Remark

In vitro

mutagenicity/genot oxicity

Carcinogenicity

Animal data

Value Method Result / Evaluation Remark

Carcinogenicity

Reproductive toxicity

Animal data

Value Method Result / Evaluation Remark

Reproductive toxicity

* STOT-single exposure

Overall Assessment on CMR properties

- STOT SE 1 and 2
- **Animal data**

Effective dose Method Specific effects: Organs affected: Source, Remark

Oral specific target

organ toxicity (single exposure)

Species Rat

Dermal specific

target organ

Species Rat

toxicity (single exposure)

Inhalative specific target organ toxicity (single exposure)

Other information

Vzhladom na

dostupné údaje, klasifikacné kritériá nie sú splnené



Ballistol Universalöl-Spray

Print date 14.12.2022 Revision date 01.12.2022 Version 13.0 (en)

replaces version of 07.09.2022 (12.3)

* STOT-repeated exposure

STOT SE 3

Narcotic effects

* Animal data

Effective dose Method Specific effects: Organs affected: Source, Remark

Oral specific target

organ toxicity (repeated exposure)

Species Rat

Oral specific target organ toxicity (repeated exposure)

Dermal specific target organ

Species Rat

toxicity (repeated exposure)

Dermal specific target organ toxicity (repeated exposure)

Inhalative specific target organ toxicity (repeated

Species Rat

toxicity (repeated exposure)

Inhalative specific target organ toxicity (repeated exposure)

Other information

Vzhladom na

dostupné údaje, klasifikacné kritériá nie sú splnené

* Aspiration hazard

* Remark

Based on the available data, the classification criteria are not met

11.2 Information on other hazards

No data available

Other information

Based on the available data, the classification criteria have not been met

SECTION 12: Ecological information

Chronic (long-term) fish toxicity not determined

12.1 Toxicity

Aquatic toxicity

	Effective dose	Method, Evaluation	Source, Remark	
Acute (short-term) fish toxicity	not determined			



Ballistol Universalöl-Spray

Print date 14.12.2022
Revision date 01.12.2022
Version 13.0 (en)

replaces version of 07.09.2022 (12.3)

OECD 301B/ ISO 9439/

EEC 92/69/V, C.4-C

Biodegradable.

	Effective dose	Method,Evaluation	Source, Remark
Acute (short-term) toxicity to crustacea	not determined		
Chronic (long-term) toxicity to aquatic invertebrate	not determined		
Acute (short-term) toxicity to algae and cyanobacteria	not determined		
Chronic (long-term) toxicity to aquatic algae and cyanobacteria	not determined		
Toxicity to other aquatic plants/organisms	not determined		
Toxicity to microorganisms	not determined		
Persistence and degradability			
-	Value	Method	Source, Remark

12.3 Bioaccumulative potential

No data available

Biodegradation

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste codes/waste designations according to EWC/AVV

Waste code product Waste name

130207 * readily biodegradable engine, gear and lubricating oils

Appropriate disposal / Package

Non-contaminated packages may be recycled.

Recycle sales packaging via DSD (Duales System Deutschland).

SECTION 14: Transport information

	Land transport (ADR/RID)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA- DGR)
14.1 UN number or ID number	UN 1950	UN 1950	UN 1950
14.2 UN proper shipping name	AEROSOLS	AEROSOLS	Aerosols, flammable
14.3 Transport hazard class(es)	2.1	2.1	2.1



Ballistol Universalöl-Spray

Print date 14.12.2022 Revision date 01.12.2022 Version 13.0 (en)

replaces version of 07.09.2022 (12.3)

	Land transport (ADR/RID)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA- DGR)
14.4 Packing group	-	-	-
14.5 Environmental hazards	No	No	No

14.6 Special precautions for user

No data available

14.7 Maritime transport in bulk according to IMO instruments

No data available

Land transport (ADR/RID)

UN number or ID number UN 1950 UN proper shipping name AEROSOLS

Transport hazard class(es) 2.1
Hazard label(s) 2.1
Classification code 5F
Packing group Environmental hazards No
Limited quantity (LQ) 1 L

Special provisions 190, 327, 344, 625

Tunnel restriction code D

Sea transport (IMDG)

UN number or ID number UN 1950
UN proper shipping name AEROSOLS

Transport hazard class(es) 2.1
Packing group Environmental hazards No
Limited quantity (LQ) 1 L
Marine pollutant No
EmS F-D, S-U

Air transport (ICAO-TI / IATA-DGR)

UN number or ID number UN 1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es) 2.1
Packing group Environmental hazards No

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

No data available



Ballistol Universalöl-Spray

Print date 14.12.2022 Revision date 01.12.2022 Version 13.0 (en)

replaces version of 07.09.2022 (12.3)

15.2 Chemical Safety Assessment

For this substance a chemical safety assessment is not required.

SECTION 16: Other information

Additional information

National and local regulations concerning chemicals shall be observed.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Relevant H- and EUH-phrases (Number and full text)

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Indication of changes

* Data changed compared with the previous version