



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 18

Pattex Powerkleber Stabilit Express

SDS No. : 43189
V004.1

Revision: 21.10.2022

printing date: 08.12.2022

Replaces version from: 29.06.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Pattex Powerkleber Stabilit Express, Harz

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

2-Component methyl methacrylate adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

| | |
|--|------------|
| Flammable liquids | Category 2 |
| H225 Highly flammable liquid and vapour. | |
| Skin irritation | Category 2 |
| H315 Causes skin irritation. | |
| Serious eye irritation | Category 2 |
| H319 Causes serious eye irritation. | |
| Skin sensitizer | Category 1 |
| H317 May cause an allergic skin reaction. | |
| Specific target organ toxicity - single exposure | Category 3 |
| H335 May cause respiratory irritation. | |

2.2. Label elements

Label elements (CLP):

Hazard pictogram:**Contains**

methyl methacrylate

Signal word:

Danger

Hazard statement:

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

Precautionary statement:

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P261 Avoid breathing vapors.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/eye protection.
P501 Dispose of contents/container in accordance with national regulation.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

Following substances are present in a concentration $\geq 0,1\%$ and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):This mixture does not contain any substances in concentration \geq the concentration limit that are assessed to be a PBT, vPvB or ED.**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components CAS-No. EC Number REACH-Reg No. | Concentration | Classification | Specific Conc. Limits, M-factors and ATEs | Add. Information |
|---|----------------------|--|--|-------------------------|
| methyl methacrylate 80-62-6 201-297-1 01-2119452498-28 | 20- 40 % | Flam. Liq. 2, H225 STOT SE 3, H335 Skin Irrit. 2, H315 Skin Sens. 1, H317 | STOT SE 3; H335; C >= 10 % | EU OEL |
| Vinyltoluene 25013-15-4 246-562-2 01-2119622074-50 | 10- < 20 % | Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, Inhalation, H332 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 | | |
| 1,1'-(p-Tolylimino)dipropan-2-ol 38668-48-3 254-075-1 | 0,1- < 1 % | Acute Tox. 3, Oral, H301 Eye Irrit. 2, H319 Aquatic Chronic 3, H412 | | |
| Hydroquinone 123-31-9 204-617-8 01-2119524016-51 | 0,1- < 1 % | Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Carc. 2, H351 Muta. 2, H341 Acute Tox. 4, Oral, H302 Eye Dam. 1, H318 Skin Sens. 1, H317 | M acute = 10 M chronic = 1 | |

**For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.**

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing. If necessary, see a dermatologist.

Eye contact:

Immediately flush eyes with soft jet of water or eye rinse solution for at least 5 minutes. If pains remain (intensive smarting, sensitivity to light, visual disturbance) continue flushing and contact/seek doctor or hospital.

Ingestion:

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Redness, inflammation.

May cause an allergic skin reaction.

Causes serious eye irritation.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media:**

carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

Can form explosive gas/air mixtures.

5.3. Advice for firefighters

Wear protective equipment.

Wear self-contained breathing apparatus.

Additional information:

Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective equipment.

Danger of slipping on spilled product.

Avoid contact with skin and eyes.

Ensure adequate ventilation.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Ensure that workrooms are adequately ventilated.

Take measures to prevent the build-up of electrostatic charges.

Avoid naked flames, sparking and sources of ignition.

Avoid skin and eye contact.

Hygiene measures:

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Keep only in original container.

Keep container in a well ventilated place.

Store protected from heat influence.

Temperatures between 0 °C and + 30 °C

Store in a cool place, max. storage temperature 30°C.

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

7.3. Specific end use(s)

2-Component methyl methacrylate adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|---|-----|-------------------|-----------------------------------|--|-----------------|
| Methyl methacrylate 80-62-6 [METHYL METHACRYLATE] | 50 | 208 | Time Weighted Average (TWA): | | EH40 WEL |
| Methyl methacrylate 80-62-6 [METHYL METHACRYLATE] | 100 | | Short Term Exposure Limit (STEL): | Indicative | ECLTV |
| Methyl methacrylate 80-62-6 [METHYL METHACRYLATE] | 50 | | Time Weighted Average (TWA): | Indicative | ECLTV |
| Methyl methacrylate 80-62-6 [METHYL METHACRYLATE] | 100 | 416 | Short Term Exposure Limit (STEL): | 15 minutes | EH40 WEL |

Occupational Exposure Limits

Valid for
Ireland

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|--|-----|-------------------|-----------------------------------|--|-----------------|
| Methyl methacrylate 80-62-6 [METHYL METHACRYLATE] | 50 | | Time Weighted Average (TWA): | Indicative OELV | IR_OEL |
| Methyl methacrylate 80-62-6 [METHYL METHACRYLATE] | 100 | | Short Term Exposure Limit (STEL): | Indicative | ECLTV |
| Methyl methacrylate 80-62-6 [METHYL METHACRYLATE] | 50 | | Time Weighted Average (TWA): | Indicative | ECLTV |
| Methyl methacrylate 80-62-6 [METHYL METHACRYLATE] | 100 | | Short Term Exposure Limit (STEL): | 15 minutes Indicative OELV | IR_OEL |
| Vinyltoluene 25013-15-4 [METHYLSTYRENE, ALL ISOMERS] | 50 | 242 | Time Weighted Average (TWA): | | IR_OEL |
| Vinyltoluene 25013-15-4 [METHYLSTYRENE, ALL ISOMERS] | 10 | 483 | Short Term Exposure Limit (STEL): | 15 minutes | IR_OEL |

Predicted No-Effect Concentration (PNEC):

| Name on list | Environmental Compartment | Exposure period | Value | | | | Remarks |
|--------------------------------|------------------------------------|-----------------|------------------|-----|------------------|--------|---------|
| | | | mg/l | ppm | mg/kg | others | |
| methyl methacrylate 80-62-6 | aqua (freshwater) | | 0,94 mg/l | | | | |
| methyl methacrylate 80-62-6 | aqua (marine water) | | 0,94 mg/l | | | | |
| methyl methacrylate 80-62-6 | aqua (intermittent releases) | | 0,94 mg/l | | | | |
| methyl methacrylate 80-62-6 | sewage treatment plant (STP) | | 10 mg/l | | | | |
| methyl methacrylate 80-62-6 | sediment (freshwater) | | | | 5,74 mg/kg | | |
| methyl methacrylate 80-62-6 | Soil | | | | 1,47 mg/kg | | |
| Vinytoluene 25013-15-4 | aqua (freshwater) | | 0,05 mg/l | | | | |
| Vinytoluene 25013-15-4 | aqua (marine water) | | 0,002 mg/l | | | | |
| Vinytoluene 25013-15-4 | aqua (intermittent releases) | | 0,013 mg/l | | | | |
| Vinytoluene 25013-15-4 | sewage treatment plant (STP) | | 1 mg/l | | | | |
| Vinytoluene 25013-15-4 | sediment (freshwater) | | | | 0,684 mg/kg | | |
| Vinytoluene 25013-15-4 | sediment (marine water) | | | | 0,068 mg/kg | | |
| Vinytoluene 25013-15-4 | Soil | | | | 0,133 mg/kg | | |
| Vinytoluene 25013-15-4 | oral | | | | 2,5 mg/kg | | |
| Hydroquinone 123-31-9 | aqua (freshwater) | | 0,00057 mg/l | | | | |
| Hydroquinone 123-31-9 | aqua (marine water) | | 0,000057 mg/l | | | | |
| Hydroquinone 123-31-9 | sediment (freshwater) | | | | 0,0049 mg/kg | | |
| Hydroquinone 123-31-9 | sediment (marine water) | | | | 0,00049 mg/kg | | |
| Hydroquinone 123-31-9 | aqua (intermittent releases) | | 0,00134 mg/l | | | | |
| Hydroquinone 123-31-9 | Soil | | | | 0,00064 mg/kg | | |
| Hydroquinone 123-31-9 | sewage treatment plant (STP) | | 0,71 mg/l | | | | |

Derived No-Effect Level (DNEL):

| Name on list | Application Area | Route of Exposure | Health Effect | Exposure Time | Value | Remarks |
|--------------------------------|--------------------|-------------------|--|---------------|------------------------|---------|
| methyl methacrylate 80-62-6 | Workers | dermal | Acute/short term exposure - local effects | | 1,5 mg/cm ² | |
| methyl methacrylate 80-62-6 | Workers | dermal | Long term exposure - systemic effects | | 13,67 mg/kg | |
| methyl methacrylate 80-62-6 | Workers | Inhalation | Long term exposure - systemic effects | | 208 mg/m ³ | |
| methyl methacrylate 80-62-6 | Workers | dermal | Long term exposure - local effects | | 1,5 mg/cm ² | |
| methyl methacrylate 80-62-6 | Workers | Inhalation | Long term exposure - local effects | | 208 mg/m ³ | |
| methyl methacrylate 80-62-6 | General population | dermal | Acute/short term exposure - local effects | | 1,5 mg/cm ² | |
| methyl methacrylate 80-62-6 | General population | dermal | Long term exposure - systemic effects | | 8,2 mg/kg | |
| methyl methacrylate 80-62-6 | General population | Inhalation | Long term exposure - systemic effects | | 74,3 mg/m ³ | |
| methyl methacrylate 80-62-6 | General population | dermal | Long term exposure - local effects | | 1,5 mg/cm ² | |
| methyl methacrylate 80-62-6 | General population | Inhalation | Long term exposure - local effects | | 104 mg/m ³ | |
| Vinytoluene 25013-15-4 | Workers | inhalation | Long term exposure - systemic effects | | 37 mg/m ³ | |
| Vinytoluene 25013-15-4 | Workers | inhalation | Acute/short term exposure - systemic effects | | 37 mg/m ³ | |
| Hydroquinone 123-31-9 | Workers | dermal | Long term exposure - systemic effects | | 3,33 mg/kg | |
| Hydroquinone 123-31-9 | Workers | inhalation | Long term exposure - systemic effects | | 2,1 mg/m ³ | |
| Hydroquinone 123-31-9 | General population | dermal | Long term exposure - systemic effects | | 1,66 mg/kg | |
| Hydroquinone 123-31-9 | General population | inhalation | Long term exposure - systemic effects | | 1,05 mg/m ³ | |
| Hydroquinone 123-31-9 | General population | oral | Long term exposure - systemic effects | | 0,6 mg/kg | |

Biological Exposure Indices:

None

8.2. Exposure controls:

Respiratory protection:

Suitable breathing mask when there is inadequate ventilation.

Combination filter: ABEKP (EN 14387)

This recommendation should be matched to local conditions.

Hand protection:

Recommended are gloves made from Nitril rubber (Material thickness >0,1 mm, Perforation time < 30s).Gloves should be replaced after each short time contact or contamination. Available at laboratory specialized trade or at pharmacies / chemist's shops.

In the case of longer contact protective gloves made from nitrile rubber are recommended according to EN 374.

material thickness > 0.4 mm

Perforation time > 10 minutes

In the case of longer and repeated contact please note that in practice the penetration times may be considerably shorter than those determined according to EN 374. The protective gloves must always be checked for their suitability for use at the specific workplace (e.g. mechanical and thermal stress, product compatibility, antistatic effects, etc.). The gloves must be replaced immediately at the first signs of wear and tear. The information provided by the manufacturers and given in the relevant trade association regulations for industrial safety must always be observed. We recommend that a hand care plan is drawn up in cooperation with a glove manufacturer and the trade association in accordance with the local operating conditions.

Eye protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

Skin protection:

Suitable protective clothing

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties

| | |
|---|---|
| Physical state | liquid |
| Delivery form | liquid |
| Colour | brown |
| Odor | characteristic |
| Melting point | Not applicable, Product is a liquid |
| Initial boiling point | Currently under determination |
| Flammability | Currently under determination |
| Explosive limits | |
| lower | 1,1 %(V); No data available. |
| upper | 12,5 %(V); No data available. The product is not explosive. The formation of explosive vapor/air mixtures is possible. |
| Flash point | 10 °C (50 °F); no method |
| Auto-ignition temperature | Currently under determination |
| Decomposition temperature | Currently under determination |
| pH | Not applicable |
| Viscosity (kinematic) | Currently under determination |
| Viscosity, dynamic (Brookfield; 20 °C (68 °F)) | 15.000 - 25.000 mPa.s no method |
| Solubility (qualitative) (23 °C (73.4 °F); Solvent: Water) | Partially soluble |
| Partition coefficient: n-octanol/water | Not applicable |
| Vapour pressure | Mixture Currently under determination |
| Density (20 °C (68 °F)) | 0,96 - 1,00 g/cm ³ no method |
| Relative vapour density: | Currently under determination |
| Particle characteristics | Not applicable Product is a liquid |

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reducing agents.
Strong oxidizing agents.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information

General toxicological information:

Persons suffering from allergic reactions to acrylates should avoid contact with the product.

1.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|--|---------------|-------------|---------|---|
| methyl methacrylate 80-62-6 | LD50 | 9.400 mg/kg | rat | not specified |
| 1,1'-(p-Tolylimino)dipropan-2-ol 38668-48-3 | LD50 | 100 mg/kg | rat | equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity) |
| Hydroquinone 123-31-9 | LD50 | 367 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|--|---------------|---------------|---------|--|
| methyl methacrylate 80-62-6 | LD50 | > 5.000 mg/kg | rabbit | not specified |
| 1,1'-(p-Tolylimino)dipropan-2-ol 38668-48-3 | LD50 | > 2.000 mg/kg | rat | OECD Guideline 402 (Acute Dermal Toxicity) |
| Hydroquinone 123-31-9 | LD50 | > 2.000 mg/kg | rabbit | OECD Guideline 402 (Acute Dermal Toxicity) |

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Test atmosphere | Exposure time | Species | Method |
|---------------------------------|---------------|-----------|-----------------|------------------|---------|---------------|
| methyl methacrylate 80-62-6 | LC50 | 29,8 mg/l | vapour | 4 h | rat | not specified |

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|--|----------------|------------------|---------|--|
| 1,1'-(p-Tolylimino)dipropan-2-ol 38668-48-3 | not irritating | 4 h | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |
| Hydroquinone 123-31-9 | not irritating | 24 h | rabbit | Weight of evidence |

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|--|------------|------------------|---------|---|
| 1,1'-(p-Tolylimino)dipropan-2-ol 38668-48-3 | irritating | 24 h | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Test type | Species | Method |
|--|-----------------|---------------------------------------|------------|--|
| methyl methacrylate 80-62-6 | sensitising | Mouse local lymphnode assay (LLNA) | mouse | OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |
| 1,1'-(p-Tolylimino)dipropan-2-ol 38668-48-3 | not sensitising | Guinea pig maximisation test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |
| Hydroquinone 123-31-9 | sensitising | Guinea pig maximisation test | guinea pig | equivalent or similar to OECD Guideline 406 (Skin Sensitisation) |
| Hydroquinone 123-31-9 | sensitising | Mouse local lymphnode assay (LLNA) | mouse | equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Type of study / Route of administration | Metabolic activation / Exposure time | Species | Method |
|------------------------------|----------|--|--------------------------------------|---------|---|
| methyl methacrylate 80-62-6 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | not specified |
| Hydroquinone 123-31-9 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Hydroquinone 123-31-9 | negative | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Hydroquinone 123-31-9 | positive | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Hydroquinone 123-31-9 | positive | intraperitoneal | | mouse | equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test) |
| Hydroquinone 123-31-9 | negative | oral: gavage | | rat | equivalent or similar to OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test) |
| Hydroquinone 123-31-9 | positive | intraperitoneal | | mouse | equivalent or similar to OECD Guideline 483 (Mammalian Spermatogonial Chromosome Aberration Test) |

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous components CAS-No. | Result | Route of application | Exposure time / Frequency of treatment | Species | Sex | Method |
|------------------------------|--------------|----------------------|--|---------|-------------|--|
| Hydroquinone 123-31-9 | carcinogenic | oral: gavage | 103 w 5 d/w | rat | male/female | equivalent or similar OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies) |
| Hydroquinone 123-31-9 | carcinogenic | oral: gavage | 103 w 5 d/w | mouse | female | equivalent or similar OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies) |

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Test type | Route of application | Species | Method |
|------------------------------|--|----------------------|----------------------|---------|---|
| Hydroquinone 123-31-9 | NOAEL P 15 mg/kg NOAEL F1 150 mg/kg NOAEL F2 150 mg/kg | Two generation study | oral: gavage | rat | EPA OTS 798.4700 (Reproduction and Fertility Effects) |

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Route of application | Exposure time / Frequency of treatment | Species | Method |
|---|-----------------------|---------------------------------|---|----------------|---|
| methyl methacrylate 80-62-6 | LOAEL 2000 ppm | inhalation | 14 weeks 6 hrs/day, 5 days/wk | mouse | Dose Range Finding Study |
| methyl methacrylate 80-62-6 | NOAEL 1000 ppm | inhalation | 14 weeks 6 hrs/day, 5 days/wk | mouse | Dose Range Finding Study |
| Hydroquinone 123-31-9 | NOAEL 50 mg/kg | oral: gavage | 13 w 5 d/w | rat | not specified |
| Hydroquinone 123-31-9 | NOAEL 73,9 mg/kg | dermal | 13 w 6 h/d, 5 d/w | rat | equivalent or similar to OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study) |

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

LC50 > 10 - <= 100 mg product/l.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|------------|---------------|--|--|
| methyl methacrylate 80-62-6 | LC50 | 350 mg/l | 96 h | Leuciscus idus | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Vinyltoluene 25013-15-4 | LC50 | 5,2 mg/l | 96 h | Pimephales promelas | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| 1,1'-(p-Tolylimino)dipropan- 2-ol 38668-48-3 | LC50 | 17 mg/l | 96 h | Brachydanio rerio (new name: Danio rerio) | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Hydroquinone 123-31-9 | LC50 | 0,638 mg/l | 96 h | Oncorhynchus mykiss | OECD Guideline 203 (Fish, Acute Toxicity Test) |

Toxicity (Daphnia):

EC50 > 10 - <= 100 mg product/l.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|------------|---------------|---------------|---|
| methyl methacrylate 80-62-6 | EC50 | 69 mg/l | 48 h | Daphnia magna | EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids) |
| Vinyltoluene 25013-15-4 | EC50 | 1,3 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| 1,1'-(p-Tolylimino)dipropan- 2-ol 38668-48-3 | EC50 | 28,8 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Hydroquinone 123-31-9 | EC50 | 0,134 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---------------------------------|---------------|-------------|---------------|---------------|--|
| methyl methacrylate 80-62-6 | NOEC | 37 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
| Hydroquinone 123-31-9 | NOEC | 0,0057 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |

Toxicity (Algae):

EC50 > 10 - <= 100 mg product/l.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---------------------------------|---------------|------------|---------------|---|--|
| methyl methacrylate 80-62-6 | EC50 | 170 mg/l | 96 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| methyl methacrylate 80-62-6 | NOEC | 100 mg/l | 96 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Vinyltoluene 25013-15-4 | EC50 | 2,6 mg/l | 72 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Vinyltoluene 25013-15-4 | NOEC | 1,6 mg/l | 72 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Hydroquinone 123-31-9 | EC50 | 0,335 mg/l | 72 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---------------------------------|---------------|------------------|---------------|----------------------------|---|
| methyl methacrylate 80-62-6 | EC20 | > 150 - 200 mg/l | 30 min | activated sludge, domestic | ISO 8192 (Test for Inhibition of Oxygen Consumption by Activated Sludge) |
| Hydroquinone 123-31-9 | EC 50 | 0,038 mg/l | 30 min | | not specified |

12.2. Persistence and degradability

| Hazardous substances CAS-No. | Result | Test type | Degradability | Exposure time | Method |
|--|-----------------------|-----------|---------------|------------------|---|
| methyl methacrylate 80-62-6 | readily biodegradable | aerobic | 94 % | 14 d | OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I)) |
| 1,1'-(p-Tolylimino)dipropan- 2-ol 38668-48-3 | | | < 20 % | | OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test) |
| 1,1'-(p-Tolylimino)dipropan- 2-ol 38668-48-3 | | aerobic | < 1 % | 28 d | OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test) |
| Hydroquinone 123-31-9 | readily biodegradable | aerobic | 75 - 81 % | 30 d | EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test) |

12.3. Bioaccumulative potential

| Hazardous substances CAS-No. | Bioconcentratio n factor (BCF) | Exposure time | Temperature | Species | Method |
|---------------------------------|-----------------------------------|---------------|-------------|------------------------|---------------|
| Vinyltoluene 25013-15-4 | 96 - 180 | 30 d | | Lepomis macrochirus | not specified |

12.4. Mobility in soil

| Hazardous substances CAS-No. | LogPow | Temperature | Method |
|--|--------|-------------|--|
| methyl methacrylate 80-62-6 | 1,38 | 20 °C | other guideline: |
| Vinyltoluene 25013-15-4 | 3,35 | 25 °C | not specified |
| 1,1'-(p-Tolylimino)dipropan-2-ol 38668-48-3 | 1,47 | | OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method) |
| Hydroquinone 123-31-9 | 0,59 | | EU Method A.8 (Partition Coefficient) |

12.5. Results of PBT and vPvB assessment

| Hazardous substances CAS-No. | PBT / vPvB |
|--|---|
| methyl methacrylate 80-62-6 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Vinyltoluene 25013-15-4 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| 1,1'-(p-Tolylimino)dipropan-2-ol 38668-48-3 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Hydroquinone 123-31-9 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code

080409

SECTION 14: Transport information**14.1. UN number or ID number**

| | |
|------|------|
| ADR | 1133 |
| RID | 1133 |
| ADN | 1133 |
| IMDG | 1133 |
| IATA | 1133 |

14.2. UN proper shipping name

| | |
|------|-----------|
| ADR | ADHESIVES |
| RID | ADHESIVES |
| ADN | ADHESIVES |
| IMDG | ADHESIVES |
| IATA | Adhesives |

14.3. Transport hazard class(es)

| | |
|------|---|
| ADR | 3 |
| RID | 3 |
| ADN | 3 |
| IMDG | 3 |
| IATA | 3 |

14.4. Packing group

| | |
|------|-----|
| ADR | III |
| RID | III |
| ADN | III |
| IMDG | III |
| IATA | III |

14.5. Environmental hazards

| | |
|------|----------------|
| ADR | not applicable |
| RID | not applicable |
| ADN | not applicable |
| IMDG | not applicable |
| IATA | not applicable |

14.6. Special precautions for user

| | |
|------|-----------------------------------|
| ADR | not applicable Tunnelcode: (E) |
| RID | not applicable |
| ADN | not applicable |
| IMDG | not applicable |
| IATA | not applicable |

Packed goods < 450 L (ADR/IMDG) can be classified in packaging group III, based of the viscosity (ADR 2.2.3.1.4 und IMDG 2.3.2.2)

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

| | |
|---|----------------|
| Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009): | Not applicable |
| Prior Informed Consent (PIC) (Regulation (EU) No 649/2012): | Not applicable |
| Persistent organic pollutants (Regulation (EU) 2019/1021): | Not applicable |
| VOC content | 71,00 % |
| (VOCV 814.018 VOC regulation CH) | |

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H301 Toxic if swallowed.
 H302 Harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H341 Suspected of causing genetic defects.
 H351 Suspected of causing cancer.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

| | |
|-------------|---|
| ED: | Substance identified as having endocrine disrupting properties |
| EU OEL: | Substance with a Union workplace exposure limit |
| EU EXPLD 1: | Substance listed in Annex I, Reg (EC) No. 2019/1148 |
| EU EXPLD 2 | Substance listed in Annex II, Reg (EC) No. 2019/1148 |
| SVHC: | Substance of very high concern (REACH Candidate List) |
| PBT: | Substance fulfilling persistent, bioaccumulative and toxic criteria |
| PBT/vPvB: | Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria |
| vPvB: | Substance fulfilling very persistent and very bioaccumulative criteria |

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.



Safety Data Sheet according to (EC) No 1907/2006 as amended Page 1 of 12

Pattex Powerkleber Stabilit Express

SDS No. : 43188
V004.1

Revision: 21.10.2022
printing date: 08.12.2022

Replaces version from: 25.11.2003

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Pattex Powerkleber Stabilit Express, Härter

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

2-Component methyl methacrylate adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Ltd
Adhesives
Wood Lane End
HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

| | |
|--|------------|
| Organic peroxides | Type C |
| H242 Heating may cause a fire. | |
| Serious eye irritation | Category 2 |
| H319 Causes serious eye irritation. | |
| Skin sensitizer | Category 1 |
| H317 May cause an allergic skin reaction. | |
| Acute hazards to the aquatic environment | Category 1 |
| H400 Very toxic to aquatic life. | |
| Chronic hazards to the aquatic environment | Category 1 |
| H410 Very toxic to aquatic life with long lasting effects. | |

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains Dibenzoyl peroxide

Signal word: Danger

Hazard statement:
 H242 Heating may cause a fire.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H410 Very toxic to aquatic life with long lasting effects.

Precautionary statement:
 P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P235 Keep cool.
 P280 Wear protective gloves/eye protection.
 P501 Dispose of contents/container in accordance with national regulation.

2.3. Other hazards

None if used properly.
 Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

Following substances are present in a concentration >= 0,1% and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in concentration ≥ the concentration limit that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components CAS-No. EC Number REACH-Reg No. | Concentration | Classification | Specific Conc. Limits, M-factors and ATEs | Add. Information |
|--|---------------|---|---|------------------|
| Dibenzoyl peroxide 94-36-0 202-327-6 01-2119511472-50 | 10- 20 % | Org. Perox. B, H241 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 | M acute = 10 M chronic = 10 | |

**For full text of the H - statements and other abbreviations see section 16 "Other information".
 Substances without classification may have community workplace exposure limits available.**

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:
 In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Skin care. Remove contaminated clothes immediately.

Eye contact:

Immediately flush eyes with soft jet of water or eye rinse solution for at least 5 minutes. If pains remain (intensive smarting, sensitivity to light, visual disturbance) continue flushing and contact/seek doctor or hospital. Do not rub eyes; mechanical action may cause corneal damage.

Ingestion:

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media:**

carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

Intensifies fire by releasing oxygen.

5.3. Advice for firefighters

Wear protective equipment.

Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective equipment.

Avoid contact with skin and eyes.

Avoid dust formation.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove mechanically.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid naked flames, sparking and sources of ignition.
 Avoid skin and eye contact.
 Avoid dust formation.

Hygiene measures:

Do not eat, drink or smoke while working.
 Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool place in closed original container.
 Temperatures between 0 °C and + 30 °C
 Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

7.3. Specific end use(s)

2-Component methyl methacrylate adhesive

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**

Valid for
 Great Britain

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|---|-----|-------------------|------------------------------|--|-----------------|
| Dibenzoyl peroxide 94-36-0 [DIBENZOYL PEROXIDE] | | 5 | Time Weighted Average (TWA): | | EH40 WEL |
| Magnesium carbonate 546-93-0 [MAGNESITE, INHALABLE DUST] | | 10 | Time Weighted Average (TWA): | | EH40 WEL |
| Magnesium carbonate 546-93-0 [MAGNESITE, RESPIRABLE DUST] | | 4 | Time Weighted Average (TWA): | | EH40 WEL |

Occupational Exposure Limits

Valid for
 Ireland

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|---|-----|-------------------|------------------------------|--|-----------------|
| Calcium sulfate 7778-18-9 [CALCIUM SULPHATE] | | 10 | Time Weighted Average (TWA): | | IR_OEL |
| Dibenzoyl peroxide 94-36-0 [DIBENZOYL PEROXIDE] | | 5 | Time Weighted Average (TWA): | | IR_OEL |

Predicted No-Effect Concentration (PNEC):

| Name on list | Environmental Compartment | Exposure period | Value | | | | Remarks |
|----------------------------|------------------------------|-----------------|---------------|-----|-------------|--------|---------|
| | | | mg/l | ppm | mg/kg | others | |
| Dibenzoyl peroxide 94-36-0 | aqua (freshwater) | | 0,00002 mg/l | | | | |
| Dibenzoyl peroxide 94-36-0 | aqua (marine water) | | 0,000002 mg/l | | | | |
| Dibenzoyl peroxide 94-36-0 | sewage treatment plant (STP) | | 0,35 mg/l | | | | |
| Dibenzoyl peroxide 94-36-0 | sediment (freshwater) | | | | 0,013 mg/kg | | |
| Dibenzoyl peroxide 94-36-0 | Soil | | | | 0,003 mg/kg | | |
| Dibenzoyl peroxide 94-36-0 | sediment (marine water) | | | | 0,001 mg/kg | | |

Derived No-Effect Level (DNEL):

| Name on list | Application Area | Route of Exposure | Health Effect | Exposure Time | Value | Remarks |
|----------------------------|--------------------|-------------------|---------------------------------------|---------------|--------------|---------|
| Dibenzoyl peroxide 94-36-0 | Workers | Inhalation | Long term exposure - systemic effects | | 39 mg/m3 | |
| Dibenzoyl peroxide 94-36-0 | Workers | dermal | Long term exposure - systemic effects | | 13,3 mg/kg | |
| Dibenzoyl peroxide 94-36-0 | Workers | dermal | Long term exposure - local effects | | 0,034 mg/cm2 | |
| Dibenzoyl peroxide 94-36-0 | General population | oral | Long term exposure - systemic effects | | 2 mg/kg | |

Biological Exposure Indices:

None

8.2. Exposure controls:**Respiratory protection:**

In case of dust formation, we recommend wearing of appropriate respiratory protection equipment with particle filter P (EN 14387).

This recommendation should be matched to local conditions.

Hand protection:

Recommended are gloves made from Nitril rubber (Material thickness >0,1 mm, Perforation time < 30s).Gloves should be replaced after each short time contact or contamination. Available at laboratory specialized trade or at pharmacies / chemist's shops.

In the case of longer contact protective gloves made from nitrile rubber are recommended according to EN 374. material thickness > 0.4 mm

Perforation time > 10 minutes

In the case of longer and repeated contact please note that in practice the penetration times may be considerably shorter than those determined according to EN 374. The protective gloves must always be checked for their suitability for use at the specific workplace (e.g. mechanical and thermal stress, product compatibility, antistatic effects, etc.). The gloves must be replaced immediately at the first signs of wear and tear. The information provided by the manufacturers and given in the relevant trade association regulations for industrial safety must always be observed. We recommend that a hand care plan is drawn up in cooperation with a glove manufacturer and the trade association in accordance with the local operating conditions.

Eye protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

Skin protection:

Suitable protective clothing

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|---|
| Physical state | solid |
| Delivery form | powder |
| Colour | white |
| Odor | odourless |
| Solidification temperature | Not applicable, Product is a solid. |
| Initial boiling point | Currently under determination |
| Flammability | Currently under determination |
| Explosive limits | Not applicable, Product is a solid. |
| Flash point | Not applicable, Product is a solid. |
| Auto-ignition temperature | Not applicable, Product is a solid. |
| Decomposition temperature | Currently under determination |
| pH | Not applicable |
| Viscosity (kinematic) | Not applicable, Product is a solid. |
| Solubility (qualitative) | Insoluble |
| (23 °C (73.4 °F); Solvent: Water) | |
| Partition coefficient: n-octanol/water | Not applicable |
| | Mixture |
| Vapour pressure | Currently under determination |
| Density | 0,5000 g/ml Supplier method |
| (20 °C (68 °F)) | |
| Bulk density | 450 - 550 g/l DIN ISO 697-84 Bulk density |
| Relative vapour density: | Not applicable, Product is a solid. |
| Particle characteristics | Currently under determination |

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Strong oxidizing agents.

Reducing agents.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

At higher temperature possible generation of :

carbon dioxide
Benzoic acid
Benzene
Biphenyl
Phenyl benzoate

SECTION 11: Toxicological information

General toxicological information:

Persons suffering from allergic reactions to peroxides should avoid contact with the product.

1.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|---------------------------------|---------------|---------------|---------|--|
| Dibenzoyl peroxide 94-36-0 | LD50 | > 2.000 mg/kg | mouse | OECD Guideline 401 (Acute Oral Toxicity) |

Acute dermal toxicity:

No data available.

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Test atmosphere | Exposure time | Species | Method |
|---------------------------------|---------------|-------------|-----------------|------------------|---------|---|
| Dibenzoyl peroxide 94-36-0 | LC0 | 24,3 mg/l | dust/mist | 4 h | rat | equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity) |
| Dibenzoyl peroxide 94-36-0 | LC50 | > 24,3 mg/l | dust/mist | 4 h | rat | equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity) |

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|---------------------------------|----------------|------------------|---------|---|
| Dibenzoyl peroxide 94-36-0 | not irritating | 4 h | rabbit | equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|---------------------------------|----------------|------------------|---------|---------------|
| Dibenzoyl peroxide 94-36-0 | not irritating | | rabbit | FDA Guideline |

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Test type | Species | Method |
|---------------------------------|-------------|---------------------------------------|---------|--|
| Dibenzoyl peroxide 94-36-0 | sensitising | Mouse local lymphnode assay (LLNA) | mouse | equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Type of study / Route of administration | Metabolic activation / Exposure time | Species | Method |
|---------------------------------|----------|--|--|---------|---|
| Dibenzoyl peroxide 94-36-0 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Dibenzoyl peroxide 94-36-0 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Dibenzoyl peroxide 94-36-0 | negative | intraperitoneal | | mouse | OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test) |

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous components CAS-No. | Result | Route of application | Exposure time / Frequency of treatment | Species | Sex | Method |
|---------------------------------|------------------|-------------------------|---|---------|-------------|---|
| Dibenzoyl peroxide 94-36-0 | not carcinogenic | dermal | 2 y daily | rat | male/female | equivalent or similar OECD Guideline 451 (Carcinogenicity Studies) |

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Test type | Route of application | Species | Method |
|---------------------------------|--|-----------|-------------------------|---------|---|
| Dibenzoyl peroxide 94-36-0 | NOAEL P >= 1.000 mg/kg NOAEL F1 500 mg/kg | screening | oral: gavage | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Route of application | Exposure time / Frequency of treatment | Species | Method |
|---------------------------------|-------------------|-------------------------|--|---------|---|
| Dibenzoyl peroxide 94-36-0 | NOAEL 190 mg/kg | oral: feed | 120 w daily | rat | not specified |
| Dibenzoyl peroxide 94-36-0 | NOAEL > 833 mg/kg | dermal | 104 w daily | mouse | OECD Guideline 451 (Carcinogenicity Studies) |

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information**General ecological information:**

Do not empty into drains, soil or bodies of water.

12.1. Toxicity**Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---------------------------------|---------------|-----------|---------------|---------------------|---|
| Dibenzoyl peroxide 94-36-0 | LC50 | 0,06 mg/l | 96 h | Oncorhynchus mykiss | OECD Guideline 203 (Fish, Acute Toxicity Test) |

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---------------------------------|---------------|-----------|---------------|---------------|--|
| Dibenzoyl peroxide 94-36-0 | EC50 | 0,11 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---------------------------------|---------------|------------|---------------|---------------|--|
| Dibenzoyl peroxide 94-36-0 | EC10 | 0,001 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---------------------------------|---------------|------------|---------------|---------------------------------|--|
| Dibenzoyl peroxide 94-36-0 | ErC50 | 0,071 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Dibenzoyl peroxide 94-36-0 | NOEC | 0,02 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---------------------------------|---------------|---------|---------------|--|--|
| Dibenzoyl peroxide 94-36-0 | EC 50 | 35 mg/l | 30 min | activated sludge of a predominantly domestic sewage | OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test) |

12.2. Persistence and degradability

| Hazardous substances CAS-No. | Result | Test type | Degradability | Exposure time | Method |
|---------------------------------|-----------------------|-----------|---------------|---------------|---|
| Dibenzoyl peroxide 94-36-0 | readily biodegradable | aerobic | 71 % | 28 d | OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test) |

12.3. Bioaccumulative potential

| Hazardous substances CAS-No. | Bioconcentration factor (BCF) | Exposure time | Temperature | Species | Method |
|---------------------------------|-------------------------------|---------------|-------------|---------|---|
| Dibenzoyl peroxide 94-36-0 | 66,6 | | | fish | OECD Guideline 305 (Bioconcentration: Flow-through Fish Test) |

12.4. Mobility in soil

| Hazardous substances CAS-No. | LogPow | Temperature | Method |
|---------------------------------|--------|-------------|---|
| Dibenzoyl peroxide 94-36-0 | 3,2 | 22 °C | OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method) |

12.5. Results of PBT and vPvB assessment

| Hazardous substances CAS-No. | PBT / vPvB |
|---------------------------------|---|
| Dibenzoyl peroxide 94-36-0 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code

080409

| |
|--|
| SECTION 14: Transport information |
|--|

14.1. UN number or ID number

| | |
|------|------|
| ADR | 3077 |
| RID | 3077 |
| ADN | 3077 |
| IMDG | 3077 |
| IATA | 3077 |

14.2. UN proper shipping name

| | |
|------|---|
| ADR | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Dibenzoyl peroxide) |
| RID | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Dibenzoyl peroxide) |
| ADN | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Dibenzoyl peroxide) |
| IMDG | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Dibenzoyl peroxide) |
| IATA | Environmentally hazardous substance, solid, n.o.s. (Dibenzoyl peroxide) |

14.3. Transport hazard class(es)

| | |
|------|---|
| ADR | 9 |
| RID | 9 |
| ADN | 9 |
| IMDG | 9 |
| IATA | 9 |

14.4. Packing group

| | |
|------|-----|
| ADR | III |
| RID | III |
| ADN | III |
| IMDG | III |
| IATA | III |

14.5. Environmental hazards

| | |
|------|------------------|
| ADR | not applicable |
| RID | not applicable |
| ADN | not applicable |
| IMDG | Marine pollutant |
| IATA | not applicable |

14.6. Special precautions for user

| | |
|------|-------------------------------|
| ADR | not applicable Tunnelcode: |
| RID | not applicable |
| ADN | not applicable |
| IMDG | not applicable |
| IATA | not applicable |

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), A197 (IATA), 2.10.2.7 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

No information available:

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

| | |
|---|----------------|
| Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009): | Not applicable |
| Prior Informed Consent (PIC) (Regulation (EU) No 649/2012): | Not applicable |
| Persistent organic pollutants (Regulation (EU) 2019/1021): | Not applicable |

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H241 Heating may cause a fire or explosion.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.

| | |
|-------------|---|
| ED: | Substance identified as having endocrine disrupting properties |
| EU OEL: | Substance with a Union workplace exposure limit |
| EU EXPLD 1: | Substance listed in Annex I, Reg (EC) No. 2019/1148 |
| EU EXPLD 2 | Substance listed in Annex II, Reg (EC) No. 2019/1148 |
| SVHC: | Substance of very high concern (REACH Candidate List) |
| PBT: | Substance fulfilling persistent, bioaccumulative and toxic criteria |
| PBT/vPvB: | Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria |
| vPvB: | Substance fulfilling very persistent and very bioaccumulative criteria |

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSInfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.