

MATERIAL SAFETY DATA SHEET

Product Name		Lithium Ion Battery		
1. Product Identification;				
Product Name		FP1880100A_10AH		
Company of Produ	cing	BYD		
2. Composition/Information	on on Ingredients			
Composition		Wt%		
Lithium cobalt - ferrum -	phosphorus oxide	28-32		
PVDF		1-3		
Carbon		13-15		
SBR		0.7-0.9		
Electrolyte(EC/EM	(C/DEC /1molLiPF6)	17-19		
PP+PE		3-4		
Copper		11-13		
Aluminum		19-21		
Nickel		0.8-1.0		
3. Hazard Identification				
Material	Emergency Overview	Toxicity		
	(Appearance)	(Potential Health Effects)		
Lithium cobalt – ferrum				
- phosphorus oxide	Black Powder (odorless)	Cobalt and Cobalt compounds are considered to be possible human carcinogen(s) .By IARC:		
		May irritate eyes, skin, nose ,throat, and		
		respiratory system May cause allergic skin		
		sensitization (rash).		
Carbon	Black Powder (odorless)	No cases of carbon being harmful to humans have		
Carbon	Diack Fowder (odoriess)	been reported. WHO and ILO have never		
		verified that carbon irritation of the skin and		
		mucous membrane, etc. In some individuals.		
SBR	Odorless White Powder	Inhalation and skin contact are expected to be the		
		primary routes of occupational exposure to this material .As a finished product ,it is a synthetic, high molecular weight polymer . due to its		
		chemical and physical properties, this material dos not require special handing other than the good industrial hygiene and safety practical		
		employed with any industrial material of this		



CAUTION!

MELT

PROCESSING

RELEASES

VAPORS

WHICH

MAY

CAUSE

EYE,

SKIN

AND

RESPIRATORY

TRACT

IRRITATION.

type. Under normal processing conditions, this material release fame or vapor components of these release may vary with processing time and temperatures . These process releases may produce eye, skin and/or respiratory tract irritation and, with repeated or prolonged exposures ...nausea , drowsiness , headache and weakness Although unlikely under normal handling conditions, if this material is heated in excess of 600F(315C) hazardous decomposition products will be produced. hazardous decomposition products include hydrogen fluoride and oxides of carbon, the concentrations of which vary with temperature and heating regimens

Electrolyte

Colorless Liquid

WARNING!

FLAMMABLE.

REACTS WITH WSTER

TO FORM

HYDROFLUORIC ACID.

MAY CAUSE BURNS TO

SKIN AND EYES

EFFECTS MAY BE

DELEYED. MAY CAUSE

BLINDNESS.

PROBABLE

REPRODUCTIVE

HAZARD.

May cause moderate to severe irritation, burring, and dryness of the skin. May cause eye irritation or burning. Breathing of the mists, vapors or fumes may irritate the nose, throat and lungs or fumes may irritate the nose throat and lungs Exposure of material with areas which contain water may generate hydrofluoric acid which can cause immediate burns on skin, severe eye burns burns to the mouth and gastrointestinal tract if ingested, and laryngeal edema if inhaled. Direct exposure to areas of the body need to be treated

immediately to prevent injury.

4. First Aid Measures

Eyes: Flush with water for at least 15 minutes. If irritation occurs and persists, contact a medical doctor.

Skin: Remove contaminated clothing and thoroughly wash with soap and plenty of water. If irritation persists, contact a medical doctor.

Inhalation: Remove to fresh air. If breathing difficulty or discomfort occurs and persists, see a medical doctor. If breathing has stopped, give artificial respiration and see a medical doctor IMMEDIATELY.

5. Fire Fighting Measures

Hazardous Combustion Products: When burned, hazardous products of combustion including fumes of carbon monoxide, carbon dioxide, and fluorine can occur



Extinguishing Media: Water, carbon dioxide, dry chemical, or foam.

Basic Fire Fighting Procedures: Wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

Unusual Fire & Explosion Hazards: This material does not represent an unusual fire or explosion hazard.

Autolgnition Temperature: No Data.

Flammability Limits in Air, Lower, % by Volume: 1.4 Flammability Limits in Air, Upper, % by Volume: 11

6. Accidental Release Measures

Procedure for Release and Spill:

Sweep up and place in a suitable container, Dispose or waste according to all local, state and Federal Laws and Regulations.

Before cleanup measures begin, review the entire MSDS with particular attention Potential Health Effects; and on Recommended Personal Protective Equipment.

7. Handling and storage

Handling: Avoid contact with eyes, skin or clothing, use with adequate ventilation. Wear safety glasses and rubber gloves. Wash thoroughly after handling.

Storage

Lithium cobalt – ferrum

- phosphorus oxide Keep away from strong acids. Keep container closed.

Carbon Store this material in a sealed enclosure to avoid dispersion of carbon fiber

dust. Keep container closed.

SBR Store in a cool, dry place. This material is not hazardous under normal storage

condition; however, material should be stored in closed container, in a

secure area to prevent container damage and subsequent spillage.

Electrolyte Store in tightly closed containers in a cool, dry, isolated, well-ventilated

area away from heat, sources of ignition and in compatibles. Store in original container. Keep from freezing. Avoid exposure to high

temperatures

8. Exposure Controls/Person Protection.

Engineering controls: Investigate engineering techniques to reduce exposures use with adequate

ventilation a Recommended personal protective Equipment

Eye/Face protection: Use good industrial practice to avoid eye contact. Processing of this product

releases vapors or fumes which may cause eye irritation. Where eye contact may be likely wear chemical goggles and have eye flushing equipment available

Skin protection: Minimize skin contamination by following good industrial hygiene practices Wearing

protective gloves is recommended Wash hands and contaminated skin thoroughly



after handling.

Respiratory protection: Avoid breathing dust and processing vapors When adequate ventilation is not available wear a NIOSH/MSHA respirator approved for protection against inorganic dusts.

Special clothing: Robber gloves.

Other: Quick-drench eye wash and safety shower.

Other: Quick-drench eye wash and safety shower.					
9. Physical and C	hemical Properties				
Material	Appearance	Odor	Molecular Weight	Vapor Pressure	
LiCo1-xFe _x I	PO ₄ Solid, Black Powder	Odorless	160.8-216.6	_	
Carbon	Black Powder	Odorless	12.01	_	
SBR	Latex	Odorless	-	-	
PVDF	Powder	Odorless	-	_	
Copper	Metal	Odorless	63.55	_	
Nickel	Metal	Odorless	58.69	-	
Aluminum	Metal	Odorless	26.98	-	
Electrolyte	Colorless Liquid, with a mild	-	-	_	
Material	Sublimating Point	Freezing Point/ Melting Point	Solubility in water	Density (Specific Gravity)	
LiCo1-xFe _x PO	_	>1000 deg.C	Insoluble	-	
Carbon	3000°C or more	_	Insoluble	2.2 g/ml	
SBR	_	_	Insoluble	-	
PVDF	_	165-172℃	Negligible	1.76-1.80 g/ml	
Copper	_	1083℃	Insoluble	8.96 g/ml	
Nickel	_	1555℃	Insoluble	8.91g/ml	
Aluminun	n _	660℃	Insoluble	2.7 g/ml	



Build Your Dreams

Electrolyte 126°C _	Partial	1.22 (20/20°C)	
(EC/EMC/DEC/1molLiPF6)		WATER=1	

10. Stability and Reactivity

Material	Stability	Incompatibility	Hazardous Polymerization	Hazardous Decomposition Products
				Troducts
LiCo1-xFe _x PO	4 Stable	alkalescent	Dose not polymerize	None
Carbon	Stable	Strong oxidants	_	_
SBR	Stable	Strong base, ester, Ketones, Sillca, Titanium .	Dose not occur	possible oxides of carbon
Electrolyte	Volatile	Strong reducers, bases, strong acids oxidizing agents, moist air or water.		Volatile pentafluoride compounds, Hydrogen fluoride, carbon monoxide Carbon dioxide and other decomposition product, etc.

11. Ecological Information

Eco Toxicological Information: No information available.

Chemical Fate Information: No data are available.

Environmental Effects: No data are available.

12. Disposal Information

Ensure disposal of material in compliance with all local. State and Federal-Laws and Regulations.

13. Transport Information

In the case of transportation, confirm no leakage and no overspill from a container. Take in a cargo of them without falling, dropping and breakage. Prevent collapse of cargo piles and wet by rain. The container must be handled carefully. Do not give shocks that result in a mark of hitting on a cell. Please refer to Section 7-HANDLING AND STORAGE also.

Codes and classifications according to:

International regulations for transport Air IATA-DGR: PI 965/966/967

International regulations for transport Sea IMDG CODE: special provision 188

National regulations for transport land GB12268-2005

The UN classification number: Class 9 3480

However, since it corresponds to special provision PI 965/966/967 of IATA-DGR, special provision 188 of IMDG CODE, GB12268-2005 of land regulation, this battery cell can be conveyed normally.

Lithium battery dose not contains any recalled/defective battery and meeting Packing Instruction 965/966/967 of IATA DGR



Production of MSDS proving UN manual of Tests and Criteria, part III, sub-section 38.3 is met on MSDS.

14. Regulatory Information

OSHA Hazard communication standard(29 CFR 1910.1200)

Hazardous ______Non-hazardous

15. Other Information

The information contained in this Safety date sheet is based on the present state of knowledge and current legislation.

This safety date sheet provides guidance on health. Safety and environmental aspecs of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

16. Reference

Chemical substances information: Japan Advanced Information center of Safety and Health International Chemical Safety Cards (ICSCs):

International Occupational Safety and Health Information Centre (CIS)

1999 TLVs and BEIs: American Conference of Governmental Industrial Hygienists (ACGIH)

Dangerous Goods Regulations: 50th Edition of IATA DGR Effective 1 January 2009: International Air Transport Association (IATA)

IMDG CODE Effective during 2001 to 2010: International Maritime Organization (IMO)

GB12268 Effective 1 November 2005: Standardization Administration of the People's Republic of China

MSDS of raw materials by prepared by the manufactures

;last data revised 2009-5-13

The material safety data sheet is furnished to every manufacturer as a reference to secure the safe handling of chemical. Every manufacturer is requested to carry out appropriate actions for chemical handling as their own responsibility. The supplier makes no warrantee, either express or implied. concerning of this products. User assumes all risks resulting from its use.

For more information contact:

Technology Manager

Cell Development Dept.6, PowerBattery Division, Group 2, Shenzhen,

BYD COMPANY LIMITED

NO1, Baoping Road, Baolong Industrial Town,

Longgang Shenzhen ,518116,

P.R. China

Tel:+86-755-8988 8888 Fax: +86-755-8483 5502 http://www.byd.com.cn