

Article Safety Data Sheet - Lithium Ion/Polymer Batteries

Edition date: 21. December 2022

Version: 01-03-2023

Valid: as from 01. March 2023

Renata SA
Kreuzenstrasse 30
CH-4452 ITINGEN / Switzerland
Tel: +41 61 975 75 75
Mail: sales@renata.com

Section I - Product identification

Product Name: **Lithium-ion Polymer Battery Pack** Nominal Voltage: 3.7 V
(Rechargeable Single Cell Battery)

Models: **ICP / AHB Series see Annex I (Pouch cell construction)**

Chemical System: Lithium - Graphit - Cobalt oxide

Section II - Hazardous ingredients

IMPORTANT NOTE: The battery should not be opened or exposed to heat because exposure of the following ingredients contained within could be harmful under some circumstances.

Chemical Name	CAS No.	Content % of total weight
LiCoO ₂	12190-79-3	29.36 - 35.88
Carbon black	1333-86-4	15.26 - 18.66
Aluminium	7429-90-5	13.14 - 16.06
Copper	7440-50-8	7.08 - 8.66
Ethylene carbonate	96-49-1	4.55 - 5.57
Nylon		3.47 - 4.24
Ethyl methyl carbonate	623-53-0	3.45 - 4.21
Diethyl carbonate	105-58-8	3.36 - 4.10
Polyethylene	9002-88-4	3.26 - 3.98
Polypropylene	9003-07-0	2.40 - 2.94
Poly(vinylidene difluoride)	24937-79-9	2.11 - 2.57
Lithium hexafluorophosphate	21324-40-3	1.64 - 2.00
Nickel	7440-02-0	0.54 - 0.66
Polyester		0.13 - 0.15
Polyimide		0.09 - 0.11
Activated Carbon	7440-44-0	0.08 - 0.10
Acrylic		0.05 - 0.07
Oxalic acid	00144-62-7	0.04 - 0.06

1) This Article Safety Data Sheet is provided as a service to our customers.

Based on the definition of the term 'article' in the Occupational Safety and Health Administration (OSHA) Hazard Communication Standard, 29 CFR Subpart 1910.1200, there is no requirement for a Material Safety Data Sheet (MSDS) for lithium Ion Polymer Batteries. Notification is not required because these products are 'articles' that do not release a covered toxic chemical under the normal conditions of processing or use.

Disclaimer:

The batteries are exempt articles and are not subject to hazard Communication Standard Requirement. This sheet is provided as technical information only. The information contained in this Product Safety Data Sheet has been established to the best of RENATA SA's knowledge and belief. RENATA SA makes no representation and provides no warranty or guarantee regarding the contents of this Product Safety Data Sheet and excludes its liability, express or implied.

Section III - Possible Hazards

Cells or Batteries may explode when placed in a fire, when exposed to excessive heat, when opened or during inappropriate use; which could release hydrogen fluoride gas and smoke.

Use only suitable extinguishing media.

The chemicals mentioned in Section II are contained in a sealed can.

Risk of exposure occurs only if the battery is mechanically or electrically abused (see Safety precautions in Section VII).

The most likely risk is acute exposure when a cell vents or opened, can cause irritation when inhaled.

Carcinogenicity - NTP: NO

Carcinogenicity - IARC: NO

Carcinogenicity - OSHA: NO

Contact with electrolyte with skin and eyes should be avoided.

3.2 Risk and Safety sentences:

(1) – Nature of special risks :

R14 Reacts with water

R21 Harmful in contact with skin

R22 Harmful if swallowed

R41 Risk of serious damage to the eye

R42/43 May cause sensitization by inhalation and skin contact

R43 May cause sensitization by skin contact

(2) – Safety advices :

S2 Keep out of reach from children

S8 Keep away from moisture

S22 Do not breathe dust

S24 Avoid contact with skin

S26 In case of contact with eyes, rinse immediately with plenty of water and get medical advice / attention

S36 Wear suitable protective clothing

S37 Wear suitable gloves

3.3 EU-GHS Classification:

Hazard statements:

H302 Harmful if swallowed

H312 Harmful in contact with skin

H315 Causes skin irritation

H318 Causes serious eye damage

H332 Harmful if inhaled

Precautionary statements:

P102 Keep out of reach of children

P223 Keep away from any possible contact with water, because of violent reaction and possible flash fire

P232 Protect from moisture

P260 Do not breathe dust/fume/gas/mist/vapors/spray
P262 Do not get in eyes, on skin, or on clothing
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P280 Wear protective gloves / protective clothing / eye protection / face protection

Section IV - First Aid Procedures

None unless internal material exposure.

Explanation Carcinogenicity: NOT RELEVANT

Skin contact with contents of an opened battery can cause irritation, wash immediately with soap and water. Remove contaminated clothing. If irritation persists, get medical help

Eye contact:

Contents of an opened battery can cause severe irritation, IMMEDIATELY FLUSH THOROUGHLY WITH COPIOUS AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION.

Ingestion:

CALL MEDICAL PRACTITIONER IMMEDIATELY

Inhalation:

Do not inhale leaked material. PROVIDE IMMEDIATELY FRESH AIR, IF IRRITATION PERSISTS, GET MEDICAL HELP.

Section V - Fire Fighting Instructions

5.1 Fire and explosion hazard:

The battery can leak and/or spout vaporized or decomposed and combustible electrolyte fumes in case of exposure above 70°C resulting from inappropriate use or the environment.

Cells or batteries may flame or leak potentially hazardous organic vapors if exposed to excessive heat or fire. Fire, excessive heat, or over voltage conditions may produce hazardous decomposition products.

Damaged or opened cells or batteries can result in rapid heating and the release of flammable vapors.

Vapors may be heavier than air and may travel along the ground or be moved by ventilation to an ignition source and flash back fire, excessive heat, or over voltage conditions may produce hazardous decomposition products.

During water application, caution is advised as burning pieces of flammable particles may be ejected from the fire.

5.2 Extinguishing Media:

Suitable CO₂

Dry chemical or Foam extinguishers.

Not to be used: Type D extinguishers.

Special Fire Fighting Procedure: WEAR NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT.

Unusual Fire and Explosion Hazards: NONE SPECIFIED BY MANUFACTURER.

As with any fire, wear self-contained breathing apparatus to avoid inhalation of hazardous decomposition products.

Section VI - Accidental Release

Steps to be taken in case material is released or spilled:

Wear appropriate personal protective equipment.

Isolate hazard area.

Keep unnecessary and unprotected personnel from entering.

Section VIII - Exposure Controls / Personal Protection

<u>Respiratory protection (specify type):</u>	Not necessary under conditions of normal use (see section VI)
<u>Ventilation:</u>	Not necessary under conditions of normal use (see section VI)
<u>Protective gloves:</u>	Not necessary under conditions of normal use (see section VI)
<u>Eye protection:</u>	Not necessary under conditions of normal use (see section VI)
<u>Other protective clothing or equipment:</u>	Not necessary under conditions of normal use (see section VI)

Section IX - Physical and Chemical Properties

The chemicals mentioned in Section II are contained in a sealed pouch. Under conditions of normal use, the chemicals will not be released.

Section X - Stability and Reactivity

Lithium-ion Polymer Battery Pack (*Rechargeable Single cell Battery*) are stable, no chemical release under conditions of normal use.

Conditions to avoid: See Sections VII & VIII

Section XI - Toxicological Information

In case electrolyte is spilled and exposed to air, HF could be released. May include hydrogen fluoride and carbon oxides gas. May cause skin and eye Irritation when contacted.

Section XII - Ecological Information

The chemicals mentioned in Section II are contained in a sealed pouch. Under conditions of normal use, the chemicals will not be released. It does not pose a physical or health risk to users, see section XIII for disposal.

Section XIII - Disposal Considerations

Waste disposal method:

- a) **Be sure to comply with your federal, state and local regulation disposal of used batteries.**

Dispose in accordance with appropriate national and international regulations, below some references.
 European Community: according to Directive 2002/96/EC on Waste Electrical and Electronic Equipment (WEEE), Annex II, batteries have to be removed from any separately collected WEEE. The removed batteries have to be treated according to the Battery directive 2006/66/EC

US: Lithium batteries are neither specifically listed nor exempted from the Federal Environmental Protection Agency (US EPA) hazardous waste regulations. The only material of possible concern due to its reactivity is lithium metal. However, button cells contain so little lithium that they can be disposed off in the normal municipal waste stream.

Use a professional disposal firm for disposal of mass quantities of undischarged lithium batteries.

b) Open cells should be treated as hazardous waste

DO NOT INCINERATE or subject battery cells to temperatures in excess of 212°F (100°C). Such treatment can cause cell rupture.

Section XIV - Transport Information

Lithium Ion Batteries are classified as Dangerous goods under Class 9 per the United Nations. Our cells and batteries are in compliance of the United Nation Transport Recommendations and meets all the requirements of UN Manual of Test and Criteria (IATA DGR 3.9.2.6).

For transporting our cell or batteries, depending of the shipping method used, the dangerous goods regulations and/or rules are fulfilled and must be followed in case of further transportation.

Our button cells or batteries are packed and shipped under compliance of IEC 60086-1. Our original packaging are adequate to avoid mechanical damages during the transport, handling and stacking. The materials used prevent the development of unintentional electrical conduction, corrosion of the terminals and ingress of moisture, shock and vibration are kept to a minimum. For the transport, handling and storage the boxes must be handled with care – cartons should not be thrown off trucks, slammed into position or piled so high as to overload battery containers below. Protection from inclement weather should be provided – See Section 7, Annex I.

Provisions for the international transportation (pursuant to ICAO-TI/IATA-DGR, IMDG Code, ADR, RID, DOT):

UN-No. UN 3480
Proper Shipping Name: Lithium Ion Batteries (including lithium polymer batteries)

Lithium Ion cells and batteries are subject to the following dangerous goods regulations/rules:

Shipping Method	Dangerous Goods Regulation	Packing Instruction and Special Provisions
Air Cargo aircraft only (Forbidden for transport aboard passenger aircraft)	ICAO TI 2023-2024 related to: IATA Dangerous Goods Regulations 2023 (64 th Edition)	Packing Instruction 965, Section IB Applies for shipments with 1 or more packages. Each carton do not have to exceed more than 10 kg total net weight. (No limitation in the number of packaging per shipment) Shipper's Declaration (DGD) is required. SIGNIFICANT CHANGES AND AMENDMENTS IN THE 64th EDITION (2023) PI 965—Has been revised to require that each package prepared in accordance with Section IB must be capable of withstanding the 3 m stack test as applies to limited quantity packages.
Road and Rail Europe	ADR / RID 2023	Special Provision 188
Marine	IMDG Code, 2023 Edition (Amdt. 41-22) comes into force on 01-Jan-2024 and may be applied voluntarily as from 01-Jan-2023	Special Provision 188
USA	DOT/ HMR; 49 C.F.R.	Parts 171-180

Summary of Transport Packing Instructions and Special Provisions of above mentioned Technical Guidelines:

1. For all lithium ion and lithium polymer cells, listed in Annex I, the Watt-hour rating is not more than 2.7Wh.

Excepting Articles: ICP543759 (Watt-hour rating is 4.9 Wh) and ICP606168 (Watt-hour rating is 10.4 Wh).

- For all the lithium ion cells or batteries, listed in Annex I, are fully and successfully tested to meet the requirements of each test in the UN Manual of Tests and Criteria, Part III, subsection 38.3 – (IATA DGR 3.9.2.6).
- Our cells are safe for transport when build-in equipment¹ (IATA - PI 967) or packed with equipment² (IATA - PI 966) shipped under UN 3481. Proper shipper name vary, see below:

UN No.	IATA DGR - Proper Shipper Name	IATA DGR - Packaging Instruction
¹ UN3481	Lithium ion batteries contained in equipment	967
² UN3481	Lithium ion batteries packed with equipment	966

Important: assembly of the cells and batteries is the responsibility of the customer and may makes new safety tests related to devices necessary.

For download the UN38.3 Test report, press the link of the requested model, mentioned in the [Annex I](#)

- Packing, marking, labelling and weight limitations must be observed as per technical guidelines of the respective transport mode.
- We hereby declare, that the state of charge (SoC) of the cells and batteries listed in Annex 1 does not exceed a Rate of 30%.

Note I: Example of Lithium ion polymer Battery Mark, see Annex II
 Example of Cargo Aircraft Only Label, see Annex III
 Example of Dangerous Goods Class 9 Label, see Annex IV

Section XV - Regulatory Information

See ACGIH exposure limits Information as noted in Section III.

US: This MSDS meets/exceeds OSHA requirements

International: this MSDS conforms to European Union (UN), the International Standards Organisation (ISO) and the International Labor Organization (ILO) and as documental in ANSI (American National Standards Institute) Standard Z400.1-1993.

Section XVI - Other Information

Compliance: In accordance with the RoHS Directive 2002/95/EC, and its amendment directives

Test Method: With reference to IEC 62321, Ed.1 111/54/CDV

Procedures for the Determination of Levels of Regulated Substances in Electrotechnical Products.

- Determination of Cadmium by ICP-AES.
- Determination of Lead by ICP-AES
- Determination of Mercury by ICP-AES
- Determination of Hexavalent Chromium for non-metallic samples by UVA/vis Spectrometry
- Determination of PBB and PBDE by GC'MS

Test Item (s):	Methode (Refer to)	Result	MDL
		No.1	
Cadmium- Cd	(1)	n.d	2
Lead (Pb)	(2)	n.d	2
Mercury (Hg)	(3)	n.d	2
Hexavalent Chromium CR(VI) by alkaline extraction	(4)	n.d	2

A COMPANY OF THE  **SWATCH GROUP**

Renata SA Tel. +41 (0)61 975 75 75 sales@renata.com
 CH-4452 Itingen/Switzerland Fax. +41 (0)61 975 75 95 www.renata.com

The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation. RENATA S.A. makes no warranty, expressed or implied, with respect to this information and disclaims all liabilities from reliance on it.

Sum of PBBs		n.d	
Monobromobiphenyl		n.d	5
Dibromobiphenyl		n.d	5
Tribromobiphenyl		n.d	5
Tetrabromobiphenyl		n.d	5
Pentabromobiphenyl		n.d	5
Hexabromobiphenyl		n.d	5
Heptabromobiphenyl		n.d	5
Octabromobiphenyl		n.d	5
Nonabromobiphenyl		n.d	5
Decabromobiphenyl		n.d	5
Sum of PBDEs (Mono to Nona) (Note 4)	(5)	n.d	-
Moniobromobiphenyl ether		n.d	5
Dibromobiphenyl ether		n.d	5
Tribromobiphenyl ether		n.d	5
Tetrabiphenyl ether		n.d	5
Pentabromobiphenyl ether		n.d	5
Hexabromobiphenyl ether		n.d	5
Heptabromobiphenyl ether		n.d	5
Octabiphenyl ether		n.d	5
Nonabiphenyl ether		n.d	5
Decabromobiphenyl ether		n.d	5
Sum of PBDEs (Mono to Deca)		n.d	-

References:

Chemical substances Information: Japan Advanced Information center of Safety and Health
 International Chemical Safety Cards (ICSCs): International Occupational Safety and Health Information Centre (CIS)
 2002 TLVs and BELs: American Conference of Governmental Industrial Hygienists (ACGIH)
 The United Nations Economic Commission for Europe (UNECE)
 MSDS of raw materials prepared by the manufactures

ANNEX I

MODELS OVERVIEW

Model no.	Approx.	Nominal Capacity [mAh]	Nominal Voltage	Wh	UN38.3 Test Summary <i>(link to our homepage)</i>
	Weight of battery [g]		[V]		
ICP241019	1.2	24	3.7	0.0888	Test Summary
ICP341018	1.5	35	3.7	0.1295	Test Summary
ICP331319	2	50	3.7	0.185	Test Summary
AHB701218	2.5	75	3.7	0.2775	Test Summary
ICP501022	2.6	80	3.7	0.296	Test Summary
ICP641414	2.7	95	3.7	0.3515	Test Summary
ICP631519	2.9	115	3.7	0.4255	Test Summary
ICP501421	3.1	115	3.7	0.4255	Test Summary
ICP651321	3.3	120	3.7	0.444	Test Summary
AHB331242	3.5	125	3.7	0.4625	Test Summary
ICP401230	3.5	130	3.7	0.481	Test Summary
ICP501230	3.3	135	3.7	0.4995	Test Summary
ICP581323	3.7	145	3.7	0.5365	Test Summary
ICP402025	4	155	3.7	0.5735	Test Summary
ICP641620	3.9	165	3.7	0.6105	Test Summary
ICP631524	3.9	170	3.7	0.629	Test Summary
ICP501233	4.2	175	3.7	0.6475	Test Summary
ICP402035	4.8	195	3.7	0.7215	Test Summary
ICP631530	5	235	3.7	0.8695	Test Summary
ICP621333	5.5	240	3.7	0.888	Test Summary
ICP521630	5.4	250	3.7	0.925	Test Summary
ICP422339	7.3	340	3.7	1.258	Test Summary
ICP602823	7.3	350	3.7	1.295	Test Summary
ICP402050	8.8	420	3.7	1.554	Test Summary
ICP582930	9.1	450	3.7	1.665	Test Summary
ICP303450	10.8	510	3.7	1.887	Test Summary
ICP622540	11	600	3.7	2.22	Test Summary
ICP543759	26	1320	3.7	4.884	Test Summary
ICP606168	70	2800	3.7	10.36	Test Summary
ICP281029H	2.4	68	3.85	0.2618	Test Summary
ICP390831	2.8	80	3.7	0.296	Test Summary
ICP401835	5.4	215	3.7	0.7955	Test Summary
ICP621333H	5.6	270	3.85	1.0395	Test Summary
ICP403029	7	325	3.7	1.2025	Test Summary
ICP582035	7.3	340	3.7	1.258	Test Summary
ICP632136H	9.6	520	3.85	2.002	Test Summary
ICP682828H	10.3	560	3.85	2.156	Test Summary
ICP521522PS	3.4	125	3.7	0.500	Test Summary

For download the UN38.3 Test summary, please press on the link of each model above.

A COMPANY OF THE  SWATCH GROUP

Renata SA
CH-4452 Itingen/Switzerland

Tel. +41 (0)61 975 75 75
Fax. +41 (0)61 975 75 95

sales@renata.com
www.renata.com

The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation. RENATA S.A. makes no warranty, expressed or implied, with respect to this information and disclaims all liabilities from reliance on it.

ANNEX II

Lithium Battery Mark

For further Information, consult the IATA DGR, 64th Edition, Figure 7.1.C Lithium Battery Mark 7.1.5.5



The Lithium Battery Mark (see above) may continue to be used until 31 December 2026 to provide a telephone number for additional information (no need to be 24h reachable). Beginning 1 January 2027 the telephone number has to be removed from the label.

In case that the cell or battery is packed with, or contained in, equipment the UN Nr. must be amended to UN 3481

ANEX III

For further Information consult the IATA DGR, 64th Edition (Section 7.4.2 Cargo Aircraft Only Figure 7.4.B)



ANNEX IV

Class 9 – Miscellaneous Dangerous Goods - Lithium Batteries

For further Information consult the IATA DGR, 64th Edition (Section 7.3.18.2 – Figure 7.3.X)

