



Material Safety Data Sheet

1. Product & Company Identification

Product:	Coin type Lithium Manganese Dioxide Rechargeable Battery, Model: LIR2032
Manufacturer:	Conrad Electronic SE
Nominal voltage:	3,7 V
Nominal capacity:	45 mAh
Address:	Klaus-Conrad-Str. 1, D-92240 Hirschau
Telephone:	+49 (0) 9604 / 40 - 8988
Date of issue:	29.09.2016

2. Composition/Information on the Ingredients

Ingredient	CAS#	Content (wt%)
Manganese Dioxide	1313-13-9	15 - 40
Propylene Carbonate	108-32-7	2 - 6
Lithium Perchlorate	7791-03-9	0 - 1,5
Lithium or Lithium Alloy *	7439-93-2	1 - 5
Graphite	7782-42-5	1 - 4

* Lithium Content for each battery 0,07 g (rated specification: 0,63 Wh)

3. Hazards Identification

This contains lithium, organic solvent, and other combustible materials. For this reason, improper handling of the battery could lead to distortion, leakage, overheating, explosion, or fire and cause human injury or equipment trouble. Please strictly observe safety instructions.

(Leakage is defined as an unintended escape of liquid from a battery)

4. First Aid Measures

None unless internal materials exposure. If contents are leaked out, observe following instructions:

Inhalation:

Fumes can cause respiratory irritation. Remove to fresh air and consult a physician.

Skin

Immediately flush skin with plenty of water. If itch or irritation by chemical burn persists, consult a physician.

Eyes

Immediately flush eye with plenty of water for at least 15 minutes. Consult a physician immediately.

Ingestion

If swallowing a battery. consult a physician immediately. If contents come into mouth. immediately rinse by plenty of water and consult a physician.



Material Safety Data Sheet

5. Fire Fighting Measures

Extinguishing Media

Extinguisher of alkaline metal fire is effective. Plenty of cold water is also effective to cool the surrounding area and control the spread fire. But hydrogen gas may be evolves by the reaction of water and lithium and it can form an explosive mixture. Therefore in the case that lots of lithium batteries are burning in a confined space, use a smothering agent.

Fire fighting procedure

Use self-contained breathing apparatus and full protective gear not to inhale harmful gas.

6. Accidental Release Measures

N/A

7. Handling and Storage

Handling

Never swallow. Never charge. Never heat. Never expose to open flame. Never disassemble. Never reverse the positive and negative terminals when mounting. Never short-circuit the battery. Never weld the terminal or wire to the body of the battery directly. Never use different batteries together. Never touch the liquid leaked out of battery. Never bring fire close to battery liquid, Never keep in touch with battery.

Storage

Never let the battery contact with water. Never store the battery in hot and high humid place.

8. Exposure Controls/Personal Protection

Respiratory Protection:	NA
Ventilation Local Exhaust:	NA
Mechanical:	NA
Special:	NA
Other:	NA
Eye Protection:	NA
Protective Gloves:	NA
Other protective clothing:	NA

9. Physical/Chemical Characteristics

N/A



Material Safety Data Sheet

10. Stability and Reactivity

Stability:	Stable
Incompatibility:	Water
Hazardous polymerization:	Will not occur.
Condition to avoid:	See section 7.
Hazardous Decomposition or Byproducts:	Hydrogen

11. Toxicological Information

N/A

12. Ecological Information

N/A

13. Disposal Condition

The battery may be regulated by national or local regulation. Please follow the instructions of proper regulation. As electric capacity is left in a discarded battery and it comes into contact with other metals, it could lead to distortion, leakage, overheating, or explosion, so make sure to cover the (+) and (-) terminals with friction tape or some other insulator before disposal.

14. Transport Information

Shipping Name (UN Number)

Lithium metal batteries (UN3090)

Lithium metal batteries packed with equipment (UN3091)

Lithium metal batteries contained in equipment (UN3091)

Organizations governing the transport of lithium batteries

Area	Method	Organization	Special Provision
International	Air	IATA, ICAO	Packing instruction 968-970
International	Marine	IMDG	SP188
USA	Air, Rail, Road, Marine	DOT	49 CFR Section 173.185

Their regulations are based on the UN Recommendations. Each special provision provides specifications on exceptions and packaging for lithium batteries shipping. The product can be transported as „Non Dangerous Goods“ when they meet the requirements of packing instruction 968 section II or 969 section II or part 970 section II of IATA-DGR (55th edition/2014) or SP188 of IMO-IMDG Code, Shipping.



Material Safety Data Sheet

15. Regulatory Information

N/A

16. Other Information

N/A