

**TBF (polyester empty enclosure)  
TBF 60/37/18 7035**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)



**Polyester housings** The housings of the TBF series are made of extremely tough glass fibre-reinforced polyester. These enclosures are ideal for applications that call for low weight coupled with high shock resistance. The weather-resistant TBF enclosures are designed for a wide range of applications. Together with their comprehensive range of accessories, they provide universal solutions for accommodating built-in items such as regulators, measuring instruments, valves and other equipment.

**Features:**

- 9 sizes in 2 versions
- cover with nylon screws
- fixing holes outside the sealed area
- Thread for fitting to terminal rails and mounting plates
- Comprehensive accessories Weidmüller can manufacture and supply this housing to match customer specifications, fitted with all necessary terminals and cable glands.

**General ordering data**

|            |                            |
|------------|----------------------------|
| Type       | TBF 60/37/18 7035          |
| Order No.  | <a href="#">9502820000</a> |
| GTIN (EAN) | 4032248025473              |
| Qty.       | 1 pc(s).                   |

**TBF (polyester empty enclosure)  
TBF 60/37/18 7035**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Technical data**
**Dimensions and weights**

|        |         |                 |             |
|--------|---------|-----------------|-------------|
| Width  | 372 mm  | Width (inches)  | 14.646 inch |
| Height | 603 mm  | Height (inches) | 23.74 inch  |
| Depth  | 175 mm  | Depth (inches)  | 6.89 inch   |
| Weight | 5,350 g | Net weight      | 5,000 g     |

**Environmental Product Compliance**

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

**Cable glands, right**

|     |    |     |    |
|-----|----|-----|----|
| M12 | 88 | M16 | 48 |
| M20 | 40 | M25 | 20 |
| M32 | 8  | M40 | 6  |
| M50 | 6  | M63 | 4  |

**Cable glands, top/bottom**

|     |    |     |    |
|-----|----|-----|----|
| M12 | 52 | M16 | 30 |
| M20 | 26 | M25 | 12 |
| M32 | 5  | M40 | 4  |
| M50 | 4  | M63 | 3  |

**General information**

|                             |                                                                                           |                             |                                                        |
|-----------------------------|-------------------------------------------------------------------------------------------|-----------------------------|--------------------------------------------------------|
| Areas of use                | Building systems and technology, Transportation, Packaging industry, Machine construction | Standards                   | IEC 61439-2, IEC 60529, EN 61439-2, EN 60529, EN 62208 |
| Toxicity                    | Free from halogens                                                                        | UL 94 flammability rating   | HB                                                     |
| Material                    | Glass fibre-reinforced polyester                                                          | Seal material               | Polyurethane                                           |
| Operating temperature, min. | -50 °C                                                                                    | Operating temperature, max. | 130 °C                                                 |
| Impact resistance           | IK08 in accordance with IEC 62208, IK10 in accordance with IEC 62262                      | Protection degree           | IP67                                                   |
| Enclosure attachment        | 6.5 mm hole in enclosure base                                                             | Lid attachment              | Crosshead nylon screws                                 |
| Integral fixing             | 4 or 6 stud bolts M6 inner (female) thread                                                |                             |                                                        |

**General information on accessories**

|          |                                  |
|----------|----------------------------------|
| Material | Glass fibre-reinforced polyester |
|----------|----------------------------------|

**horizontal assembly**

|                             |       |                 |      |
|-----------------------------|-------|-----------------|------|
| WDU 10 / ZDU 10             | 2x51  | WDU 16 / ZDU 16 | 2x37 |
| WDU 2,5 / ZDU 2,5 / IDU 2,5 | 2x101 | WDU 35 / ZDU 35 | 2x32 |
| WDU 4 / ZDU 4               | 2x85  | WDU 6 / ZDU 6   | 2x64 |

**TBF (polyester empty enclosure)  
TBF 60/37/18 7035**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Technical data**
**vertical assembly**

|                             |      |                 |      |
|-----------------------------|------|-----------------|------|
| WDU 10 / ZDU 10             | 5x29 | WDU 16 / ZDU 16 | 5x21 |
| WDU 2,5 / ZDU 2,5 / IDU 2,5 | 5x57 | WDU 35 / ZDU 35 | 5x18 |
| WDU 4 / ZDU 4               | 5x48 | WDU 6 / ZDU 6   | 5x36 |

**Classifications**

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 3.0   | EC000058    | ETIM 4.0   | EC000058    |
| ETIM 5.0   | EC000058    | ETIM 6.0   | EC000261    |
| UNSPSC     | 31-26-15-02 | eClass 5.1 | 27-14-91-07 |
| eClass 6.2 | 27-14-91-07 | eClass 7.1 | 27-14-91-07 |
| eClass 8.1 | 27-14-91-07 | eClass 9.0 | 27-18-01-01 |
| eClass 9.1 | 27-18-92-90 |            |             |

**Approvals**

Approvals



ROHS

Conform

**Downloads**

|                    |                                     |
|--------------------|-------------------------------------|
| Brochure/Catalogue | <a href="#">CAT 5 ENCL 17/18 EN</a> |
| Engineering Data   | <a href="#">EPLAN, WSCAD</a>        |
| Engineering Data   | <a href="#">STEP</a>                |

### TBF (polyester empty enclosure) TBF 60/37/18 7035

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

