

**OMNIMATE Housing - series CH20M  
CH20M BUS 4.50/05 AU/750**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**The integrated rail bus for the modular electronics housing system**

When supplying, connecting or distributing within modular applications, the rail bus can replace the tedious individual wiring process with a flexible and uninterrupted system-wide solution.

The system bus is securely integrated within the 35-mm standard mounting rail. The SMD-bus contact block can be reflow-soldered so that it can be completely automatically processed during the component assembly. The resistant, gold-plated contact surfaces ensure a permanent and reliable contact for all housing widths.

- **Unlimited scalability** The integrated connection solution covers all system widths: from the 6-mm slice to the 67-mm large-area housing.
- **Easy to service during installation** It's easy to replace a module, even in existing modules groups – without any influence on the neighbouring modules.
- **Universal integration** The uninterrupted system bus is securely integrated within the 35-mm standard mounting rail.
- **Maximum availability** Five fully-galvanized and partially gold-plated twin-arched contacts are used to establish a permanent contact to the rail bus. THR solder flanges ensure that the connection to the circuit board is stable.

**General ordering data**

Type	CH20M BUS 4.50/05 AU/750
Order No.	<a href="#">1248240000</a>
Version	Electronics housings, OMNIMATE Housing - series CH20M , Bus PCB, Width: 21.8 mm
GTIN (EAN)	4050118053210
Qty.	5 pc(s).

**Datenblatt**

**OMNIMATE Housing - series CH20M  
CH20M BUS 4.50/05 AU/750**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technische Daten**

**Dimensions and weights**

Length	750 mm	Width	21.8 mm
Height	1.7 mm	Net weight	75 g

**System characteristics**

Version	Bus PCB
---------	---------

**Material data**

UL 94 flammability rating	V-0	Contact material	Au (Gold)
Contact surface	Gold-plated		

**Classifications**

eClass 6.2	27-18-08-02	eClass 7.1	27-18-27-02
------------	-------------	------------	-------------