OMNIMATE Housing - series CH20M CH20M17 B BUS BK/OR



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com





Superior efficiency, flexibility and design - the "standard tailor-made fit"

When selecting a housing design, flexibility is a key factor. Other important criteria are: scalability, customised design, innovative functionality and cost efficiency. You need a choice which offers the maximum performance with the minimum overhead.

The CH20M17 modular electronics housing is the ideal housing solution for compact standard electronics applications.

The entire system is characterized by excellence: outstanding scalability and flexibility, a high security level, innovative application functionality and a variety of practical details.

- Quicker installation with features such as "Wire ready" the universal multi-tool screw head
- **User-friendly operations:** with clear and permanent labelling and extra marking possibilities, integrated release clip or transparent cover
- Maximum interference immunity with EMCcompliant construction featuring deeply overlapping module joint edges made from high-performance plastic
- **High operational reliability** with the unique Auto-Set coding system and featuring double-sided touch protection on the pin header and socket blocks

CH2OM - a compact name for the most flexible system available on the market. It doesn't just stand for "Component Housing IP2O Modular". CH2OM also stands for efficiency and innovation throughout design, production and use.

General ordering data

Туре	CH20M17 B BUS BK/OR		
Order No.	<u>1254180000</u>		
Version	Electronics housings, OMNIMATE Housing - series CH20M Black, Base element, Width: 17.5 mm		
GTIN (EAN)	4050118047042		
Qty.	12 pc(s).		

OMNIMATE Housing - series CH20M CH20M17 B BUS BK/OR

Technische Daten

Dimensions and weights



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

 			
Length	107.4 mm	Width	17.5 mm
Height	109.3 mm	Net weight	29.858 g
System characteristics			
Version	Base element	Type of connection	Bus connection
Number of PCBs per module	1	PCB thickness	1.6 mm
Tolerance for the PCB shape	±0.15 mm	Contact to terminal rail	No
Encapsulation option	No		
Material data			
UL 94 flammability rating	V-0	Insulating material	PA 66 GF 30
Colour	Black		
Classifications			
	07 40 00 00		07.40.07.00
eClass 6.2	27-18-08-02	eClass 7.1	27-18-27-02
Approvals			
ROHS	Conform		