# OMNIMATE Signal - series BL/SL 5.00
# SL 5.00/06/180 3.2SN OR BX

**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com






Male connectors with straight outlet direction. The solder pin length is optimised for wave flow soldering. The pin headers provide space for labelling and can be coded.
- 400 V (IEC) / 300 V (UL)
- 18 A (IEC) / 15 A (UL)

## General ordering data

| | |
|---|---|
| Type | SL 5.00/06/180 3.2SN OR BX |
| Order No. | 1581360000 |
| Version | PCB plug-in connector, male header, open side, Solder connection, 5.00 mm, No. of poles: 6, 180°, Solder pin length (l): 3.2 mm, tinned, Orange, Box |
| GTIN (EAN) | 4008190035303 |
| Qty. | 50 pc(s). |
| Product data | IEC: 400 V / 18 A<br>UL: 300 V / 15 A |
| Packaging | Box |

# OMNIMATE Signal - series BL/SL 5.00
# SL 5.00/06/180 3.2SN OR BX

**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

## Technische Daten

### Dimensions and weights

| | |
|---|---|
| Net weight | 1.77 g |

### System parameters

| | | | |
|---|---|---|---|
| Product family | OMNIMATE Signal - series BL/SL 5.00 | Mounting onto the PCB | Solder connection |
| Outgoing elbow | 180° | Pitch in mm (P) | 5 mm |
| Pitch in inches (P) | 0.197 inch | No. of poles | 6 |
| Solder pin length (l) | 3.2 mm | Pin dimensions | d = 1.2 mm, Octagonal |
| Can be coded | Yes | Number of solder pins per pole | 1 |
| Solder eyelet hole diameter (D) | 1.3 mm | Solder eyelet hole diameter tolerance (D) | + 0,1 mm |
| L1 in mm | 25 mm | L1 in inches | 0.984 inch |
| Touch-safe protection acc. to DIN VDE 0470 | IP20 plugged | Touch-safe protection acc. to DIN VDE 57 106 | Safe from finger touch, plugged |

### Material data

| | | | |
|---|---|---|---|
| Insulating material | PBT | Colour | Orange |
| Insulating material group | IIIa | UL 94 flammability rating | V-0 |
| CTI | ≥ 200 | Contact material | CuSn |
| Contact surface | tinned | Max. relative humidity during storage | 80 % |

### DIN IEC rating data

| | | | |
|---|---|---|---|
| Rated current, min. no. of poles (TU=20°C) | 18 A | Rated current, max. no. of poles (Tu=20°C) | 14.5 A |
| Rated current, number of poles (Tu=40°C), min | 15 A | Rated current, number of poles (Tu=40°C), max. | 12 A |
| Rated voltage for surge voltage class pollution degree III/3 | 250 V | Rated impulse voltage for surge voltage classcontamination degree III/3 | 4 kV |
| Rated voltage for surge voltage class pollution degree III/2 | 320 V | Rated impulse voltage for surge voltage classpollution degree III/2 | 4 kV |
| Rated voltage for surge voltage class pollution degree II/2 | 400 V | Rated impulse voltage for surge voltage classpollution degree II/2 | 4 kV |
| Short-time withstand current resistance | 3 x 1s with 120 A | | |

### CSA rating data

| | | | |
|---|---|---|---|
| Institute (CSA) | | Rated voltage (Use group B) | 300 V |
| Rated current (use group B) | 15 A | Rated voltage (use group D) | 300 V |
| Rated current (use group D) | 10 A | | |

### UL 1059 rating data

| | | | |
|---|---|---|---|
| Institute (UR) | | Rated voltage (use group B) | 300 V |
| Rated current (use group B) | 15 A | Rated voltage (use group D) | 300 V |
| Rated current (use group D) | 10 A | | |

# OMNIMATE Signal - series BL/SL 5.00
# SL 5.00/06/180 3.2SN OR BX

**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

## Technische Daten

### Classifications

| | | | |
|---|---|---|---|
| ETIM 3.0 | EC001284 | UNSPSC | 30-21-18-10 |
| eClass 5.1 | 27-26-07-04 | eClass 6.2 | 27-26-07-04 |
| eClass 7.1 | 27-44-04-02 | | |

### Notes

| | |
|---|---|
| Notes | • Additional colours on request<br>• Gold-plated contact surfaces on request<br>• Rated current related to rated cross-section & min. No. of poles.<br>• P on drawing = pitch<br>• Rated data refer only to the component itself. Clearance and creepage distances to other components are to be designed in accordance with the relevant application standards. |

### Approvals

| | |
|---|---|
| Approvals | |
| ROHS | Conform |

### Downloads

| | |
|---|---|
| CAD Library (P-CAD Format - ASCII) | SL.zip |
| CAD Library (P-CAD Format - Standard) | SL.zip |
| 3D Modell | |

# OMNIMATE Signal - series BL/SL 5.00
# SL 5.00/06/180 3.2SN OR BX

**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

## Zeichnungen

