

## OMNIMATE Signal - series RSV SL FLA 2,3/24

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)



### Effective: the link between LED and front panel.

Floodlight indicators allow users to monitor the switching states without requiring a special design: optical plastic directs the light from standard LEDs around a bend into the connectors or through the front plate.

The fibre-optic elements are simply clipped behind the relevant 90° bend male connectors (90° outlet direction). Versions with different incoming light beam heights achieve maximum light efficiency for LEDs with different designs or heights.

The advantages compared to conventional solutions:

- No additional LED circuit board required behind the front panel
- No "long-legged" LEDs with separate mounting required
- Bent fibre-optic cable line for maximum light efficiency
- Uncomplicated front plate bore holes due to circular shape of outgoing light beam
- Easy to maintain correct clearance and creepage distance
- Can be partitioned for smaller pole numbers

The result: simplified manufacturing process, reduced costs and simplified design

### General ordering data

|              |                                                                          |
|--------------|--------------------------------------------------------------------------|
| Type         | SL FLA 2,3/24                                                            |
| Order No.    | <a href="#">1636680000</a>                                               |
| Version      | PCB plug-in connector, Accessories, Flood-light display, No. of poles: 1 |
| GTIN (EAN)   | 4008190409968                                                            |
| Qty.         | 10 pc(s).                                                                |
| Product data |                                                                          |

## OMNIMATE Signal - series RSV SL FLA 2,3/24

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

## Technische Daten

### Dimensions and weights

|            |        |
|------------|--------|
| Net weight | 12.1 g |
|------------|--------|

### Classifications

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 3.0   | EC001284    | UNSPSC     | 30-21-18-01 |
| eClass 6.2 | 27-26-92-01 | eClass 7.1 | 27-44-92-02 |

### Notes

Notes

### Approvals

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|