# Conductor markers
# TM-I 20 MC NE WS

**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



TM-I is an acknowledged and accredited marker type for traffic engineering applications. There are five different tag lengths available for individual labelling with long character strings. Easy handling of separation and installation thanks to the project marker field. Pre-attachment of sleeves and retrofitting of tags offer excellent versatility
The special contour of TM-I allows easy assembly and secures firm positioning. They are compatible with a number of commercially available sleeves. Thanks to the MultiCard format, the tags can be printed quickly and conveniently with the SMark laser printer, PrintJet ADVANCED, plotter, MC-Mobilo or the STI pen.

- Easy handling of separation and installation thanks to the project marker field.
- Acknowledged and accredited marker for traffic engineering applications
- Pre-attachment of sleeves and retrofitting of tags offer excellent versatility
- Not suited for labelling with P-Ink or STI pen in connection with CLI T sleeves

## General ordering data

| | |
|---|---|
| Type | TM-I 20 MC NE WS |
| Order No. | 1680411044 |
| Version | Conductor markers, MultiCard, 20 x 4 mm, Polyamide 66, Colour: White |
| GTIN (EAN) | 4008190914769 |
| Qty. | 400 pc(s). |

# Conductor markers
# TM-I 20 MC NE WS

**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

## Technische Daten

### Dimensions and weights

| | | | |
|---|---|---|---|
| Length | 20 mm | Width | 4 mm |
| Height | 2 mm | Depth | 2 mm |
| Net weight | 0.298 g | | |

### General data

| | | | |
|---|---|---|---|
| Colour | White | Material | Polyamide 66 |
| Material colour according to resistance code | 9 | Operating temperature range, max. | 100 °C |
| Operating temperature range, min. | -40 °C | Recommended industries | Transportation, Machinery |
| Type of printing | blank | UL 94 flammability rating | V-2 |

### Conductor and cable markers

| | | | |
|---|---|---|---|
| Conductor O.D., max. | 40 mm | Conductor O.D., min. | 1 mm |
| Conductor cross-section, max. | 500 mm² | Conductor cross-section, min. | 0.22 mm² |
| Halogen | No | | |

### Classifications

| | | | |
|---|---|---|---|
| ETIM 3.0 | EC001530 | UNSPSC | 44-12-17-08 |
| eClass 5.1 | 27-14-91-03 | eClass 6.2 | 27-14-91-03 |
| eClass 7.1 | 27-14-91-03 | | |

### Approvals

| | |
|---|---|
| Approvals | |
| ROHS | Conform |

### Downloads

| | |
|---|---|
| M-Print® PRO configuration file | mc_tm-i_20_mcf.zip |