

**Accessories**  
**SCT 4 ,6/127 C**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



Weidmüller Steel Series contains a comprehensive assortment of steel cable ties for extreme conditions such as high temperatures or severe chemical effects.

- stainless steel AISI 304,
- patented closure enables easy, secure installation,
- patented rounded edges reduce the risk of injury,
- ideal for use outdoors,
- radiation- and corrosion-resistant,
- anti-magnetic,
- no serrations, so no damage to the insulation.

**General ordering data**

Type	SCT 4 ,6/127 C
Order No.	<a href="#">1699800000</a>
Version	Accessories, Cable ties, x 4.6445 N
GTIN (EAN)	4008190892241
Qty.	100 pc(s).

## Data sheet

### Accessories SCT 4,6/127 C

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

Width	4.6 mm	Width (inches)	0.181 inch
Height	127 mm	Height (inches)	5 inch
Depth	0.25 mm	Depth (inches)	0.01 inch
Net weight	1.6 g		

### Installation materials

Cable diameter, max.	25 mm	Material	Stainless steel 1.4301
Operating temperature range, max.	538 °C	Operating temperature range, min.	-80 °C
Tensile strength	445 N		

### Classifications

ETIM 3.0	EC000046	ETIM 4.0	EC000761
ETIM 5.0	EC000761	ETIM 6.0	EC000046
UNSPSC	30-21-18-01	eClass 5.1	27-14-07-02
eClass 6.2	27-14-07-02	eClass 7.1	27-14-11-37
eClass 8.1	27-14-11-37	eClass 9.0	27-14-07-02
eClass 9.1	27-14-07-02		

### Approvals

ROHS	Conform
------	---------

### Downloads

Engineering Data	<a href="#">EPLAN, WSCAD</a>
------------------	------------------------------

**Data sheet**

**Accessories**  
**SCT 4,6/127 C**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

**Drawing**

