

**Terminal markers  
DEK 5/3,5 MC FSZ 51-60**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Connector markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

**General ordering data**

|            |                                                                      |
|------------|----------------------------------------------------------------------|
| Type       | DEK 5/3,5 MC FSZ 51-60                                               |
| Order No.  | <a href="#">1762320051</a>                                           |
| Version    | Terminal markers, MultiCard, 5 x 3.5 mm, Polyamide 66, Colour: White |
| GTIN (EAN) | 4032248043606                                                        |
| Qty.       | 500 pc(s).                                                           |

**Terminal markers  
DEK 5/3,5 MC FSZ 51-60**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Technische Daten****Dimensions and weights**

|            |         |       |        |
|------------|---------|-------|--------|
| Length     | 5 mm    | Width | 3.5 mm |
| Net weight | 0.174 g |       |        |

**General data**

|                                   |              |                                              |         |
|-----------------------------------|--------------|----------------------------------------------|---------|
| Colour                            | White        | Colour of printing                           | Black   |
| Material                          | Polyamide 66 | Material colour according to resistance code | 9       |
| Operating temperature range, max. | 100 °C       | Operating temperature range, min.            | -40 °C  |
| Orientation of print              | vertical     | Printed characters                           | Numbers |
| Printing method                   | MC Laser     | UL 94 flammability rating                    | V-2     |

**Connector markers**

|                 |        |
|-----------------|--------|
| Pitch in mm (P) | 3.5 mm |
|-----------------|--------|

**Classifications**

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 3.0   | EC000761    | eClass 6.2 | 27-14-11-37 |
| eClass 7.1 | 27-14-11-37 |            |             |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Terminal markers DEK 5/3,5 MC FSZ 51-60

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

## Zeichnungen

### Example of use



### Drawing

