

Electronic housing - MKDSO 2,5/ 4-L YE - 1730359

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

PCB terminal block

Key commercial data

package_quantity	50
GTIN	4046356152716

classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27141190
eCl@ss 6.0	27141190
eCl@ss 7.0	27141190
eCl@ss 8.0	27141190

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002643
ETIM 5.0	EC002643

UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

approvals

CSA / UL Recognized / VDE Gutachten mit Fertigungsüberwachung / cUL Recognized / GOST / CCA / IECB Scheme / GOST / cULus Recognized /

Approval details

Electronic housing - MKDSO 2,5/ 4-L YE - 1730359

approvals

Usegroups	B	D
Nominal voltage UN	300 V	300 V
Nominal current IN	10 A	10 A
mm ² /AWG/kcmil	28-12	28-12

Usegroups	B	D
Nominal voltage UN	300 V	300 V
Nominal current IN	20 A	10 A
mm ² /AWG/kcmil	30-12	30-12

Nominal voltage UN	450 V
Nominal current IN	24 A
mm ² /AWG/kcmil	0.2-2.5


Usegroups	B	D
Nominal voltage UN	300 V	300 V
Nominal current IN	20 A	10 A
mm ² /AWG/kcmil	30-12	30-12



--	--

Nominal voltage UN	450 V
Nominal current IN	24 A
mm ² /AWG/kcmil	2.5

Electronic housing - MKDSO 2,5/ 4-L YE - 1730359

approvals

IECEE CB Scheme 	
Nominal voltage UN	450 V
Nominal current IN	24 A
mm ² /AWG/kcmil	2.5



© Phoenix Contact 2013 - all rights reserved
<http://www.phoenixcontact.com>