

Electronic housing - ME 45 OT-1MSTBO KMGY - 2709299

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)



Upper part of housing, for COMBICON connection, single-level

Product Features

- ▼ Tool-free mounting
- ME...TBUS connector with 5 parallel contacts can be snapped onto DIN rails to save space
- Gold contacts for data transmission and power supply (125 V, 8 A)

- Recessed labeling areas
- Fast mounting on DIN rails according to EN 60715
- ✓ Inflammability class V0 according to UL 94
- Material and part identification embossed on the housing (recyclability)
- Cost savings thanks to easy device production
- Metal foot catch
- Functional earth ground contact (EMC) integrated in the housing base
- Optional BUS connection integrated in the housing, for either parallel or serial contacting

Key commercial data

package_quantity	10
GTIN	4017918885618

Technical data

General

Housing type	Upper part
Housing material	PA 6.6
Color	light gray

Dimensions

Length	99 mm
Constructional height	38.5 mm
Width	45 mm



Electronic housing - ME 45 OT-1MSTBO KMGY - 2709299

Technical data

Technical data

Inflammability class according to UL 94	V0
Number of positions	8

classifications

eCl@ss

eCl@ss 4.0	27180401
eCl@ss 4.1	27180401
eCl@ss 5.0	27180506
eCl@ss 5.1	27180506
eCl@ss 6.0	27180802
eCl@ss 7.0	27182702
eCI@ss 8.0	27182702

ETIM

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC001031
ETIM 5.0	EC000886

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

approvals

UL Recognized /

Approval details





Drawings



Electronic housing - ME 45 OT-1MSTBO KMGY - 2709299

Dimensioned drawing





© Phoenix Contact 2013 - all rights reserved http://www.phoenixcontact.com