

Components of electronic housing - UM-PRO PCB C-LOCK L1 BK - 2200164

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Locking element for locking the PCB onto UM-PRO housing at level 1

The figure shows the versions for PCB level 1

Product Features

- Plug-in assembly reduces assembly time and therefore saves costs
- Mounting close to the edge provides wiring advantages
- Freely positionable covers offer flexibility
- PE contacts that can be fitted on both sides ensure safety
- Additional foot elements increase mechanical stability
- Temperature range up to 100°C extends the possible fields of application (UM-PRO)
- Device communication can be extended by BUS cross contacting
- Additional labeling of PCB with Phoenix Contact PMB module marker carrier (drill hole diameter 4 mm)
- Well-designed profile geometry increases the form stability

Key commercial data

package_quantity	50
GTIN	4046356547581

Technical data

General

Housing material	Polyamide
Color	black

Technical data

Inflammability class according to UL 94	V0
--	----

classifications

eCl@ss

eCl@ss 4.0	27180401
eCl@ss 4.1	27180401
eCl@ss 5.0	27180506
eCl@ss 5.1	27180506

Components of electronic housing - UM-PRO PCB C-LOCK L1 BK - 2200164

classifications

eCl@ss

eCl@ss 6.0	27180802
eCl@ss 7.0	27182701
eCl@ss 8.0	27182701

ETIM

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC002608
ETIM 5.0	EC002608


UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

approvals

UL Recognized /

Approval details



Drawings

© Phoenix Contact 2013 - all rights reserved
<http://www.phoenixcontact.com>