

64446 - UHU hart 35g FS DE/FR/IT

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.02.2021

Version number 5

Revision: 10.02.2021

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· Trade name: UHU hart 35g FS DE/FR/IT

- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Adhesive
- 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: UHU GmbH & Co.KG Herrmannstraße 7 D-77815 Bühl (Baden) Tel.:0049-(0)7223-284-0 emaill: sds@boltonadhesives.com

Fax: 0049-(0)7223-284-245

- Further information obtainable from: UHU QESH 1.4 Emergency telephone number:
- Tel.: + 49 (0) 30/19240 (Notruf) Tel.: + 49 (0) 72 23/28 40

England and Wales (NHS Direct) 111 Schottland (NHS 24) 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms



· Signal word Danger

• Hazard-determining components of labelling: methyl acetate

(Contd. on page 2)

EU-EN



Printing date 10.02.2021

Version number 5

Revision: 10.02.2021

Trade name: UHU hart 35g FS DE/FR/IT

	(Contd. of page 1)
n-butyl acetate	
 Hazard statemen 	nts
H225 Highly flam	mable liquid and vapour.
H319 Causes ser	ious eye irritation.
H336 May cause	drowsiness or dizziness.
 Precautionary st 	atements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources. No smoking.
P261	Avoid breathing vapours.
P305+P351+P33	8 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing.
P501	Dispose of contents/container in accordance with national regulations.
 Additional inform 	nation:
EUH066 Repeate	d exposure may cause skin dryness or cracking.
2.3 Other hazard	S
Results of PBT a	ind vPvB assessment

- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

Г

· Description: Adhesive

· Dangerous components:

Dangerous components.		
CAS: 79-20-9 EINECS: 201-185-2 Index number: 607-021-00-X Reg.nr.: 01-2119459211-47- XXXX	methyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	50-100%
CAS: 9004-70-0 EC number: 682-719-5	nitrocellulose solutions, with not more than 12.6% nitrogen, by dry mass, and not more than 55% nitrocellulose Flam. Sol. 1, H228	
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate	2.5-10%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information: No special measures required.

· After inhalation:

- Supply fresh air; consult doctor in case of complaints.
- No special measures required.

(Contd. on page 3) EU-EN



64446 - UHU hart 35g FS DE/FR/IT

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.02.2021

Version number 5

Revision: 10.02.2021

(Contd. of page 2)

Trade name: UHU hart 35g FS DE/FR/IT

· After skin contact: Generally the product does not irritate the skin.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- \cdot 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

- **Information about fire and explosion protection:** Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep container tightly sealed.

(Contd. on page 4)

EU-EN



Printing date 10.02.2021

Version number 5

Revision: 10.02.2021

(Contd. of page 3)

Trade name: UHU hart 35g FS DE/FR/IT

Store in cool, dry conditions in well sealed receptacles.

• Storage class: 3

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

 \cdot Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

IOELV Short-term value: 723 mg/m³, 150 ppm Long-term value: 241 mg/m³, 50 ppm

79-20-9 m	ethyl acetate	
Oral	Consumer, oral, longterm exposition	44 mg/kg bw/day
Dermal	Consumer, dermal, longterm exposition	44 mg/kg bw/day
Inhalative	Consumer DNEL, acute inhalation	mg/m³ (rat)
		mg/m³ (rabbit)
	Consumer, inhalation, longterm exposition	131 mg/m³
123-86-4 ı	n-butyl acetate	
Oral	Consumer, oral, longterm exposition	3.4 mg/kg bw/day

DermalConsumer, dermal, longterm exposition3.4 mg/kg bw/dayInhalativeConsumer, inhalation, longterm exposition102.34 mg/m³

• PNECs 79-20-9 methyl acetate

Fresh water 0.12 mg/l

Marine water 0.012 mg/l

Soil 0.0416 mg/kg

123-86-4 n-butyl acetate Fresh water 0.18 mg/l

Marine water 0.018 mg/l

Soil 0.0903 mg/kg

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

(Contd. on page 5)

www.uhu.com



Printing date 10.02.2021

Version number 5

Revision: 10.02.2021

(Contd. of page 4)

Trade name: UHU hart 35g FS DE/FR/IT

· Respiratory protection: Not required.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves

Recommended thickness of the material: > 0,12 mm

glove material: butyl rubber

thickness of the glove material: 0,6 - 0,8 mm

breakthrough time (maximum wearing time): 60 - 120 min.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

Eye protection:



Tightly sealed goggles

Goggles recommended during refilling

9.1 Information on basic physical	and chemical properties		
· General Information			
Appearance:			
Form:	Fluid		
Colour:	Colourless		
Odour:	Ester-like		
Odour threshold:	Not determined.		
pH-value:	Not determined.		
Change in condition			
Melting point/freezing point:	Undetermined.		
Initial boiling point and boiling r	ange: 57 °C		
Flash point:	-10 °C		
Flammability (solid, gas):	Not applicable.		
Ignition temperature:	180 °C		
Decomposition temperature:	Not determined.		
Auto-ignition temperature:	Product is not selfigniting.		



Printing date 10.02.2021

Version number 5

Revision: 10.02.2021

Trade name: UHU hart 35g FS DE/FR/IT

	(Contd. of page s
· Explosive properties:	Product is not explosive. However, formation o explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	3.1 Vol %
Upper:	16 Vol %
· Vapour pressure at 20 °C:	220 hPa
· Density at 20 °C:	1.115 g/cm³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic at 20 °C:	9000 mPas
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	68.7 %
Solids content:	31.3 %
• 9.2 Other information	All relevant physical data were determined for the mixture. All non-determined data are not measurable o not relevant for the characterization of the mixture.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

79-20-9 methyl acetate

Oral LD50 3705 mg/kg (rabbit)

(Contd. on page 7) EU-EN



Printing date 10.02.2021

Version number 5

Revision: 10.02.2021

Trade name: UHU hart 35g FS DE/FR/IT

123-86-4	n-butyl ac	(Contd. c	of page
Oral	LD50	13100 mg/kg (rat)	
Dermal	LD50	>5000 mg/kg (rabbit)	
		>21 mg/l (rat)	
• Primary in		act: ation Based on available data, the classification criteria are not met.	
		elion based on available data, the classification chiena are not met.	
	erious eye		
		sensitisation Based on available data, the classification criteria are no	ot met.
		e toxicity, irritation and corrosivity) Not applicable.	
· Sensitisa			
		icity Not applicable.	
		nogenity, mutagenicity and toxicity for reproduction)	
		icity Not applicable. sed on available data, the classification criteria are not met.	
		ity Based on available data, the classification criteria are not met.	
STOT-sin			
May cause	e drowsine	ess or dizziness.	
		posure Based on available data, the classification criteria are not met.	
· Aspiratio	n hazard I	Based on available data, the classification criteria are not met.	
SECTIO	N 12: Ec	cological information	
· 12.1 Toxi	city		
		o further relevant information available.	
		nd degradability No further relevant information available.	
		ive potential No further relevant information available.	
		I No further relevant information available.	
		cal information:	
· General r			
		2 (German Regulation) (Self-assessment): hazardous for water	
Do not allo Danger to	drinking w	t to reach ground water, water course or sewage system. vater if even small quantities leak into the ground.	
		T and vPvB assessment	
• PBT: Not			
· vPvB: No			
		effects No further relevant information available.	
SECTIO	N 42. D:	anagal considerations	
SECHO	IN IS. DI	sposal considerations	
· 13.1 Wast	te treatme	ent methods	
· Recomme			
	be dispos	ed together with household garbage. Do not allow product to reach s	sewag
system.			
Disposal r	nust be ma	ade according to official regulations.	n noac
		(Contd. o	ni paye

(Contd. on page 8)



Printing date 10.02.2021

Version number 5

Revision: 10.02.2021

Trade name: UHU hart 35g FS DE/FR/IT

(Contd. of page 7)

• Uncleaned packaging:
 • Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR/ADN, IMDG, IATA	UN1133
14.2 UN proper shipping name ADR/ADN IMDG, IATA	1133 ADHESIVES, special provision 640D ADHESIVES
14.3 Transport hazard class(es) ADR/ADN	
· Class · Label	3 (F1) Flammable liquids. 3
IMDG, IATA	5
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR/ADN, IMDG, IATA	Ш
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids. 33 F-E,S-D E
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
Transport/Additional information: Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
ADR/ADN Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 50 ml



Printing date 10.02.2021

Version number 5

Revision: 10.02.2021

Trade name: UHU hart 35g FS DE/FR/IT

	(Contd. of page 8
 Transport category Tunnel restriction code 	2 D/E
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1133 ADHESIVES, SPECIAL PROVISION 640D, 3, II

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements $50000\ t$
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

- H226 Flammable liquid and vapour.
- H228 Flammable solid.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Classification according to Regulation (EC) No 1272/2008

Flammable liquids	Bridging principles
	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
 Department issuing SDS: UHU QESH Contact: UHU QESH 	

(Contd. on page 10)



Printing date 10.02.2021

Version number 5

Revision: 10.02.2021

Trade name: UHU hart 35g FS DE/FR/IT

(Contd. d	of page 9)
Abbreviations and acronyms:	
 ADDreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concelenternational Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent 	erning the
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Liq. 2: Flammable liquids – Category 2	
Flam. Liq. 3: Flammable liquids – Category 3	
Flam. Sol. 1: Flammable solids – Category 1	
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
* * Data compared to the previous version altered.	
	EU-EN