

Productname : DIESEL SMOKE STOP CAR Creationdate : 23.05.18 Version : 3.0
 Ref.Nr.: UDS000329_3_20180523 (EN) Replaces: UDS000329_20170629

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DIESEL SMOKE STOP CAR
Bulk

1.2. Relevant identified uses of the substance or mixture and uses advised against

Additives

1.3. Details of the supplier of the safety data sheet

CRC Industries Europe bvba
Touwslagerstraat 1
9240 Zele
Belgium
Tel.: +32(0)52/45.60.11
Fax.: +32(0)52/45.00.34
E-mail : hse@crcind.com

| Subsidiaries | | Tel | Fax |
|---------------------------------|---|-------------------|------------------|
| CRC Industries Finland Oy | Laurinkatu 57 A 23 B, 08100 Lohja | +358/(19)32.921 | |
| CRC Industries France | 6, avenue du marais, C.S. 90028, 95102 Argenteuil Cedex | 01.34.11.20.00 | 01.34.11.09.96 |
| CRC Industries Deutschland GmbH | Südring 9, D-76473 Iffezheim | (07229) 303 0 | (07229)30 32 66 |
| CRC INDUSTRIES IBERIA S.L.U. | GREMIO DEL CUERO-PARC.96, POLIGONO INDUSTRI. DE HONTORIA, 40195 SEGOVIA | 0034/921.427.546 | 0034/921.436.270 |
| CRC Industries Sweden | Laxfiskevägen 16, 433 38 Partille | 0046/31 706 84 80 | 0046/31 27 39 91 |

1.4. Emergency telephone number

CRC Industries Europe, Belgium: Tel.: +32(0)52/45.60.11 (office hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Physical: Not classified
 Classification is based on test data.
Health: Aspiration Hazard Category 1
 May be fatal if swallowed and enters airways.



Productname : DIESEL SMOKE STOP CAR
Ref.Nr.: UDS000329_3_20180523 (EN)
Creationdate : 23.05.18 Version : 3.0
Replaces: UDS000329_20170629

Classification based on calculation method.

Environment: Not classified


Classification based on calculation method.

Other hazards : Repeated exposure may cause skin dryness or cracking.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

Product identifier: Contains:
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Hazard pictogram(s): 

Signal word: Danger

Hazard statement(s): H304 : May be fatal if swallowed and enters airways.

Precautionary statement(s): P102 : Keep out of reach of children.
P301/310 : IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P331 : Do NOT induce vomiting.
P405 : Store locked up.
P501-2 : Dispose of contents/container to an authorised waste collection point.

Supplemental Hazard information: Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.

3.2. Mixtures

| Hazardous ingredient | Registration number | CAS-nr. | EC-nr | w/w % | Hazard Class and Category | Hazard statement | Notes |
|---|---------------------|------------|-------------|-------|--|---------------------|-------|
| Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics | 01-2119456620-43 | - | (926-141-6) | 25-75 | Asp. Tox. 1 | H304 | B,Q |
| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics | 01-2119457273-39 | - | (918-481-9) | 10-25 | Asp. Tox. 1 | H304 | Q |
| 2-ethylhexan-1-ol | 01-2119487289-20 | 104-76-7 | 203-234-3 | <10 | Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3 | H315,H319,H332,H335 | B |
| Distillates (petroleum), hydrotreated heavy paraffinic | 01-2119484627-25 | 64742-54-7 | 265-157-1 | 1-5 | Asp. Tox. 1 | H304 | L |
| Explanation notes | | | | | | | |
| B : substance with national established workplace exposure limit | | | | | | | |

Productname : DIESEL SMOKE STOP CAR **Creationdate :** 23.05.18 Version : 3.0
Ref.Nr.: UDS000329_3_20180523 (EN) **Replaces:** UDS000329_20170629

L : not classified as carcinogen, less than 3% DMSO extract as measured by IP 346

Q : The CAS-no is only an indicative identifier to be used outside the EU for global inventory entries.

(* Explanation phrases : see chapter 16)

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|----------------------------|--|
| Contact with eyes : | If substance has got into eyes, immediately wash out with plenty of water for several minutes Seek medical attention if irritation persists |
| Contact with skin : | Wash with water and soap. Seek medical attention if irritation persists |
| Inhalation : | IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. |
| Ingestion : | IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|-----------------------|--|
| Inhalation : | Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness |
| Ingestion : | After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia. Symptoms : sore throat, abdominal pain, nausea, vomiting |
| Skin contact : | Mildly irritating to skin Symptoms : redness and pain |
| Eye contact : | Mildly irritating to eyes Symptoms : redness and pain |

4.3. Indication of any immediate medical attention and special treatment needed

| | |
|-------------------------|---|
| General Advice : | If you feel unwell, seek medical advice (show the label where possible) If symptoms persist always call a doctor |
|-------------------------|---|

SECTION 5: Firefighting measures

5.1. Extinguishing media

foam, carbon dioxide or dry agent

5.2. Special hazards arising from the substance or mixture

May form explosive vapour/air mixtures
Forms hazardous decomposition products
CO,CO2

5.3. Advice for firefighters



Productname : DIESEL SMOKE STOP CAR **Creationdate :** 23.05.18 Version : 3.0
Ref.Nr.: UDS000329_3_20180523 (EN) **Replaces:** UDS000329_20170629

Keep container(s) exposed to fire cool, by spraying with water
In case of fire, do not breathe fumes

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources
Ensure adequate ventilation
Wear suitable protective clothing including eye/face protection.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/.../equipment.

6.2. Environmental precautions

Do not allow to enter public sewers and watercourses

6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material

6.4. Reference to other sections

For further information see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat and sources of ignition
Take precautionary measures against static discharges
Equipment should be earthed
Use explosion-proof electrical/ventilating/lighting/.../equipment.
Use only non-sparking tools.
Do not breathe aerosols or vapours.
Ensure adequate ventilation
Avoid contact with skin and eyes.
Wash thoroughly after use
Wear protective gloves/protective clothing/eye protection/face protection.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed, in a cool, well ventilated place.
Keep out of reach of children.

7.3. Specific end use(s)

Additives



Productname : DIESEL SMOKE STOP CAR Creationdate : 23.05.18 Version : 3.0
 Ref.Nr.: UDS000329_3_20180523 (EN) Replaces: UDS000329_20170629

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits :

| Hazardous ingredient | CAS-nr. | method | |
|--|----------|--------|-------|
| EU established exposure limits: | | | |
| 2-ethylhexan-1-ol | 104-76-7 | TWA | 1 ppm |

8.2. Exposure controls

| | |
|-------------------------------------|--|
| Control procedures : | Ensure adequate ventilation Keep away from heat and sources of ignition Take precautionary measures against static discharges |
| Personal protection : | Take precautions to avoid contact with skin and eyes when handling the product. It is good practice to wear gloves and to provide adequate ventilation whenever using the product. In all cases handle and use the product in accordance with good industrial hygiene practices. |
| inhalation : | In case of insufficient ventilation, wear suitable respiratory equipment. |
| recommended respiratory protection: | Air purifying respirator equipped with organic gas/vapor cartridge (type A) |
| hands and skin : | Wear suitable protective gloves against chemicals. Check the appropriateness of the recommended gloves for your own particular conditions of use and replace gloves regularly after check for signs of damage or defects. |
| Recommended gloves: | Nitrile |
| eyes : | Wear safety eyewear according to EN 166. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|-----------------------------------|
| Apperance : physical state : | Liquid. |
| colour : | Brown. |
| odour : | Characteristic odor. |
| pH : | Not applicable. |
| Boiling point/range : | Not available. |
| Flash point : | 67 °C (Closed Cup) |
| Evaporation rate : | Not available. |
| Explosion limits : upper limit : | Not available. |
| lower limit : | Not available. |
| Vapour pressure : | Not available. |
| Relative density : | 0.823 g/cm ³ (@ 20°C). |
| Solubility in water : | Insoluble in water |
| Auto-ignition : | Not available. |
| Viscosity : | Not available. |



Productname : DIESEL SMOKE STOP CAR
Ref.Nr.: UDS000329_3_20180523 (EN)
Creationdate : 23.05.18 Version : 3.0
Replaces: UDS000329_20170629

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions known if used for its intended purpose

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

10.4. Conditions to avoid

Avoid overheating

10.5. Incompatible materials

Strong oxidising agent

10.6. Hazardous decomposition products

CO,CO2

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|---|---|
| acute toxicity: | based on available data the classification criteria are not met |
| skin corrosion/irritation: | based on available data the classification criteria are not met |
| serious eye damage/irritation: | based on available data the classification criteria are not met |
| respiratory or skin sensitisation: | based on available data the classification criteria are not met |
| germ cell mutagenicity: | based on available data the classification criteria are not met |
| carcinogenicity: | based on available data the classification criteria are not met |
| toxicity for reproduction: | based on available data the classification criteria are not met |
| STOT-single exposure: | based on available data the classification criteria are not met |
| STOT repeated exposure: | based on available data the classification criteria are not met |
| aspiration hazard: | May be fatal if swallowed and enters airways. |

Information on likely routes of exposure:

Inhalation : Inhalation of solvent vapours may give rise to nausea, headaches and dizziness



Productname : DIESEL SMOKE STOP CAR
Ref.Nr.: UDS000329_3_20180523 (EN)

Creationdate : 23.05.18 Version : 3.0
Replaces: UDS000329_20170629

Ingestion : After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia.
Skin contact : Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis
Eye contact : May cause irritation.

Toxicological data :

| Hazardous ingredient | CAS-nr. | method | |
|---|---------|-----------------|--------------|
| Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics | - | LD50 oral rat | > 5000 mg/kg |
| | | LC50 inhal.rat | >5000 mg/kg |
| | | LD50 derm.rabit | > 5000 mg/kg |

SECTION 12: Ecological information

12.1. Toxicity

Not classified

Ecotoxicological data:

| Hazardous ingredient | CAS-nr. | method | |
|---|---------|--------------|-----------|
| Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics | - | IC50 algae | 1000 mg/l |
| | | LC50 fish | 1000 mg/l |
| | | EC50 daphnia | 1000 mg/l |

12.2. Persistence and degradability

No information available

12.3. Bioaccumulative potential

No information available

12.4. Mobility in soil

Insoluble in water

12.5. Results of PBT and vPvB assessment

No information available

12.6. Other adverse effects

No information available



Productname : DIESEL SMOKE STOP CAR Creationdate : 23.05.18 Version : 3.0
Ref.Nr.: UDS000329_3_20180523 (EN) Replaces: UDS000329_20170629

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product : This material and its container must be disposed of in a safe way.
Do not discharge into drains or the environment, dispose to an authorised waste collection point.
Contaminated packaging : Disposal should be in accordance with local, state or national legislation

SECTION 14: Transport information

14.1. UN number

UN-number : Not classified as hazardous for transport

14.2. UN proper shipping name

Proper shipping name: Not applicable.

14.3. Transport hazard class(es)

Class: Not applicable.
ADR/RID - Classification code: Not applicable.

14.4. Packing group

Packing group: Not applicable.

14.5. Environmental hazards

ADR/RID - Environmentally hazardous: No
IMDG - Marine pollutant: No
IATA/ICAO - Environmentally hazardous: No

14.6. Special precautions for user

IMDG - Ems: Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture



| | |
|--|--|
| Productname : DIESEL SMOKE STOP CAR | Creationdate : 23.05.18 Version : 3.0 |
| Ref.Nr.: UDS000329_3_20180523 (EN) | Replaces: UDS000329_20170629 |

The Safety Data Sheet is compiled according to the current European requirements.
Regulation (EC) No 1907/2006 (REACH)
Regulation (EC) No 1272/2008 (CLP)

15.2. Chemical safety assessment

No information available

SECTION 16: Other information

*Explanation hazard statements: H304 : May be fatal if swallowed and enters airways.
H315 : Causes skin irritation.
H319 : Causes serious eye irritation.
H332 : Harmful if inhaled.
H335 : May cause respiratory irritation.

REVISIONS IN CHAPTRE : Classification according to Regulation (EC) No 1272/2008
Labelling according to Regulation (EC) No 1272/2008
8.2. Exposure controls

acronyms and synonyms: TWA = time weight average
STEL = short time exposure limit
VOC = volatile organic compounds
PBT = persistant bioaccumulative toxic
vPvB = very persitant very bioaccumulative

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.