

Power storage devices - QUINT-BAT/24DC/ 7.2AH - 2866352

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Power storage device, lead AGM, VRLA technology, 24 V DC, 7.2 Ah. Connection via pin cable lug, 14 mm.



Key commercial data

package_quantity	1
GTIN	4017918959753

Technical data

Dimensions

Width	164 mm
Height	156 mm
Depth	110 mm

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 40 °C
Ambient temperature (storage/transport)	0 °C ... 40 °C

Input data

Nominal input voltage	24 V DC
-----------------------	---------

Output data

Nominal output voltage	24 V DC
Output current	max. 50 A
Connection in parallel	Yes, for increasing the buffer period
Connection in series	No
Output fuse	2x 25 A

General

IQ technology	No
Net weight	6 kg
Memory medium	battery 7.2 Ah
Protection class	III
Shipbuilding approval	Germanischer Lloyd (EMC 2), ABS

Power storage devices - QUINT-BAT/24DC/ 7.2AH - 2866352

Technical data

classifications

eCl@ss

eCl@ss 4.0	27040603
eCl@ss 4.1	27040603
eCl@ss 5.0	27040603
eCl@ss 5.1	27040603
eCl@ss 6.0	27040603
eCl@ss 7.0	27040603
eCl@ss 8.0	27040603

ETIM

ETIM 2.0	EC000382
ETIM 3.0	EC000382
ETIM 4.0	EC000382
ETIM 5.0	EC000357

UNSPSC

UNSPSC 6.01	30211510
UNSPSC 7.0901	39121011
UNSPSC 11	39121011
UNSPSC 12.01	39121011
UNSPSC 13.2	39121011

approvals

GL /

Approval details

GL

accessories

Assembly adapter

QUINT-ADAPTER/4 - 2866857



Power storage devices - QUINT-BAT/24DC/ 7.2AH - 2866352

accessories

Fuse

SI FORM C 25 A DIN 72581 - 0913757



Drawings

Block diagram

