## Wiring Ducts and Accessories

3.14

## **Flexible Cable Support**

• Heladuct Flex

## **Features and Benefits**

The Heladuct Flex cable supports are a space-saving wiring system which holds the routed cable clearly open to view. Cables can be routed in or out over the whole length of the support. The supports can be rapidly mounted either with screws or an adhesive strip. The high-quality foam bonding layer smooths over irregularities in the underlying surface and works particularly well on powder-coated surfaces. Due to their flexibility, it is possible to install the supports at angles of 90° and higher.

## Application

Heladuct flexible cable supports are commonly used in switching cabinets. They are also used in the furniture industry, where cables need to be routed rapidly and attractively.



Heladuct Flex- clearly and space-saving arrangement of wiring, even at angles above 90°.

Material Data	
Material	Polypropylene (PP)
Colour	White (WH)
Operating Temperature	-20 °C to +70 °C
Adhesive	Synthetic rubber with base of polyethylene foam
Flammability	UL94 V0 (excluding adhesive)
Specification	
	halogenfree RO

Technical Tab	le					
			No. of Wires			
	_	Ø				Max. load on a length of 500 mm
Article-No.	Туре	D	0.75 mm <sup>2</sup>	1.5 mm²	2.5 mm <sup>2</sup>	at 70 °C (g)
Screwable 0.	5m lengths					
164-11008	Heladuct Flex10	9 x 11	9 x 0.75 mm²	6 x 1.50 mm²	4 x 2.50 mm²	100
164-21008	Heladuct Flex20	20	32 x 0.75 mm <sup>2</sup>	22 x 1.50 mm <sup>2</sup>	14 x 2.50 mm <sup>2</sup>	300
164-31008	Heladuct Flex30	30	67 x 0.75 mm <sup>2</sup>	50 x 1.50 mm <sup>2</sup>	34 x 2.50 mm <sup>2</sup>	650
164-41008	Heladuct Flex40	40	-	81 x 1.50 mm <sup>2</sup>	60 x 2.50 mm <sup>2</sup>	1100
Adhesive 0.5	m lengths					
164-11108	Heladuct Flex10SK	9 x 11	9 x 0.75 mm²	6 x 1.50 mm²	4 x 2.50 mm²	100
164-21108	Heladuct Flex20SK	20	32 x 0.75 mm <sup>2</sup>	22 x 1.50 mm <sup>2</sup>	14 x 2.50 mm <sup>2</sup>	300
164-31108	Heladuct Flex30SK	30	67 x 0.75 mm <sup>2</sup>	50 x 1.50 mm <sup>2</sup>	34 x 2.50 mm <sup>2</sup>	500
164-41108	Heladuct Flex40SK	40	-	81 x 1.50 mm <sup>2</sup>	60 x 2.50 mm <sup>2</sup>	400

All dimensions in mm. Subject to technical changes.



Please note! Not all products listed on this page may have this approval. For product specific approvals please refer to the Appendix.