



**ANGLED FEMALE PLUG WITH FIXING  
FLANGE PIN SPACING 5 MM / 0.197 IN  
100% PROTECTED AGAINST  
MISMATING**

721-106/027-000 TO 721-120/027-000

|   |   |
|---|---|
| <b>ITEM-NO. (ITEM-NO.)</b>                                  | 721-110/027-000   |
| <b>Cross section1 (Cross section / mm<sup>2</sup>)</b>      | 0.08 - 2.5  |
| <b>Cross section2 (Cross section / AWG)</b>                 | 28 - 12   |
| <b>Strip length (Strip length / mm)</b>                     | 8 - 9   |
| <b>Measured voltage (Measured voltage / V)</b>              | 320   |
| <b>Measured shock voltage (Measured shock voltage / kV)</b> | 4   |
| <b>Pollution degree (Pollution degree)</b>                  | 2   |
| <b>Current intensity (Current intensity / A)</b>            | 16  |
| <b>RM (PIN SPACING / mm)</b>                                | 5   |
| <b>P (NO. OF POLES)</b>                                     | 10  |
| <b>Height (Height / mm)</b>                                 | 14.3  |
| <b>Width (Width / mm)</b>                                   | 64.8  |
| <b>Depth (Depth / mm)</b>                                   | 26.45   |
| <b>No. of connection Points (No. of connection Points)</b>  | 10  |
| <b>No. of potentials (No. of potentials)</b>                | 10  |
| <b>COLOR (COLOR)</b>  | lichtgrau   |
| <b>WEIGHT (WEIGHT / g)</b>                                  | 18.84   |
| <b>Comment (Comment)</b>                                    | L1 = (No. of poles x Pin Spacing) + 3 mm   L2 = (No. of poles x Pin Spacing) + 8,8 mm   L3 = (No. of poles x Pin Spacing) + 14,8 mm |