Cable Protection Systems Braided Sleeving

3.15

Standard braided sleeving in dispenser boxes

• Helagaine HLB

Features and Benefits

Helagaine HLB polyester braided sleeving has an expansion ratio of 3:1. With diameters running from 5mm to 54mm, just 3 sizes of the versatile Helagaine HLB covers a very wide range of applications. Large differences in diameter, for instance due to cable jacks and connectors, are easy to handle.


The sleeves are supplied in practical 10m reels in dispenser boxes. The boxes protect the sleeves and can be efficiently stocked. The dispenser opening also guarantees easy extraction of the sleeves.

Application

Helagaine HLB is supplied in practical dispenser boxes and covers a wide range of applications with only a few sizes. It is ideal for both the professional and the home user. Helagaine HLB bundles and effectively protects cables and wires, for instance in HiFi systems and in industrial plants. Helagaine HLB also provides good resistance to abrasion.



Helagaine HLB: The expansion rate makes it possible. Only three sizes in a handy dispenser box for almost all standard diameters.



Helagaine HLB covers a wide range of applications with only three sizes.

To prevent fraying, the sleeve can be cut with the hot cutting tool HSG0, see page 424.

Material Data	
Material	Polyester (PET)
Colour	Black (BK)
Operating Temperature	-50 °C to +150 °C, Intermittent +220 °C
Melting Point	+250 °C
	ROIN

Technical Ta	able	1			
Article-No	. Туре	Ø D	Bundle Ø min.	Bundle Ø max.	Reel Length (m)
170-80150	HLB15	15	5	21	10
170-80250	HLB25	25	10	30	10
170-80350	HLB35	35	18	54	10

All dimensions in mm. Subject to technical changes.