

# Conductor marker carrier - PATG 3/23 - 1013863

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Conductor marker carrier, transparent, Unlabeled, Mounting type: Slide on, Cable diameter: 4-7 mm, Lettering field: 4 x 23 mm

The illustration shows version PATG 0/15

## Product Features

- The corresponding UC-WMT ..., US-WMT ..., and EMT insert labels are used for marking
- The PATG ... collar is a captive marker carrier
- These conductor marking systems consist of marker carriers and insert labels
- Can be used to mark conductors with a diameter of 0.6 ... 50 mm

## Key commercial data

<b>package_quantity</b>	500
<b>GTIN</b>	4017918014056

## Technical data

### Dimensions

<b>Width (a)</b>	23 mm
------------------	-------

### Ambient conditions

<b>Ambient temperature (operation)</b>	-50 °C ... 80 °C
--	------------------

### General

<b>Color</b>	transparent
<b>Components</b>	Silicone-free
<b>Inflammability class according to UL 94</b>	V0
<b>Material</b>	PVC

## classifications

### eCl@ss

<b>eCl@ss 4.0</b>	24190219
<b>eCl@ss 4.1</b>	24190219
<b>eCl@ss 5.0</b>	27149103
<b>eCl@ss 5.1</b>	27141137
<b>eCl@ss 6.0</b>	27141137

## Conductor marker carrier - PATG 3/23 - 1013863

### classifications

#### eCl@ss

<b>eCl@ss 7.0</b>	27141137
<b>eCl@ss 8.0</b>	27141137

#### ETIM

<b>ETIM 2.0</b>	EC000761
<b>ETIM 3.0</b>	EC000761
<b>ETIM 4.0</b>	EC000761
<b>ETIM 5.0</b>	EC001530

#### UNSPSC

<b>UNSPSC 6.01</b>	30211811
<b>UNSPSC 7.0901</b>	39121410
<b>UNSPSC 11</b>	39121410
<b>UNSPSC 12.01</b>	39121410
<b>UNSPSC 13.2</b>	39121410

### Drawings