

Fuse plug - ST-SILA500 - 0920290

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Fuse plug, Nominal current: 6.3 A, Length: 45.4 mm, Width: 9.9 mm, Color: black

The figure shows ST-SILA250

Key commercial data

package_quantity	50
GTIN	4017918010188

Technical data

General

Color	black
Insulating material	PA
Inflammability class according to UL 94	V2

General

Fuse	G / 5 x 20 / 5 x 25 / 5 x 30
Insulating material group	CTI 600
Nominal current I_N	6.3 A
Nominal voltage U_N	400 V

Dimensions

Width	9.9 mm
Length	45.4 mm

classifications

eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141145
eCl@ss 5.1	27141145
eCl@ss 6.0	27141149
eCl@ss 7.0	27141149
eCl@ss 8.0	27141149

ETIM

Fuse plug - ST-SILA500 - 0920290

classifications

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC002018
ETIM 5.0	EC002018

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

approvals

CSA / GOST / GOST /

Approval details

Nominal voltage UN	300 V
Nominal current IN	10 A
mm ² /AWG/kcmil	

--	--

--	--

accessories

Documentation

Fuse plug - ST-SILA500 - 0920290

accessories

ST-IL - 3039900



Drawings

© Phoenix Contact 2013 - all rights reserved
<http://www.phoenixcontact.com>