

Fuse modular terminal block - UK 6,3-HESILED 24 - 3004265

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Fuse terminal block for cartridge fuse insert, cross section: 0.5 - 16 mm², AWG: 26 - 8, width: 10.2 mm, color: black

Product Features

- ☒ Versions with LED
- ☒ Large-surface labeling
- ☒ Safety lever locked in end position

Key commercial data

package_quantity	50
GTIN	4017918090753

Technical data

General

Number of levels	1
Number of connections	2
Color	black
Insulating material	PA
Inflammability class according to UL 94	V2

General

Fuse	G / 6,3 x 32
Fuse type	Glass
Rated surge voltage	6 kV
Pollution degree	3
Surge voltage category	III
Insulating material group	I
Connection in acc. with standard	IEC 60947-7-3
Nominal current I _N	10 A
Nominal voltage U _N	500 V (As a fuse terminal block)
Open side panel	nein

Dimensions

Width	10.2 mm
Length	79 mm

Fuse modular terminal block - UK 6,3-HESILED 24 - 3004265

Technical data

Dimensions

Height NS 35/7,5	60.5 mm
Height NS 35/15	68 mm
Height NS 32	65 mm

Connection data

Conductor cross section solid min.	0.5 mm ²
Conductor cross section solid max.	16 mm ²
Conductor cross section stranded min.	0.5 mm ²
Conductor cross section stranded max.	16 mm ²
Conductor cross section AWG/kcmil min.	20
Conductor cross section AWG/kcmil max	6
Conductor cross section stranded, with ferrule without plastic sleeve min.	0.5 mm ²
Conductor cross section stranded, with ferrule without plastic sleeve max.	10 mm ²
Conductor cross section stranded, with ferrule with plastic sleeve min.	0.5 mm ²
Conductor cross section stranded, with ferrule with plastic sleeve max.	10 mm ²
2 conductors with same cross section, solid min.	0.5 mm ²
2 conductors with same cross section, solid max.	4 mm ²
2 conductors with same cross section, stranded min.	0.5 mm ²
2 conductors with same cross section, stranded max.	4 mm ²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, min.	0.5 mm ²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, max.	4 mm ²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min.	0.5 mm ²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max.	6 mm ²
Cross section with insertion bridge, solid max.	10 mm ²
Cross section with insertion bridge, stranded max.	10 mm ²
Connection method	Screw connection
Stripping length	12 mm
Internal cylindrical gage	B 6
Screw thread	M4
Tightening torque, min	1.2 Nm
Tightening torque max	1.5 Nm

classifications

eCl@ss

eCl@ss 4.0	27141116
eCl@ss 4.1	27141116

Fuse modular terminal block - UK 6,3-HESILED 24 - 3004265

classifications

eCl@ss

eCl@ss 5.0	27141116
eCl@ss 5.1	27141116
eCl@ss 6.0	27141116
eCl@ss 7.0	27141116
eCl@ss 8.0	27141116

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000899
ETIM 4.0	EC000899
ETIM 5.0	EC000899

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410

approvals

CSA / UL Recognized / GOST / LR / GL / GOST /

Approval details

CSA 	
Nominal voltage UN	600 V
Nominal current IN	25 A
mm²/AWG/kcmil	26-8

UL Recognized 	
Nominal voltage UN	600 V
Nominal current IN	10 A
mm²/AWG/kcmil	26-8

Fuse modular terminal block - UK 6,3-HESILED 24 - 3004265

approvals

GOST



LR

GL	
Nominal voltage UN	
Nominal current IN	
mm²/AWG/kcmil	



accessories

Bridge

VS - 3004207



EB 2-10 - 0203153



EB 10-10 - 0203137



Terminal marking

Fuse modular terminal block - UK 6,3-HESILED 24 - 3004265

accessories

SBS10:UNBEDRUCKT - 1007248



ZB 10:UNBEDRUCKT - 1053001



UC-TM 10 - 0818069



UCT-TM 10 - 0829142



Screwdriver tools

SZS 1,0X4,0 VDE - 1205066



Mounting rail

Fuse modular terminal block - UK 6,3-HESILED 24 - 3004265

accessories

NS 32 PERF 2000MM - 1201002



NS 32 UNPERF 2000MM - 1201015



NS 35/ 7,5 PERF 2000MM - 0801733



NS 35/ 7,5 UNPERF 2000MM - 0801681



NS 35/ 7,5 WH PERF 2000MM - 1204119



NS 35/ 7,5 WH UNPERF 2000MM - 1204122



Fuse modular terminal block - UK 6,3-HESILED 24 - 3004265

accessories

NS 35/ 7,5 AL UNPERF 2000MM - 0801704



NS 35/ 7,5 ZN PERF 2000MM - 1206421



NS 35/ 7,5 ZN UNPERF 2000MM - 1206434



NS 35/ 7,5 CU UNPERF 2000MM - 0801762



NS 35/ 7,5 CAP - 1206560



Fuse modular terminal block - UK 6,3-HESILED 24 - 3004265

accessories

NS 35/15 PERF 2000MM - 1201730



NS 35/15 UNPERF 2000MM - 1201714



NS 35/15 WH PERF 2000MM - 0806602



NS 35/15 WH UNPERF 2000MM - 1204135



NS 35/15 AL UNPERF 2000MM - 1201756



NS 35/15 ZN PERF 2000MM - 1206599



Fuse modular terminal block - UK 6,3-HESILED 24 - 3004265

accessories

NS 35/15 ZN UNPERF 2000MM - 1206586



NS 35/15 CU UNPERF 2000MM - 1201895



NS 35/15 CAP - 1206573



NS 35/15-2,3 UNPERF 2000MM - 1201798



Labeled terminal marker

ZB 10 CUS - 0824941



Fuse modular terminal block - UK 6,3-HESILED 24 - 3004265

accessories

UC-TM 10 CUS - 0824605



UCT-TM 10 CUS - 0829623



End block

CLIPFIX 35 - 3022218



CLIPFIX 35-5 - 3022276



E/NS 35 N - 0800886



Fuse modular terminal block - UK 6,3-HESILED 24 - 3004265

accessories

E/UK - 1201442




E/UK 1 - 1201413



Drawings

Fuse modular terminal block - UK 6,3-HESILED 24 - 3004265

Circuit diagram



1 = fixed bridge 2 = insertion bridge

© Phoenix Contact 2013 - all rights reserved
<http://www.phoenixcontact.com>