

Feed-through terminal block - ST 16 BU - 3036152

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Feed-through terminal block, Connection method: Spring-cage connection, Cross section: 0.2 mm² - 25 mm², AWG: 24 - 4, Width: 12.2 mm, Color: blue, Mounting type: NS 35/7,5, NS 35/15

Product Features

- ✓ The double bridge shaft not only enables individual chain bridging, but also reducing bridging to spring-cage terminal blocks with smaller cross sections
- ✓ The flexible options for reducing bridging in the CLIPLINE complete system can be found in "Accessories for the CLIPLINE complete modular terminal block system"



Key commercial data

package_quantity	50
GTIN	4017918821081

Technical data

General

Number of levels	1
Number of connections	2
Color	blue
Insulating material	PA
Inflammability class according to UL 94	V0

General

Maximum load current	90 A (with 25 mm ² conductor cross section)
Rated surge voltage	8 kV
Pollution degree	3
Surge voltage category	III
Insulating material group	I
Connection in acc. with standard	IEC 60947-7-1
Nominal current I _N	76 A
Nominal voltage U _N	1000 V
Open side panel	ja

Dimensions

Feed-through terminal block - ST 16 BU - 3036152

Technical data

Dimensions

Width	12.2 mm
Length	80 mm
Height NS 35/7,5	51.5 mm
Height NS 35/15	59 mm

Connection data

Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	25 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	4
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	16 mm ²
Min. AWG conductor cross section, stranded	24
Max. AWG conductor cross section, stranded	6
Conductor cross section stranded, with ferrule without plastic sleeve min.	0.25 mm ²
Conductor cross section stranded, with ferrule without plastic sleeve max.	16 mm ²
Conductor cross section stranded, with ferrule with plastic sleeve min.	0.25 mm ²
Conductor cross section stranded, with ferrule with plastic sleeve max.	16 mm ²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min.	1.5 mm ²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max.	4 mm ²
Connection method	Spring-cage connection
Stripping length	18 mm
Internal cylindrical gage	A7

classifications

eCl@ss

eCl@ss 4.0	27141121
eCl@ss 4.1	27141121
eCl@ss 5.0	27141120
eCl@ss 5.1	27141120
eCl@ss 6.0	27141120
eCl@ss 7.0	27141120
eCl@ss 8.0	27141120

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC000897

Feed-through terminal block - ST 16 BU - 3036152

classifications

ETIM

ETIM 5.0	EC000897
-----------------	----------

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410

approvals

IECEX / ATEX / CSA / UL Recognized / VDE Gutachten mit Fertigungsüberwachung / cUL Recognized / GOST / LR / GL / BV / DNV / KR / NK / IECCEB Scheme / GOST / VDE Gutachten mit Fertigungsüberwachung / IECCEB Scheme / cULus Recognized /

Approval details

IECEX	
Nominal voltage UN	550 V
Nominal current IN	65 A
mm ² /AWG/kcmil	1.5-16

ATEX 	
Nominal voltage UN	550 V
Nominal current IN	82 A
mm ² /AWG/kcmil	1.5-25

CSA 		
Usegroups	B	C
Nominal voltage UN	600 V	600 V
Nominal current IN	85 A	85 A
mm ² /AWG/kcmil	16-4	16-4

UL Recognized 
--

Feed-through terminal block - ST 16 BU - 3036152

approvals

Usegroups	B	C
Nominal voltage UN	600 V	600 V
Nominal current IN	85 A	85 A
mm²/AWG/kcmil	16-4	16-4

VDE Gutachten mit Fertigungsüberwachung 	
Nominal voltage UN	800 V
Nominal current IN	76 A
mm²/AWG/kcmil	1.5-16

cUL Recognized 		
Usegroups	B	C
Nominal voltage UN	600 V	600 V
Nominal current IN	85 A	85 A
mm²/AWG/kcmil	16-4	16-4

GOST 
--

LR

GL	
Nominal voltage UN	800 V
Nominal current IN	76 A
mm²/AWG/kcmil	16

BV

DNV


KR

NK

Feed-through terminal block - ST 16 BU - 3036152

approvals

IECEE CB Scheme 	
Nominal voltage UN	800 V
Nominal current IN	76 A
mm²/AWG/kcmil	1.5-16



	
Nominal voltage UN	800 V
Nominal current IN	76 A
mm²/AWG/kcmil	1.5-16

CB 	
Nominal voltage UN	800 V
Nominal current IN	
mm²/AWG/kcmil	16

cULus Recognized  US	
---	--

accessories

End cover

D-ST 16 - 3036657



Feed-through terminal block - ST 16 BU - 3036152

accessories

Screwdriver tools

SZF 3-1,0X5,5 - 1206612



Labeled terminal marker

WST 10/35 - 3030006



ZB 12 CUS - 0824942



UC-TM 12 CUS - 0824613



UCT-TM 12 CUS - 0829630



Feed-through terminal block - ST 16 BU - 3036152

accessories

ZBF 12 CUS - 0825018



UC-TMF 12 CUS - 0824670



UCT-TMF 12 CUS - 0829686



Documentation

ST-IL - 3039900



Bridge

FBS 2-12 - 3005950



Feed-through terminal block - ST 16 BU - 3036152

accessories

RB ST 16-(2,5/4) - 3030886



Mounting rail

NS 35/ 7,5 PERF 2000MM - 0801733



NS 35/ 7,5 UNPERF 2000MM - 0801681



NS 35/ 7,5 WH PERF 2000MM - 1204119



NS 35/ 7,5 WH UNPERF 2000MM - 1204122



Feed-through terminal block - ST 16 BU - 3036152

accessories

NS 35/ 7,5 AL UNPERF 2000MM - 0801704



NS 35/ 7,5 ZN PERF 2000MM - 1206421



NS 35/ 7,5 ZN UNPERF 2000MM - 1206434



NS 35/ 7,5 CU UNPERF 2000MM - 0801762



NS 35/ 7,5 CAP - 1206560



Terminal marking

Feed-through terminal block - ST 16 BU - 3036152

accessories

ZB 12:UNPRINTED - 0812120



UC-TM 12 - 0819194



UCT-TM 12 - 0829144



ZBF 12:UNBEDRUCKT - 0809735



UC-TMF 12 - 0819233



UCT-TMF 12 - 0829214



Feed-through terminal block - ST 16 BU - 3036152

accessories

Test plug terminal block

MPS-MT - 0201744



Insulating sleeve

MPS-IH WH - 0201663



MPS-IH RD - 0201676



MPS-IH BU - 0201689



MPS-IH YE - 0201692



Feed-through terminal block - ST 16 BU - 3036152

accessories

MPS-IH GN - 0201702



MPS-IH GY - 0201728



MPS-IH BK - 0201731



Drawings

Circuit diagram



© Phoenix Contact 2013 - all rights reserved
<http://www.phoenixcontact.com>