

High Current Connectors - HV M6/1 - 3049204

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



High Current Connectors, Connection method: Bolt connection, Cross section: 2.5 mm² - 35 mm², AWG: 14 - 2, Width: 16 mm, Height: 55 mm, Color: gray, Mounting type: NS 35/7,5, NS 35/15

Product Features

- ✓ Comprehensive, supplementary accessories
- ✓ For connecting up to four conductors

Key commercial data

package_quantity	25
GTIN	4046356184038

Technical data

General

Number of levels	1
Number of connections	1
Color	gray
Insulating material	PA
Inflammability class according to UL 94	V0

General

Rated surge voltage	8 kV
Pollution degree	3
Surge voltage category	III
Insulating material group	I
Connection in acc. with standard	IEC 60947-7-1
Nominal current I _N	125 A
Nominal voltage U _N	1000 V
Open side panel	nein

Dimensions

Length	67 mm
Width	16 mm
Height	55 mm
Height NS 35/7,5	58 mm
Height NS 35/15	65.5 mm

High Current Connectors - HV M6/1 - 3049204

Technical data

Connection data

Conductor cross section solid min.	2.5 mm ²
Conductor cross section solid max.	35 mm ²
Conductor cross section stranded min.	2.5 mm ²
Conductor cross section stranded max.	35 mm ²
Conductor cross section AWG/kcmil min.	14
Conductor cross section AWG/kcmil max	2
Screw thread	M6
Tightening torque, min	3 Nm
Tightening torque max	6 Nm
Connection method	Bolt connection
Connection in acc. with standard	DIN 46 234
Min. cross section	2.5 mm ²
Max. cross section	35 mm ²
Bolt diameter	6 mm
Tightening torque, min	3 Nm
Tightening torque max	6 Nm
Connection in acc. with standard	DIN 46,235
Min. cross section	6 mm ²
Max. cross section	35 mm ²
Bolt diameter	6 mm
Tightening torque, min	3 Nm
Tightening torque max	6 Nm

classifications

eCl@ss

eCl@ss 4.0	27141120
eCl@ss 4.1	27141120
eCl@ss 5.0	27141120
eCl@ss 5.1	27141120
eCl@ss 6.0	27141120
eCl@ss 7.0	27141120
eCl@ss 8.0	27141120

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC000897
ETIM 5.0	EC000897

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410

High Current Connectors - HV M6/1 - 3049204

classifications

UNSPSC

UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410

approvals

GOST / CSA / CSAus / GOST / cCSAus /

Approval details

GOST 

CSA 	
Nominal voltage UN	1000 V
Nominal current IN	115 A
mm²/AWG/kcmil	4

CSAus	
Nominal voltage UN	1000 V
Nominal current IN	115 A
mm²/AWG/kcmil	4



cCSAus

accessories

Bridge

High Current Connectors - HV M6/1 - 3049204

accessories

HV M6/1-VS 2 - 3049262



HV M6/1-VS 3 - 3049275



Mounting rail

NS 35/ 7,5 PERF 2000MM - 0801733



NS 35/ 7,5 UNPERF 2000MM - 0801681



NS 35/ 7,5 WH PERF 2000MM - 1204119



High Current Connectors - HV M6/1 - 3049204

accessories

NS 35/ 7,5 WH UNPERF 2000MM - 1204122



NS 35/ 7,5 AL UNPERF 2000MM - 0801704



NS 35/ 7,5 ZN PERF 2000MM - 1206421



NS 35/ 7,5 ZN UNPERF 2000MM - 1206434



NS 35/ 7,5 CU UNPERF 2000MM - 0801762



NS 35/ 7,5 CAP - 1206560



High Current Connectors - HV M6/1 - 3049204

accessories

Drawings

© Phoenix Contact 2013 - all rights reserved
<http://www.phoenixcontact.com>