

## PCB terminal block - PT 1,5/ 4-3,5-V - 1984785

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



PCB terminal block, Nominal current: 17.5 A, Nom. voltage: 200 V, Pitch: 3.5 mm, Number of positions: 4, Connection method: Screw connection, Mounting: Soldering, Conductor/PCB connection direction: 90 °, Color: green

The figure shows a 10-position version of the product

### Product Features

- ✓ 3.5 mm pitch
- ✓ Large terminal block capacity thanks to rectangular clamping space
- ✓ Rugged version with high current carrying capacity
- ✓ Highly flexible conductor protection for easy, repeated connection
- ✓ Plus/minus screw

### Key commercial data

|                  |               |
|------------------|---------------|
| package_quantity | 250           |
| GTIN             | 4017918946333 |

### Technical data

#### Dimensions

|                |         |
|----------------|---------|
| Length         | 9 mm    |
| Height         | 7.6 mm  |
| Pitch          | 3.5 mm  |
| Dimension a    | 10.5 mm |
| Pin dimensions | 0,9 mm  |
| Pin spacing    | 3.5 mm  |
| Hole diameter  | 1.2 mm  |

#### General

|                                  |             |
|----------------------------------|-------------|
| Range of articles                | PT 1,5/..-V |
| Insulating material group        | I           |
| Rated surge voltage (III/3)      | 2.5 kV      |
| Rated surge voltage (III/2)      | 2.5 kV      |
| Rated surge voltage (II/2)       | 2.5 kV      |
| Rated voltage (III/3)            | 160 V       |
| Rated voltage (III/2)            | 200 V       |
| Rated voltage (II/2)             | 400 V       |
| Connection in acc. with standard | EN-VDE      |

# PCB terminal block - PT 1,5/ 4-3,5-V - 1984785

## Technical data

### General

|                                         |                     |
|-----------------------------------------|---------------------|
| Nominal current $I_N$                   | 17.5 A              |
| Nominal cross section                   | 1.5 mm <sup>2</sup> |
| Maximum load current                    | 17.5 A              |
| Insulating material                     | PA                  |
| Solder pin surface                      | Sn                  |
| Inflammability class according to UL 94 | V0                  |
| Stripping length                        | 5 mm                |
| Number of positions                     | 4                   |
| Screw thread                            | M2                  |
| Tightening torque, min                  | 0.22 Nm             |
| Tightening torque max                   | 0.25 Nm             |

### Connection data

|                                                                         |                      |
|-------------------------------------------------------------------------|----------------------|
| Conductor cross section solid min.                                      | 0.14 mm <sup>2</sup> |
| Conductor cross section solid max.                                      | 1.5 mm <sup>2</sup>  |
| Conductor cross section stranded min.                                   | 0.2 mm <sup>2</sup>  |
| Conductor cross section stranded max.                                   | 1.5 mm <sup>2</sup>  |
| Conductor cross section stranded, with ferrule with plastic sleeve min. | 0.25 mm <sup>2</sup> |
| Conductor cross section stranded, with ferrule with plastic sleeve max. | 0.75 mm <sup>2</sup> |
| Conductor cross section AWG/kcmil min.                                  | 26                   |
| Conductor cross section AWG/kcmil max                                   | 16                   |
| 2 conductors with same cross section, solid min.                        | 0.2 mm <sup>2</sup>  |
| 2 conductors with same cross section, solid max.                        | 0.34 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded min.                     | 0.2 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded max.                     | 0.5 mm <sup>2</sup>  |
| Minimum AWG according to UL/CUL                                         | 26                   |
| Maximum AWG according to UL/CUL                                         | 16                   |

## classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27141109 |
| eCl@ss 5.0 | 27141190 |
| eCl@ss 5.1 | 27141190 |
| eCl@ss 6.0 | 27261101 |
| eCl@ss 7.0 | 27440401 |
| eCl@ss 8.0 | 27440401 |

### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001121 |
|----------|----------|

# PCB terminal block - PT 1,5/ 4-3,5-V - 1984785

## classifications

### ETIM

|                 |          |
|-----------------|----------|
| <b>ETIM 4.0</b> | EC002643 |
| <b>ETIM 5.0</b> | EC002643 |

### UNSPSC

|                      |          |
|----------------------|----------|
| <b>UNSPSC 6.01</b>   | 30211801 |
| <b>UNSPSC 7.0901</b> | 39121432 |
| <b>UNSPSC 11</b>     | 34131203 |
| <b>UNSPSC 12.01</b>  | 39121432 |
| <b>UNSPSC 13.2</b>   | 39121432 |

## approvals

UL Recognized / SEV / cUL Recognized / CCA / GOST / GOST / cULus Recognized /

### Approval details

| <b>UL Recognized</b>  |       |       |
|----------------------------------------------------------------------------------------------------------|-------|-------|
| Usegroups                                                                                                | B     | D     |
| Nominal voltage UN                                                                                       | 300 V | 300 V |
| Nominal current IN                                                                                       | 10 A  | 10 A  |
| mm²/AWG/kcmil                                                                                            | 26-16 | 26-16 |

|                    |       |
|--------------------|-------|
| <b>SEV</b>         |       |
| Nominal voltage UN | 160 V |
| Nominal current IN | 10 A  |
| mm²/AWG/kcmil      | 1.5   |

| <b>cUL Recognized</b>  |       |       |
|-----------------------------------------------------------------------------------------------------------|-------|-------|
| Usegroups                                                                                                 | B     | D     |
| Nominal voltage UN                                                                                        | 300 V | 300 V |
| Nominal current IN                                                                                        | 10 A  | 10 A  |
| mm²/AWG/kcmil                                                                                             | 26-16 | 26-16 |

|                    |       |
|--------------------|-------|
| <b>CCA</b>         |       |
| Nominal voltage UN | 160 V |
| Nominal current IN | 10 A  |

# PCB terminal block - PT 1,5/ 4-3,5-V - 1984785

## approvals

|               |     |
|---------------|-----|
|               |     |
| mm²/AWG/kcmil | 1.5 |



## accessories

### Screwdriver tools

SZS 0,4X2,5 VDE - 1205037



---

### Labeled terminal marker

SK 3,5/2,8:FORTL.ZAHLEN - 0804073



---

## accessories


SK 3,5/2,8:SO - 0805030



## PCB terminal block - PT 1,5/ 4-3,5-V - 1984785


### Drawings

#### Drilling diagram



## PCB terminal block - PT 1,5/ 4-3,5-V - 1984785

Diagram



Derating diagram for 5 pins; reduction factor=1

Dimensioned drawing

