

# Plug-in module - LDP-110DC - 2833673

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Plug-in module, for mounting on PR1 and PR2, with damping diode and yellow LED, polarity:: A1+, A2-, input voltage: 110 V DC  $\pm$  20%

## Product Features

- Mechanical coding to protect against mismatching
- Attenuation of reverse voltage induced in coil

## Key commercial data

<b>package_quantity</b>	10
<b>GTIN</b>	4017918933869

## Technical data

### General

<b>Nominal voltage <math>U_N</math></b>	110 V DC
---	----------

## classifications

### eCl@ss

<b>eCl@ss 4.0</b>	27371190
<b>eCl@ss 4.1</b>	27371190
<b>eCl@ss 5.0</b>	27371692
<b>eCl@ss 5.1</b>	27371692
<b>eCl@ss 6.0</b>	27371603
<b>eCl@ss 7.0</b>	27371603
<b>eCl@ss 8.0</b>	27371603

### ETIM

<b>ETIM 2.0</b>	EC001456
<b>ETIM 3.0</b>	EC001456
<b>ETIM 4.0</b>	EC001456
<b>ETIM 5.0</b>	EC001456

### UNSPSC

<b>UNSPSC 6.01</b>	30211917
<b>UNSPSC 7.0901</b>	39121516
<b>UNSPSC 11</b>	39121516

# Plug-in module - LDP-110DC - 2833673

## classifications

### UNSPSC

UNSPSC 12.01	39121516
UNSPSC 13.2	39121516



## approvals

---

UL Recognized / cUL Recognized / cULus Recognized /

---

### Approval details



## Drawings

# Plug-in module - LDP-110DC - 2833673

Circuit diagram

