

## Label - EML (40X25)R - 0818027

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Label, Roll, white, Unlabeled, Can be labeled with: THERMOMARK ROLL, THERMOMARK X, THERMOMARK S1.1, Mounting type: Adhesive, Lettering field: 40 x 25 mm

### Product Features

- ✓ A wide range of marker sizes and colors are available for custom designs
- ✓ Precise printing quality and good adhesive properties
- ✓ If high-quality ink ribbons are used, the labeling is resistant to solvents and suitable for use even under harsh industrial conditions
- ✓ The EML ... materials are UL-listed
- ✓ The special packaging protects rolls that have already been started from the dirt found in industrial environments
- ✓ The EML ... self-adhesive device markers have been specifically developed for marking various types of operating equipment in control, system, and control cabinet engineering

### Key commercial data

|                  |               |
|------------------|---------------|
| package_quantity | 1             |
| GTIN             | 4046356124485 |

### Technical data

#### Dimensions

|            |       |
|------------|-------|
| Length (b) | 40 mm |
| Width (a)  | 25 mm |

#### Ambient conditions

|                                 |                                                                                         |
|---------------------------------|-----------------------------------------------------------------------------------------|
| Wipe resistance                 | DIN EN 61010-1 (VDE 0411-1)                                                             |
| Ambient temperature (operation) | -40 °C ... 150 °C                                                                       |
| Ambient temperature (assembly)  | > 5 °C                                                                                  |
| Recommended storage conditions  | 21 °C / 50% relative humidity. Storage in poly bags is recommended prior to processing. |

#### General

|                                     |                                |
|-------------------------------------|--------------------------------|
| Color                               | white                          |
| Components                          | free from silicone and halogen |
| Material                            | Polyester                      |
| Number of individual labels         | 1000                           |
| Number of individual labels per row | 2                              |
| RoHS compliant                      | Yes                            |
| Adhesive                            | Acrylic                        |

## Label - EML (40X25)R - 0818027

### Technical data

#### General

|                                                                            |                                     |
|----------------------------------------------------------------------------|-------------------------------------|
| <b>Printability</b>                                                        | Thermal transfer                    |
| <b>Test for substances that would hinder coating with paint or varnish</b> | VW PV 3.10.7:2005-02                |
| <b>Result</b>                                                              | Test passed                         |
| <b>Test specification weathering-resistance</b>                            | Following ISO 4892-2:2013-03        |
| <b>Test duration</b>                                                       | 96 h                                |
| <b>Wipe resistance test result</b>                                         | Test passed                         |
| <b>Salt spray test specification</b>                                       | DIN EN 60068-2-11:2000-02           |
| <b>Test duration</b>                                                       | 96 h                                |
| <b>Salt spray testing result</b>                                           | Test passed                         |
| <b>Alternating condensation climate with SO2 test specification</b>        | Following DIN 50018:2013-05         |
| <b>Climate level</b>                                                       | AHT 1.0 S                           |
| <b>Cycles</b>                                                              | 2                                   |
| <b>Condensation test result</b>                                            | Test passed                         |
| <b>Wipe resistance of test specification inscriptions</b>                  | DIN EN 61010-1 (VDE 0411-1):2011-07 |
| <b>Result</b>                                                              | Test passed                         |
| <b>Foil strength</b>                                                       | 50 µm                               |
| <b>Adhesive strength</b>                                                   | 20 µm                               |

### classifications

#### eCl@ss

|                   |          |
|-------------------|----------|
| <b>eCl@ss 4.0</b> | 24190219 |
| <b>eCl@ss 4.1</b> | 24190219 |
| <b>eCl@ss 5.0</b> | 27149103 |
| <b>eCl@ss 5.1</b> | 27141137 |
| <b>eCl@ss 6.0</b> | 27141137 |
| <b>eCl@ss 7.0</b> | 27141137 |
| <b>eCl@ss 8.0</b> | 27141137 |

#### ETIM

|                 |          |
|-----------------|----------|
| <b>ETIM 2.0</b> | EC000761 |
| <b>ETIM 3.0</b> | EC000761 |
| <b>ETIM 4.0</b> | EC000761 |
| <b>ETIM 5.0</b> | EC000761 |

#### UNSPSC

|                      |          |
|----------------------|----------|
| <b>UNSPSC 6.01</b>   | 30211811 |
| <b>UNSPSC 7.0901</b> | 39121410 |
| <b>UNSPSC 11</b>     | 39121410 |
| <b>UNSPSC 12.01</b>  | 39121410 |
| <b>UNSPSC 13.2</b>   | 39121410 |

## Label - EML (40X25)R - 0818027

### approvals

---

UL Recognized /

---

#### Approval details

UL Recognized 

### accessories

#### Ink ribbon

THERMOMARK-RIBBON 110 - 5145384



---

### Drawings

© Phoenix Contact 2013 - all rights reserved  
<http://www.phoenixcontact.com>