

Plug-in bridge - FBS-PV - 3032185

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Vertical potential bridge, to connect the upper and lower level

Key commercial data

package_quantity	50
GTIN	4046356052566

Technical data

Technical data

Color	black
Material	PA 6.6
Maximum load current	32 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.)
Inflammability class according to UL 94	V0
Maximum temperature	125 °C

classifications

eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141140
eCl@ss 5.1	27141140
eCl@ss 6.0	27141140
eCl@ss 7.0	27141140
eCl@ss 8.0	27141140

ETIM

ETIM 2.0	EC000489
ETIM 3.0	EC000489
ETIM 4.0	EC000489
ETIM 5.0	EC000489

UNSPSC

UNSPSC 6.01	30211829
--------------------	----------

Plug-in bridge - FBS-PV - 3032185

classifications

UNSPSC

UNSPSC 7.0901	39121426
UNSPSC 11	39121426
UNSPSC 12.01	39121426
UNSPSC 13.2	39121426

Drawings

© Phoenix Contact 2013 - all rights reserved
<http://www.phoenixcontact.com>