

Application

- Horizontal and building backbone cable.
- Support current and future **Category 5 enhanced** applications, such as: 10 Base-T, 100 Base-T, 1000 Base-T (*Gigabit Ethernet*), FDDI, ATM

Standards

General standards: **ISO/IEC 11801, EN 50173, TSB 36, TIA/EIA 568-A-5 (enhanced)**
Future standards like: JTC1 SC25 WG3 N568 and prEN 50288-3-1

Construction & Dimensions

- Construction: Unshielded 4 twisted pairs
- Conductor: solid bare copper
- Conductor diameter: AWG 24 (0,51 mm)
- Conductor insulation material: Polyethylene (PE)
- Diameter over insulation: 0,90 mm ± 0.05 mm
- Jacket material: FRNC (Flame retardant)
- Outer diameter: 4,70 mm ± 0.30 mm



Colour code

Pair 1	White-Blue/Blue
Pair 2	White-Orange/Orange
Pair 3	White-Green/Green
Pair 4	White-Brown/Brown

Electrical characteristics (at 20 °C)

Attenuation

Frequency	1	4	10	16	20	31.25	62.5	100	MHz
Spec. (Max.) ¹⁾	2.1	4.3	6.6	8.2	9.2	11.8	17.1	22.0	dB/100m
Typical	2.0	4.0	6.3	8.0	9.0	11.3	16.2	20.7	dB/100m

NEXT (Near end crosstalk)

Frequency	1	4	10	16	20	31.25	62.5	100	MHz
Spec. (Min.) ¹⁾	65.3	56.3	50.3	47.3	45.8	42.9	38.4	35.3	dB
Typical	73	64	58	55	54	51	47	44	dB

Power sum NEXT

Frequency	1	4	10	16	20	31.25	62.5	100	MHz
Spec. (Min.) ¹⁾	62.3	53.3	47.3	44.3	42.8	39.9	35.4	32.3	dB/100m
Typical	71	62	56	53	52	49	45	42	dB/100m

Power sum ELFEXT

Frequency	1	4	10	16	20	31.25	62.5	100	MHz
Spec. (Min.) ²⁾	60.8	48.7	40.8	36.7	34.7	30.9	24.8	20.8	dB/100m
Typical	71	59	51	46	43	39	33	28	dB/100m

ACR

Frequency	1	4	10	16	20	31.25	62.5	100	MHz
Spec. (Min.) ¹⁾	63	52	44	39	37	31	22	14	dB/100m
Typical	71	61	52	48	45	40	31	24	dB/100m

Power sum ACR

Frequency	1	4	10	16	20	31.25	62.5	100	MHz
Spec. (Min.) ¹⁾	60	49	41	36	34	28	19	11	dB/100m
Typical	69	59	50	46	43	38	29	22	dB/100m

¹⁾: Specification values according to cable requirements of ISO/IEC 11801 category 5 enhanced

²⁾: Specification values according to cable requirements of ANSI/TIA/EIA-568-A-5 (enhanced)

Electrical characteristics (at 20 °C)

Nominal mutual capacitance at 1 kHz	50 nF/km
Maximum conductor DCR	93.5 Ohm/km
NVP - Nominal Velocity of Propagation	0.68 c
SKEW – Propagation delay difference (100 MHz)	Typical ≤ 10 ns/100m
Impedance 1-100 MHz	100 ± 15 Ohm

General and environmental characteristics

Temperature range - operation	-20°C - +60°C
Temperature range - installation	+0°C - +50°C
Minimum bending radius - operation	19 mm
Minimum bending radius - installation	38 mm
Maximum pulling tension	80 N
Flame retardancy	IEC 332-1
Energy of flame	250 kJ/m
Weight (approx.)	28 kg/km
Maximum operating voltage	48 V rms
Maximum continuous current per conductor (25°C)	1.4 A

Ordering information

MARKING

Text on the cable jacket Inkjet printing

**BELDEN 1583ENH UTP CAT5E 4PR AWG24 LSNH ISO/IEC 11801 EN50173
VERIFIED 100 OHM**

Meter marking: Yes
Production date marking: Yes

JACKET COLOUR

Colour	RAL code
Grey	RAL 7032
Blue	RAL 5015
Red	RAL 3000
Green	RAL 6018
Yellow	RAL 1018
Orange	RAL 2003